

---

# **HPy**

***Release 0.9***

**HPy Collective**

**May 02, 2023**



# CONTENTS

<b>1</b>	<b>Where to go next:</b>	<b>3</b>
<b>2</b>	<b>Full table of contents:</b>	<b>5</b>
2.1	HPy Quickstart . . . . .	5
2.2	HPy Overview . . . . .	6
2.3	HPy API Introduction . . . . .	12
2.4	Porting Guide . . . . .	22
2.5	Porting Example . . . . .	33
2.6	Debug Mode . . . . .	41
2.7	Trace Mode . . . . .	44
2.8	API Reference . . . . .	45
2.9	Contributing . . . . .	109
2.10	Misc Notes . . . . .	109
2.11	Changelog . . . . .	110
<b>3</b>	<b>Indices and tables</b>	<b>115</b>
	<b>Index</b>	<b>117</b>



HPy provides a new API for extending Python in C.

There are several advantages to writing C extensions in HPy:

- **Speed:** it runs much faster on PyPy, GraalPy, and at native speed on CPython
- **Deployment:** it is possible to compile a single binary which runs unmodified on all supported Python implementations and versions – think “stable ABI” on steroids
- **Simplicity:** it is simpler and more manageable than the `Python.h` API, both for the users and the Pythons implementing it
- **Debugging:** it provides an improved debugging experience. Debug mode can be turned on at runtime without the need to recompile the extension or the Python running it. HPy design is more suitable for automated checks.

The official [Python/C API](#), also informally known as `#include <Python.h>`, is specific to the current implementation of CPython: it exposes a lot of internal details which makes it hard to:

- implement it for other Python implementations (e.g. PyPy, GraalPy, Jython, ...)
- experiment with new approaches inside CPython itself, for example:
  - use a tracing garbage collection instead of reference counting
  - remove the global interpreter lock (GIL) to take full advantage of multicore architectures
  - use tagged pointers to reduce memory footprint



## WHERE TO GO NEXT:

- Show me the code:
  - *Quickstart*
  - *Simple documented HPy extension example*
  - *Tutorial: porting Python/C API extension to HPy*
- Details:
  - *HPy overview: motivation, goals, current status*
  - *HPy API concepts introduction*
  - *Python/C API to HPy Porting guide*
  - *HPy API reference*





## FULL TABLE OF CONTENTS:

### 2.1 HPy Quickstart

This section shows how to quickly get started with HPy by creating a simple HPy extension from scratch.

Install HPy:

```
python3 -m pip install git+https://github.com/hpyproject/hpy.git#egg=hpy.universal
```

Create a new directory for the new HPy extension. Location and name of the directory do not matter. Add the following two files:

```
// quickstart.c

// This header file is the entrypoint to the HPy API:
#include "hpy.h"

// HPy method: the HPyDef_METH macro generates some boilerplate code,
// the same code can be also written manually if desired
HPyDef_METH(say_hello, "say_hello", HPyFunc_NOARGS)
static HPy say_hello_impl(HPyContext *ctx, HPy self)
{
    // Methods take HPyContext, which must be passed as the first argument to
    // all HPy API functions. Other than that HPyUnicode_FromString does the
    // same thing as PyUnicode_FromString.
    //
    // HPy type represents a "handle" to a Python object, but may not be
    // a pointer to the object itself. It should be fully "opaque" to the
    // users. Try uncommenting the following two lines to see the difference
    // from PyObject*:
    //
    // if (self == self)
    //     HPyUnicode_FromString(ctx, "Surprise? Try HPy_Is(ctx, self, self)");

    return HPyUnicode_FromString(ctx, "Hello world");
}

static HPyDef *QuickstartMethods[] = {
    &say_hello, // 'say_hello' generated for us by the HPyDef_METH macro
    NULL,
};

static HPyModuleDef quickstart_def = {
    .doc = "HPy Quickstart Example",
```

(continues on next page)

(continued from previous page)

```

        .defines = QuickstartMethods,
    };

    // The Python interpreter will create the module for us from the
    // HPyModuleDef specification. Additional initialization can be
    // done in the HPy_mod_execute slot
    HPy_MODINIT(quickstart, quickstart_def)

```

```

# setup.py

from setuptools import setup, Extension
from os import path

DIR = path.dirname(__file__)
setup(
    name="hpy-quickstart",
    hpy_ext_modules=[
        Extension('quickstart', sources=[path.join(DIR, 'quickstart.c')]),
    ],
    setup_requires=['hpy'],
)

```

Build the extension:

```
python3 setup.py --hpy-abi=universal develop
```

Try it out – start Python console in the same directory and type:

```

import quickstart
assert quickstart.say_hello() == "Hello world"

```

Notice the shared library that was created by running `setup.py`:

```

> ls *.so
quickstart.hpy0.so

```

It does not have Python version encoded in it. If you happen to have GraalPy or PyPy installation that supports given HPy version, you can try running the same extension on it. For example, start `$GRAALVM_HOME/bin/graalpy` in the same directory and type the same Python code: the extension should load and work just fine.

Where to go next?

- *Simple documented HPy extension example*
- *Tutorial: porting Python/C API extension to HPy*

## 2.2 HPy Overview

### 2.2.1 Motivation and goals

The superpower of the Python ecosystem is its libraries, which are developed by users. Over time, these libraries have grown in number, quality, and applicability. While it is possible to write python libraries entirely in python, many of them, especially in the scientific community, are written in C and exposed to Python using the [Python.h API](#). The existence of these C extensions using the `Python.h` API leads to some issues:

1. Usually, alternative implementation of the Python programming language want to support C extensions. To do so, they must implement the same `Python.h` API or provide a compatibility layer.
2. CPython developers cannot experiment with new designs or refactoring without breaking compatibility with existing extensions.

Over the years, it has become evident that emulating `Python.h` in an efficient way is **challenging, if not impossible**. To summarize, it is mainly due to leaking of implementation details of CPython into the C/API - which makes it difficult to make different design choices than those made by CPython. As such - the main goal of HPy is to provide a **C API which makes as few assumptions as possible about the design decisions of any implementation of Python, allowing diverse implementations to support it efficiently and without compromise**. In particular, **reference counting is not part of the API**: we want a more generic way of managing resources that is possible to implement with different strategies, including the existing reference counting and/or with a moving *Garbage Collector* (like the ones used by PyPy, GraalPy or Java, for example). Moreover, each implementation can experiment with new memory layout of objects, add optimizations, etc. The following is a list of sub-goals.

**Performance on CPython** HPy is usable on CPython from day 1 with no performance impact compared to the existing `Python.h` API.

**Incremental adoption** It is possible to port existing C extensions piece by piece and to use the old and the new API side-by-side during the transition.

**Easy migration** It should be easy to migrate existing C extensions to HPy. Thanks to an appropriate and regular naming convention it should be obvious what the HPy equivalent of any existing `Python.h` API is. When a perfect replacement does not exist, the documentation explains what the alternative options are.

**Better debugging** In debug mode, you get early and precise errors and warnings when you make some specific kind of mistakes and/or violate the API rules and assumptions. For example, you get an error if you try to use a handle (see *Handles*) which has already been closed. It is possible to turn on the debug mode at startup time, *without needing to recompile*.

**Simplicity** The HPy API aims to be smaller and easier to study/use/manage than the existing `Python.h` API. Sometimes there is a trade-off between this goal and the others above, in particular *Performance on CPython* and *Easy migration*. The general approach is to have an API which is “as simple as possible” while not violating the other goals.

**Universal binaries** It is possible to compile extensions to a single binary which is ABI-compatible across multiple Python versions and/or multiple implementation. See *Target ABIs*.

**Opt-in low level data structures** Internal details might still be available, but in a opt-in way: for example, if Cython wants to iterate over a list of integers, it can ask if the implementation provides a direct low-level access to the content (e.g. in the form of a `int64_t[]` array) and use that. But at the same time, be ready to handle the generic fallback case.

## 2.2.2 API vs ABI

HPy defines *both* an API and an ABI. Before digging further into details, let's distinguish them:

- The **API** works at the level of source code: it is the set of functions, macros, types and structs which developers can use to write their own extension modules. For C programs, the API is generally made available through one or more header files (`*.h`).
- The **ABI** works at the level of compiled code: it is the interface between the host interpreter and the compiled DLL. Given a target CPU and operating system it defines things like the set of exported symbols, the precise memory layout of objects, the size of types, etc.

In general it is possible to compile the same source into multiple compiled libraries, each one targeting a different ABI. **PEP 3149** states that the filename of the compiled extension should contain the *ABI tag* to specify what the

target ABI is. For example, if you compile an extension called `simple.c` on CPython 3.8, you get a DLL called `simple.cpython-38-x86_64-linux-gnu.so`:

- `cpython-38` is the ABI tag, in this case CPython 3.8
- `x86_64` is the CPU architecture
- `linux-gnu` is the operating system

The same source code compiled on PyPy3.6 7.2.0 results in a file called `simple.pypy38-pp73-x86_64-linux-gnu.so`:

- `pypy38-pp73` is the ABI tag, in this case “PyPy3.8”, version “7.3.x”

The HPy C API is exposed to the user by including `hpy.h` and it is explained in its own section of the documentation.

## 2.2.3 Legacy and compatibility features

To allow an incremental transition to HPy, it is possible to use both `hpy.h` and `Python.h` API calls in the same extension. Using *HPy legacy features* you can:

- mix `Python.h` and HPy method defs in the same HPy module
- mix `Python.h` and HPy method defs and slots in the same HPy type
- convert HPy handles to and from `PyObject` \* using `HPy_AsPyObject()` and `HPy_FromPyObject()`

Thanks to this, you can port your code to HPy one method and one type at a time, while keeping the extension fully functional during the transition period. See the [Porting Guide](#) for a concrete example.

Legacy features are available only if you target the CPython or HPy Hybrid ABIs, as explained in the next section.

## 2.2.4 Target ABIs

Depending on the compilation options, an HPy extension can target three different ABIs:

**CPython ABI** In this mode, HPy is implemented as a set of C macros and `static inline` functions which translate the HPy API into the CPython API at compile time. The result is a compiled extension which is indistinguishable from a “normal” one and can be distributed using all the standard tools and will run at the very same speed.

*Legacy features* are available.

The output filename is e.g. `simple.cpython-38-x86_64-linux-gnu.so`.

**HPy Universal ABI** As the name suggests, the HPy Universal ABI is designed to be loaded and executed by a variety of different Python implementations. Compiled extensions can be loaded unmodified on all the interpreters which support it. PyPy and GraalPy support it natively. CPython supports it by using the `hpy.universal` package, and there is a small speed penalty<sup>1</sup> compared to the CPython ABI.

*Legacy features* are **not** available and it is forbidden to `#include <Python.h>`.

The resulting filename is e.g. `simple.hpy0.so`.

**HPy Hybrid ABI** The HPy Hybrid ABI is essentially the same as the Universal ABI, with the big difference that it allows to `#include <Python.h>`, to use the legacy features and thus to allow incremental porting.

At the ABI level the resulting binary depends on *both* HPy and the specific Python implementation which was used to compile the extension. As the name suggests, this means that the binary is not “universal”, thus negating

---

<sup>1</sup> The reason for this minor performance penalty is a layer of pointer indirection. For instance, `ctx->HPyLong_FromLong` is called from the CPython extension, which in universal mode simply forwards the call to `PyLong_FromLong`. It is technically possible to implement a CPython universal module loader which edits the program’s executable code at runtime to replace that call. Note that this is not at all trivial.

some of the benefits of HPy. The main benefit of using the HPy Hybrid ABI instead of the CPython ABI is being able to use the *Debug Mode* on the HPy parts, and faster speed on alternative implementations.

*Legacy features* are available.

The resulting filename is e.g. `simple.hpy0-cp38.so`.

Moreover, each alternative Python implementation could decide to implement its own non-universal ABI if it makes sense for them. For example, a hypothetical project *DummyPython* could decide to ship its own `hpy.h` which implements the HPy API but generates a DLL which targets the DummyPython ABI.

This means that to compile an extension for CPython, you can choose whether to target the CPython ABI or the Universal ABI. The advantage of the former is that it runs at native speed, while the advantage of the latter is that you can distribute a single binary, although with a small speed penalty on CPython. Obviously, nothing stops you compiling and distributing both versions: this is very similar to what most projects are already doing, since they automatically compile and distribute extensions for many different CPython versions.

From the user point of view, extensions compiled for the CPython ABI can be distributed and installed as usual, while those compiled for the HPy Universal or HPy Hybrid ABIs require installing the `hpy.universal` package on CPython and have no further requirements on Pythons that support HPy natively.

## 2.2.5 Benefits for the Python ecosystem

The HPy project offers some benefits to the python ecosystem, both to Python users and to library developers.

- C extensions can achieve much better speed on alternative implementations, including PyPy and GraalPy: according to early *Early benchmarks*, an extension written in HPy can be ~3x faster than the equivalent extension written using `Python.h`.
- Improved debugging: when you load extensions in *Debug Mode*, many common mistakes are checked and reported automatically.
- Universal binaries: libraries can choose to distribute only Universal ABI binaries. By doing so, they can support all Python implementations and version of CPython (like PyPy, GraalPy, CPython 3.10, CPython 3.11, etc) for which an HPy loader exists, including those that do not yet exist! This currently comes with a small speed penalty on CPython, but for non-performance critical libraries it might still be a good tradeoff.
- Python environments: With general availability of universal ABI binaries for popular packages, users can create equivalent python environments that target different Python implementations. Thus, Python users can try their workload against different implementations and pick the one best suited for their usage.
- In a situation where most or all popular Python extensions target the universal ABI, it will be more feasible for CPython to make breaking changes to its C/API for performance or maintainability reasons.

## 2.2.6 Cython extensions

If you use Cython, you can't use HPy directly. There is a [work in progress](#) to add Cython backend which emits HPy code instead of using `Python.h` code: once this is done, you will get the benefits of HPy automatically.

## 2.2.7 Extensions in other languages

On the API side, HPy is designed with C in mind, so it is not directly useful if you want to write an extension in a language other than C.

However, Python bindings for other languages could decide to target the *HPy Universal ABI* instead of the *CPython ABI*, and generate extensions which can be loaded seamlessly on all Python implementations which supports it. This is the route taken, for example, by [Rust](#).

## 2.2.8 Benefits for alternative Python implementations

If you are writing an alternative Python implementation, there is a good chance that you already know how painful it is to support the `Python.h` API. HPy is designed to be both faster and easier to implement!

You have two choices:

- support the Universal ABI: in this case, you just need to export the needed functions and to add a hook to `dlopen()` the desired libraries
- use a custom ABI: in this case, you have to write your own replacement for `hpy.h` and recompile the C extensions with it.

## 2.2.9 Current status and roadmap

HPy left the early stages of development and already provides a noticeable set of features. As on April 2023, the following milestones have been reached:

- some prominent real-world Python packages have been ported to HPy API. There is a list of HPy-compatible packages we know about on the HPy website [hpyproject.org](https://hpyproject.org).
- one can write extensions which expose module-level functions, with all the various kinds of calling conventions.
- there is support for argument parsing (i.e., the equivalents of `PyArg_ParseTuple` and `PyArg_ParseTupleAndKeywords`), and a convenient complex value building (i.e., the equivalent `Py_BuildValue`).
- one can implement custom types, whose struct may contain references to other Python objects using `HPyField`.
- there is a support for globally accessible Python object handles: `HPyGlobal`, which can still provide isolation for subinterpreters if needed.
- there is support for raising and catching exceptions.
- debug mode has been implemented and can be activated at run-time without recompiling. It can detect leaked handles or handles used after being closed.
- trace mode has been implemented and can be activated just like the debug mode. It helps analyzing the API usage (in particular wrt. performance).
- wheels can be built for HPy extensions with `python setup.py bdist_wheel` and can be installed with `pip install`.
- it is possible to choose between the *CPython ABI* and the *HPy Universal ABI* when compiling an extension module.
- extensions compiled with the CPython ABI work out of the box on CPython.
- it is possible to load HPy Universal extensions on CPython, thanks to the `hpy.universal` package.
- it is possible to load HPy Universal extensions on PyPy (using the PyPy [hpy branch](#)).

- it is possible to load HPy Universal extensions on [GraalPy](#).
- there is support for multi-phase module initialization.
- support for metaclasses has been added.

However, there is still a long road before HPy is usable for the general public. In particular, the following features are on our roadmap but have not been implemented yet:

- many of the original `Python.h` functions have not been ported to HPy yet. Porting most of them is straightforward, so for now the priority is to test HPy with real-world Python packages and primarily resolve the “hard” features to prove that the HPy approach works.
- add C-level module state to complement the `HPyGlobal` approach. While `HPyGlobal` is easier to use, it will make the migration simpler for existing extensions that use CPython module state.
- the integration with Cython is work in progress
- it is not clear yet how to approach `pybind11` and similar C++ bindings. They serve two use-cases:
  - As C++ wrappers for CPython API. HPy is fundamentally different in some ways, so fully compatible `pybind11` port of this API to HPy does not make sense. There can be a similar or even partially `pybind11` compatible C++ wrapper for HPy adhering to the HPy semantics and conventions (e.g., passing the HPy-Context pointer argument around, no reference stealing, etc.).
  - Way to expose (or “bind”) mostly pure C++ functions as Python functions where the C++ templating machinery takes care of the conversion between the Python world, i.e., `PyObject*`, and the C++ types. Porting this abstraction to HPy is possible and desired in the future. To determine the priority or such effort, we need to get more knowledge about existing `pybind11` use-cases.

## 2.2.10 Early benchmarks

To validate our approach, we ported a simple yet performance critical module to HPy. We chose [ultrajson](#) because it is simple enough to require porting only a handful of API functions, but at the same time it is performance critical and performs many API calls during the parsing of a JSON file.

This [blog post](#) explains the results in more detail, but they can be summarized as follows:

- `ujson-hpy` compiled with the CPython ABI is as fast as the original `ujson`.
- A bit surprisingly, `ujson-hpy` compiled with the HPy Universal ABI is only 10% slower on CPython. We need more evidence than a single benchmark of course, but if the overhead of the HPy Universal ABI is only 10% on CPython, many projects may find it small enough that the benefits of distributing extensions using only the HPy Universal ABI outweigh the performance costs.
- On PyPy, `ujson-hpy` runs 3x faster than the original `ujson`. Note the HPy implementation on PyPy is not fully optimized yet, so we expect even bigger speedups eventually.

## 2.2.11 Projects involved

HPy was born during EuroPython 2019, where a small group of people started to discuss the problems of the `Python.h` API and how it would be nice to have a way to fix them. Since then, it has gathered the attention and interest of people who are involved in many projects within the Python ecosystem. The following is a (probably incomplete) list of projects whose core developers are involved in HPy, in one way or the other. The mere presence in this list does not mean that the project as a whole endorses or recognizes HPy in any way, just that some of the people involved contributed to the code/design/discussions of HPy:

- PyPy
- CPython

- Cython
- GraalPy
- RustPython
- rust-hpy (fork of the `cpython` crate)

### 2.2.12 Related work

A partial list of alternative implementations which offer a `Python.h` compatibility layer include:

- PyPy
- Jython
- IronPython
- GraalPy

## 2.3 HPy API Introduction

### 2.3.1 Handles

The “H” in HPy stands for **handle**, which is a central concept: handles are used to hold a C reference to Python objects, and they are represented by the C `HPy` type. They play the same role as `PyObject *` in the `Python.h` API, albeit with some important differences which are detailed below.

When they are no longer needed, handles must be closed by calling `HPy_Close`, which plays more or less the same role as `Py_DECREF`. Similarly, if you need a new handle for an existing object, you can duplicate it by calling `HPy_Dup`, which plays more or less the same role as `Py_INCREF`.

The HPy API strictly follows these rules:

- HPy handles returned by a function are **never borrowed**, i.e., the caller must either close or return it.
- HPy handles passed as function arguments are **never stolen**; if you receive a HPy handle argument from your caller, you should never close it.

These rules makes the code simpler to reason about. Moreover, no reference borrowing enables the Python implementations to use whatever internal representation they wish. For example, the object returned by `HPy_GetItem_i` may be created on demand from some compact internal representation, which does not need to convert itself to full blown representation in order to hold onto the borrowed object.

We strongly encourage the users of HPy to also internally follow these rules for their own internal APIs and helper functions. For the sake of simplicity and easier local reasoning and also because in the future, code adhering to those rules may be suitable target for some scalable and precise static analysis tool.

The concept of handles is certainly not unique to HPy. Other examples include Unix file descriptors, where you have `dup()` and `close()`, and Windows’ `HANDLE`, where you have `DuplicateHandle()` and `CloseHandle()`.



## Handles vs PyObject \*

In order to fully understand the way HPy handles work, it is useful to discuss the `PyObject *` pointer in `Python.h`. These pointers always point to the same object, and a python object's identity is completely given by its address in memory, and two pointers with the same address can be passed to `Python.h` API functions interchangeably. As a result, `Py_INCREF` and `Py_DECREF` can be called with any reference to an object as long as the total number of calls of `incrcf` is equal to the number of calls of `decrcf` at the end of the object lifetime.

Whereas using HPy API, each handle must be closed independently.

Thus, the following perfectly valid piece of code using `Python.h`:

```
void foo(void)
{
    PyObject *x = PyLong_FromLong(42); // implicit INCRF on x
    PyObject *y = x;
    Py_INCREF(y);                      // INCRF on y
    /* ... */
    Py_DECREF(x);
    Py_DECREF(x);                      // two DECRF on x
}
```

Becomes using HPy API:

```
void foo(HPyContext *ctx)
{
    HPy x = HPyLong_FromLong(ctx, 42);
    HPy y = HPy_Dup(ctx, x);
    /* ... */
    // we need to close x and y independently
    HPy_Close(ctx, x);
    HPy_Close(ctx, y);
}
```

Calling any HPy function on a closed handle is an error. Calling `HPy_Close()` on the same handle twice is an error. Forgetting to call `HPy_Close()` on a handle results in a memory leak. When running in *Debug Mode*, HPy actively checks that you don't close a handle twice and that you don't forget to close any.

**Note:** Debug mode is a good example of how powerful it is to decouple the identity and therefore the lifetime of handles and those of objects. If you find a memory leak on CPython, you know that you are missing a `Py_DECREF` somewhere but the only way to find the corresponding `Py_INCREF` is to manually and carefully study the source code. On the other hand, if you forget to call `HPy_Close()`, debug mode is able to identify the precise code location which created the unclosed handle. Similarly, if you try to operate on a closed handle, it will identify the precise code locations which created and closed it. This is possible because handles are associated with a single call to a C/API function. As a result, given a handle that is leaked or used after freeing, it is possible to identify exactly the C/API function that produced it.

Remember that `Python.h` guarantees that multiple references to the same object results in the very same `PyObject *` pointer. Thus, it is possible to compare the pointer addresses to check whether they refer to the same object:

```
int is_same_object(PyObject *x, PyObject *y)
{
    return x == y;
}
```

On the other hand, in HPy, each handle is independent and it is common to have two different handles which point

to the same underlying object, so comparing two handles directly is ill-defined. To prevent this kind of common error (especially when porting existing code to HPy), the HPy C type is opaque and the C compiler actively forbids comparisons between them. To check for identity, you can use `HPy_Is()`:

```
int is_same_object(HPyContext *ctx, HPy x, HPy y)
{
    // return x == y; // compilation error!
    return HPy_Is(ctx, x, y);
}
```

---

**Note:** The main benefit of opaque handle semantics is that implementations are allowed to use very different models of memory management. On CPython, implementing handles is trivial because HPy is basically `PyObject *` in disguise, and `HPy_Dup()` and `HPy_Close()` are just aliases for `Py_INCREF` and `Py_DECREF`.

Unlike CPython, PyPy does not use reference counting to manage memory: instead, it uses a *moving GC*, which means that the address of an object might change during its lifetime, and this makes it hard to implement semantics like `PyObject *`'s where the address *identifies* the object, and this is directly exposed to the user. HPy solves this problem: on PyPy, handles are integers which represent indices into a list, which is itself managed by the GC. When an address changes, the GC edits the list, without having to touch all the handles which have been passed to C.

---

## 2.3.2 HPyContext

All HPy function calls take an `HPyContext` as a first argument, which represents the Python interpreter all the handles belong to. Strictly speaking, it would be possible to design the HPy API without using `HPyContext`: after all, all HPy function calls are ultimately mapped to `Python.h` function call, where there is no notion of context.

One of the reasons to include `HPyContext` from the day one is to be future-proof: it is conceivable to use it to hold the interpreter or the thread state in the future, in particular when there will be support for sub-interpreters. Another possible usage could be to embed different versions or implementations of Python inside the same process. In addition, the `HPyContext` may also be extended by adding new functions to the end without breaking any extensions built against the current `HPyContext`.

Moreover, `HPyContext` is used by the *HPy Universal ABI* to contain a sort of virtual function table which is used by the C extensions to call back into the Python interpreter.

### 2.3.3 A simple example

In this section, we will see how to write a simple C extension using HPy. It is assumed that you are already familiar with the existing `Python.h` API, so we will underline the similarities and the differences with it.

We want to create a function named `myabs` and `double` which takes a single argument and computes its absolute value:

```
#include "hpy.h"

HPyDef_METH(myabs, "myabs", HPyFunc_O)
static HPy myabs_impl(HPyContext *ctx, HPy self, HPy arg)
{
    return HPy_Absolute(ctx, arg);
}
```

There are a couple of points which are worth noting:

- We use the macro `HPyDef_METH` to declare we are going to define a HPy function called `myabs`.

- The function will be available under the name "myabs" in our Python module.
- The actual C function which implements myabs is called myabs\_impl and is inferred by the macro. The macro takes the name and adds \_impl to the end of it.
- It uses the HPyFunc\_O calling convention. Like METH\_O in Python.h, HPyFunc\_O means that the function receives a single argument on top of self.
- myabs\_impl takes two arguments of type HPy: handles for self and the argument, which are guaranteed to be valid. They are automatically closed by the caller, so there is no need to call HPy\_Close on them.
- myabs\_impl returns a handle, which has to be closed by the caller.
- HPy\_Absolute is the equivalent of PyNumber\_Absolute and computes the absolute value of the given argument.
- We also do not call HPy\_Close on the result returned to the caller. We must return a valid handle.

**Note:** Among other things, the HPyDef\_METH macro is needed to maintain compatibility with CPython. In CPython, C functions and methods have a C signature that is different to the one used by HPy: they don't receive an HPyContext and their arguments have the type PyObject \* instead of HPy. The macro automatically generates a trampoline function whose signature is appropriate for CPython and which calls the myabs\_impl. This trampoline is then used from both the CPython ABI and the CPython implementation of the universal ABI, but other implementations of the universal ABI will usually call directly the HPy function itself.

The second function definition is a bit different:

```
HPyDef_METH_IMPL(double_num, "double", double_impl, HPyFunc_O)
static HPy double_impl(HPyContext *ctx, HPy self, HPy arg)
{
    return HPy_Add(ctx, arg, arg);
}
```

This shows off the other way of creating functions.

- This example is much the same but the difference is that we use HPyDef\_METH\_IMPL to define a function named double.
- The difference between HPyDef\_METH\_IMPL and HPyDef\_METH is that the former needs to be given a name for the functions as the third argument.

Now, we can define our module:

```
static HPyDef *SimpleMethods[] = {
    &myabs,
    &double_num,
    NULL,
};

static HPyModuleDef simple = {
    .doc = "HPy Example",
    .size = 0,
    .defines = SimpleMethods,
    .legacy_methods = NULL
};
```

This part is very similar to the one you would write with Python.h. Note that we specify myabs (and **not** myabs\_impl) in the method table. There is also the .legacy\_methods field, which allows to add methods

that use the `Python.h` API, i.e., the value should be an array of `PyMethodDef`. This feature enables support for hybrid extensions in which some of the methods are still written using the `Python.h` API.

Note that the HPy module does not specify its name. HPy does not support the legacy single phase module initialization and the only module initialization approach is the multi-phase initialization (PEP 489). With multi-phase module initialization, the name of the module is always taken from the `ModuleSpec` (PEP 451), i.e., most likely from the name used in the `import {{name}}` statement that imported your module.

This is the only difference stemming from multi-phase module initialization in this simple example. As long as there is no need for any further initialization, we can just “register” our module using the `HPy_MODINIT` convenience macro. The first argument is the name of the extension file and is needed for HPy, among other things, to be able to generate the entry point for CPython called `PyInit_{{name}}`. The second argument is the `HPyModuleDef` we just defined.

```
HPy_MODINIT(simple, simple)
```

## Building the module

Let’s write a `setup.py` to build our extension:

```
from setuptools import setup, Extension
from os import path

setup(
    name="hpy-simple-example",
    hpy_ext_modules=[
        Extension('simple', sources=[path.join(path.dirname(__file__), 'simple.c')]),
    ],
    setup_requires=['hpy'],
)
```

We can now build the extension by running `python setup.py build_ext -i`. On CPython, it will target the *CPython ABI* by default, so you will end up with a file named e.g. `simple.cpython-37m-x86_64-linux-gnu.so` which can be imported directly on CPython with no dependency on HPy.

To target the *HPy Universal ABI* instead, it is possible to pass the option `--hpy-abi=universal` to `setup.py`. The following command will produce a file called `simple.hpy.so` (note that you need to specify `--hpy-abi` **before** `build_ext`, since it is a global option):

```
python setup.py --hpy-abi=universal build_ext -i
```

---

**Note:** This command will also produce a Python file named `simple.py`, which loads the HPy module using the `universal.load` function from the `hpy` Python package.

---

## VARARGS calling convention

If we want to receive more than a single arguments, we need the `HPy_METH_VARARGS` calling convention. Let's add a function `add_ints` which adds two integers:

```
HPyDef_METH(add_ints, "add_ints", HPyFunc_VARARGS)
static HPy add_ints_impl(HPyContext *ctx, HPy self, const HPy *args, size_t nargs)
{
    long a, b;
    if (!HPyArg_Parse(ctx, NULL, args, nargs, "ll", &a, &b))
        return HPy_NULL;
    return HPyLong_FromLong(ctx, a+b);
}
```

There are a few things to note:

- The C signature is different than the corresponding `Python.h` `METH_VARARGS`: in particular, instead of taking a tuple `PyObject *args`, we take an array of `HPy` and its size. This allows the call to happen more efficiently, because you don't need to create a tuple just to pass the arguments.
- We call `HPyArg_Parse` to parse the arguments. Contrarily to almost all the other `HPy` functions, this is **not** a thin wrapper around `PyArg_ParseTuple` because as stated above we don't have a tuple to pass to it, although the idea is to mimic its behavior as closely as possible. The parsing logic is implemented from scratch inside `HPy`, and as such there might be missing functionality during the early stages of `HPy` development.
- If an error occurs, we return `HPy_NULL`: we cannot simply `return NULL` because `HPy` is not a pointer type.

Once we have written our function, we can add it to the `SimpleMethods[]` table, which now becomes:

```
static HPyDef *SimpleMethods[] = {
    &myabs,
    &add_ints,
    NULL,
};
```

## 2.3.4 Creating types in HPy

Creating Python types in an `HPy` extension is again very similar to the C API with the difference that `HPy` only supports creating types from a specification. This is necessary because there is no such C-level type as `PyTypeObject` since that would expose the internal implementation.

### Creating a simple type in HPy

This section assumes that the user wants to define a type that stores some data in a C-level structure. As an example, we will create a simple C structure `PointObject` that represents a two-dimensional point.

```
typedef struct {
    long x;
    long y;
} PointObject;
HPyType_HELPERS(PointObject)
```

The macro call `HPyType_HELPERS(PointObject)` generates useful helper facilities for working with the type. It generates a C enum `PointObject_SHAPE` and a helper function `PointObject_AsStruct`. The enum is used in the type specification. The helper function is used to efficiently retrieving the pointer `PointObject *` from

an HPy handle to be able to access the C structure. We will use this helper function to implement the methods, get-set descriptors, and slots.

It makes sense to expose fields `PointObject.x` and `PointObject.y` as Python-level members. To do so, we need to define members by specifying their name, type, and location using HPy's convenience macro `HPyDef_MEMBER`:

```
HPyDef_MEMBER(Point_x, "x", HPyMember_LONG, offsetof(PointObject, x))
HPyDef_MEMBER(Point_y, "y", HPyMember_LONG, offsetof(PointObject, y))
```

The first argument of the macro is the name for the C global variable that will store the necessary information. We will need that later for registration of the type. The second, third, and fourth arguments are the Python-level name, the C type of the member, and the offset in the C structure, respectively.

Similarly, methods and get-set descriptors can be defined. For example, method `foo` is an instance method that takes no arguments (the `self` argument is, of course, implicit), does some computation with fields `x` and `y` and returns a Python `int`:

```
HPyDef_METH(Point_foo, "foo", HPyFunc_NOARGS)
static HPy Point_foo_impl(HPyContext *ctx, HPy self)
{
    PointObject *point = PointObject_AsStruct(ctx, self);
    return HPyLong_FromLong(ctx, point->x * 10 + point->y);
}
```

Get-set descriptors are also defined in a very similar way as methods. The following example defines a get-set descriptor for attribute `z` which is calculated from the `x` and `y` fields of the struct.

```
HPyDef_GETSET(Point_z, "z", .closure=(void *)1000)
static HPy Point_z_get(HPyContext *ctx, HPy self, void *closure)
{
    PointObject *point = PointObject_AsStruct(ctx, self);
    return HPyLong_FromLong(ctx, point->x*10 + point->y + (long)(HPy_ssize_t)closure);
}

static int Point_z_set(HPyContext *ctx, HPy self, HPy value, void *closure)
{
    PointObject *point = PointObject_AsStruct(ctx, self);
    long current = point->x*10 + point->y + (long)(HPy_ssize_t)closure;
    long target = HPyLong_AsLong(ctx, value); // assume no exception
    point->y += target - current;
    return 0;
}
```

It is also possible to define a get-descriptor or a set-descriptor by using HPy's macros `HPyDef_GET` and `HPyDef_SET` in the same way.

HPy also supports type slots. In this example, we will define slot `HPy_tp_new` (which corresponds to magic method `__new__`) to initialize fields `x` and `y` when constructing the object:

```
HPyDef_SLOT(Point_new, HPy_tp_new)
static HPy Point_new_impl(HPyContext *ctx, HPy cls, const HPy *args,
                          HPy_ssize_t nargs, HPy kw)
{
    long x, y;
    if (!HPyArg_Parse(ctx, NULL, args, nargs, "ll", &x, &y))
        return HPy_NULL;
    PointObject *point;
```

(continues on next page)

(continued from previous page)

```

HPy h_point = HPy_New(ctx, cls, &point);
if (HPy_IsNull(h_point))
    return HPy_NULL;
point->x = x;
point->y = y;
return h_point;
}

```

After everything was defined, we need to create a list of all defines such that we are able to eventually register them to the type:

```

static HPyDef *Point_defines[] = {
    &Point_x,
    &Point_y,
    &Point_z,
    &Point_new,
    &Point_foo,
    NULL
};

```

Please note that it is required to terminate the list with NULL. We can now create the actual type specification by appropriately filling an HPyType\_Spec structure:

```

static HPyType_Spec Point_spec = {
    .name = "simple_type.Point",
    .basicsize = sizeof(PointObject),
    .builtin_shape = PointObject_SHAPE,
    .defines = Point_defines
};

```

First, we need to define the name of the type by setting a C string to member name. Since this type has a C structure, we need to define the basicsize and best practice is to set it to `sizeof(PointObject)`. Also best practice is to set `builtin_shape` to `PointObject_SHAPE` where `PointObject_SHAPE` is generated by the previous usage of macro `HPyType_HELPERS(PointObject)`. Last but not least, we need to register the defines by setting field `defines` to the previously defined array `Point_defines`.

The type specification for the simple type `simple_type.Point` represented in C by structure `PointObject` is now complete. All that remains is to create the type object and add it to the module.

We will define a module execute slot, which is executed by the runtime right after the module is created. The purpose of the execute slot is to initialize the newly created module object. We can then add the type by using `HPyHelpers_AddType()`:

```

HPyDef_SLOT(simple_exec, HPy_mod_exec)
static int simple_exec_impl(HPyContext *ctx, HPy m) {
    if (!HPyHelpers_AddType(ctx, m, "Point", &Point_spec, NULL)) {
        return -1;
    }
    return 0; // success
}

static HPyDef *mod_defines[] = {
    &simple_exec, // 'simple_exec' is generated by the HPyDef_SLOT macro
    NULL,
};

```

(continues on next page)

(continued from previous page)

```
static HPyModuleDef moduledef = {
    .defines = mod_defines,
    // ...
}
```

Also look at the full example at: [examples/hpytype-example/simple\\_type](#).

## Legacy types

A type whose struct starts with `PyObject_HEAD` (either directly by embedding it in the type struct or indirectly by embedding another struct like `PyLongObject`) is a *legacy type*. A legacy type must set `.builtin_shape = HPyType_BuiltinShape_Legacy` in its `HPyType_Spec`. The counterpart (i.e. a non-legacy type) is called HPy pure type.

Legacy types are available to allow gradual porting of existing CPython extensions. It is possible to reuse existing `PyType_Slot` entities (i.e. slots, methods, members, and get/set descriptors). The idea is that you can then migrate one after each other while still running the tests.

The major restriction when using legacy types is that you cannot build a universal binary of your HPy extension (i.e. you cannot use *HPy Universal ABI*). The resulting binary will be specific to the Python interpreter used for building. Therefore, the goal should always be to fully migrate to HPy pure types.

A type with `.legacy_slots != NULL` is required to have `HPyType_BuiltinShape_Legacy` and to include `PyObject_HEAD` at the start of its struct. It would be easy to relax this requirement on CPython (where the `PyObject_HEAD` fields are always present) but a large burden on other implementations (e.g. PyPy, GraalPy) where a struct starting with `PyObject_HEAD` might not exist.

Types created via the old Python C API are automatically legacy types.

This section does not provide a dedicated example for how to create and use legacy types because the *Porting Example* already shows how that is useful during incremental migration to HPy.

## Inherit from a built-in type

HPy also supports inheriting from following built-in types:

- `type`
- `int`
- `float`
- `unicode`
- `tuple`
- `list`

Inheriting from built-in types is straight forward if you don't have a C structure that represents your type. In other words, you can simply inherit from, e.g., `str` if the `basicsize` in your type specification is 0. For example:

```
static HPyType_Spec Dummy_spec = {
    .name = "builtin_type.Dummy",
    .basicsize = 0
};
```



```

HPyType_SpecParam param[] = {
    { HPyType_SpecParam_Base, ctx->h_UnicodeType },
    { (HPyType_SpecParam_Kind)0 }
};
if (!HPyHelpers_AddType(ctx, module, "Dummy", &Dummy_spec, param))
    return;

```

This case is simple because there is no `Dummy_AsStruct` since there is no associated C-level structure.

It is, however, more involved if your type also defines its own C structure (i.e. `basicsize > 0` in the type specification). In this case, it is strictly necessary to use the right *built-in shape*.

### What is the right built-in shape?

This question is easy to answer: Each built-in shape (except of `HPyType_BuiltinShape_Legacy`) represents a built-in type. You need to use the built-in shape that fits to the specified base class. The mapping is described in `HPyType_BuiltinShape`.

Let's do an example. Assume we want to define a type that stores the natural language of a unicode string to the unicode object but the object should still just behave like a Python unicode object. So, we define struct `LanguageObject`:

```

typedef struct {
    char *language;
} LanguageObject;
HPyType_HELPERS(LanguageObject, HPyType_BuiltinShape_Unicode)

```

As you can see, we already specify the built-in shape here using `HPyType_HELPERS(LanguageObject, HPyType_BuiltinShape_Unicode)`. Then, in the type specification, we do:

```

static HPyType_Spec Language_spec = {
    .name = "builtin_type.Language",
    .basicsize = sizeof(LanguageObject),
    .builtin_shape = SHAPE(LanguageObject),
    .defines = Language_defines
};

```

In the last step, when actually creating the type from the specification, we need to define that its base class is `str` (aka. `UnicodeType`):

```

HPyType_SpecParam param[] = {
    { HPyType_SpecParam_Base, ctx->h_UnicodeType },
    { (HPyType_SpecParam_Kind)0 }
};
if (!HPyHelpers_AddType(ctx, module, "Language", &Language_spec, param))
    return;

```

Function `LanguageObject_AsStruct` (which is generated by `HPyType_HELPERS`) will then return a pointer to `LanguageObject`.

To summarize this: Specifying a type that inherits from a built-in type needs to be considered in three places:

1. Pass the appropriate built-in shape to `HPyType_HELPERS`.
2. Assign `SHAPE(TYPE)` to `HPyType_Spec.builtin_shape`.
3. Specify the desired base class in the type specification parameters.

For more information about the built-in shape and for a technical explanation for why it is required, see `HPyType_Spec.builtin_shape` and `HPyType_BuiltinShape`.

## 2.3.5 More Examples

The *Porting Example* shows another complete example of HPy extension ported from Python/C API.

The [HPy project space](#) on GitHub contains forks of some popular Python extensions ported to HPy as a proof of concept/feasibility studies, such as the [Kiwi solver](#). Note that those forks may not be up to date with their upstream projects or with the upstream HPy changes.

### HPy unit tests

HPy usually has tests for each API function. This means that there is lots of examples available by looking at the tests. However, the test source uses many macros and is hard to read. To overcome this we supply a utility to export clean C sources for the tests. Since the HPy tests are not shipped by default, you need to clone the HPy repository from GitHub:

```
> git clone https://github.com/hpyproject/hpy.git
```

After that, install all test requirements and dump the sources:

```
> cd hpy
> python3 -m pip install pytest filelock
> python3 -m pytest --dump-dir=test_sources test/
```

This will dump the generated test sources into folder `test_sources`. Note, that the tests won't be executed but skipped with an appropriate message.

## 2.4 Porting Guide

### 2.4.1 Porting `PyObject *` to HPy API constructs

While in CPython one always uses `PyObject *` to reference to Python objects, in HPy there are several types of handles that should be used depending on the life-time of the handle: `HPy`, `HPyField`, and `HPyGlobal`.

- `HPy` represents short lived handles that live no longer than the duration of one call from Python to HPy extension function. Rule of thumb: use for local variables, arguments, and return values.
- `HPyField` represents handles that are Python object struct fields, i.e., live in native memory attached to some Python object.
- `HPyGlobal` represents handles stored in C global variables. `HPyGlobal` can provide isolation between subinterpreters.

**Warning:** Never use a local variable of type `HPyField`, for any reason! If the GC kicks in, it might become invalid and become a dangling pointer.

**Warning:** Never store *HPy* handles to a long-lived memory, for example: C global variables or Python object structs.

The `HPy/HPyField` dichotomy might seem arbitrary at first, but it is needed to allow Python implementations to use a moving GC, such as PyPy. It is easier to explain and understand the rules by thinking about how a moving GC interacts with the C code inside an HPy extension.

It is worth remembering that during the collection phase, a moving GC might move an existing object to another memory location, and in that case it needs to update all the places which store a pointer to it. In order to do so, it needs to *know* where the pointers are. If there is a local C variable which is unknown to the GC but contains a pointer to a GC-managed object, the variable will point to invalid memory as soon as the object is moved.

Back to HPy vs HPyField vs HPyGlobal:

- HPy handles must be used for all C local variables, function arguments and function return values. They are supposed to be short-lived and closed as soon as they are no longer needed. The debug mode will report a long-lived HPy as a potential memory leak.
- In PyPy and GraalPy, HPy handles are implemented using an indirection: they are indexes inside a big list of GC-managed objects: this big list is tracked by the GC, so when an object moves its pointer is correctly updated.
- HPyField is for long-lived references, and the GC must be aware of their location in memory. In PyPy, an HPyField is implemented as a direct pointer to the object, and thus we need a way to inform the GC where it is in memory, so that it can update its value upon moving: this job is done by `tp_traverse`, as explained in the next section.
- HPyGlobal is for long-lived references that are supposed to be closed implicitly when the module is unloaded (once module unloading is actually implemented). HPyGlobal provides indirection to isolate subinterpreters. Implementation wise, HPyGlobal will usually contain an index to a table with Python objects stored in the interpreter state.
- On CPython without subinterpreters support, HPy, HPyGlobal, and HPyField are implemented as `PyObject *`.
- On CPython with subinterpreters support, HPyGlobal will be implemented by an indirection through the interpreter state. Note that thanks to the HPy design, switching between this and the more efficient implementation without subinterpreter support will not require rebuilding of the extension (in HPy universal mode), nor rebuilding of CPython.

---

**Note:** If you write a custom type using HPyField, you **MUST** also write a `tp_traverse` slot. Note that this is different than the old `Python.h` API, where you need `tp_traverse` only under certain conditions. See the next section for more details.

---



---

**Note:** The contract of `tp_traverse` is that it must visit all members of type HPyField contained within given struct, or more precisely *owned* by given Python object (in the sense of the *owner* argument to `HPyField_Store`), and nothing more, nothing less. Some Python implementations may choose to not call the provided `tp_traverse` if they know how to visit all members of type HPyField by other means (for example, when they track them internally already). The debug mode will check this contract.

---

## `tp_traverse`, `tp_clear`, `Py_TPFLAGS_HAVE_GC`

Let's quote the `Python.h` documentation about GC support

Python's support for detecting and collecting garbage which involves circular references requires support from object types which are "containers" for other objects which may also be containers. Types which do not store references to other objects, or which only store references to atomic types (such as numbers or strings), do not need to provide any explicit support for garbage collection.

A good rule of thumb is that if your type contains `PyObject *` fields, you need to:

1. provide a `tp_traverse` slot;
2. provide a `tp_clear` slot;

3. add the `Py_TPFLAGS_GC` to the `tp_flags`.

However, if you know that your `PyObject *` fields will contain only “atomic” types, you can avoid these steps.

In HPy the rules are slightly different:

1. if you have a field of type `HPyField`, you always **MUST** provide a `tp_traverse`. This is needed so that a moving GC can track the relevant areas of memory. However, you **MUST NOT** rely on `tp_traverse` to be called;
2. `tp_clear` does not exist. On CPython, HPy automatically generates one for you, by using `tp_traverse` to know which are the fields to clear. Other implementations are free to ignore it, if it’s not needed;
3. `HPy_TPFLAGS_GC` is still needed, especially on CPython. If you don’t specify it, your type will not be tracked by CPython’s GC and thus it might cause memory leaks if it’s part of a reference cycle. However, other implementations are free to ignore the flag and track the objects anyway, if their GC implementation allows it.

### `tp_dealloc` and `Py_DECREF`

Generally speaking, if you have one or more `PyObject *` fields in the old `Python.h`, you must provide a `tp_dealloc` slot where you `Py_DECREF` all of them. In HPy this is not needed and will be handled automatically by the system.

In particular, when running on top of CPython, HPy will automatically provide a `tp_dealloc` which decrefs all the fields listed by `tp_traverse`.

See also, *Deallocator slot `Py_tp_dealloc`*.

## 2.4.2 Direct C API to HPy mappings

In many cases, migrating to HPy is as easy as just replacing a certain C API function by the appropriate HPy API function. Table *Safe API function mapping* gives a mapping between C API and HPy API functions. This mapping is generated together with the code for the *CPython ABI* mode, so it is guaranteed to be correct.

Table 1: Safe API function mapping

C API function	HPy API function
<code>PyBool_FromLong</code>	<code>HPyBool_FromLong()</code>
<code>PyBytes_AS_STRING</code>	<code>HPyBytes_AS_STRING()</code>
<code>PyBytes_AsString</code>	<code>HPyBytes_AsString()</code>
<code>PyBytes_Check</code>	<code>HPyBytes_Check()</code>
<code>PyBytes_FromString</code>	<code>HPyBytes_FromString()</code>
<code>PyBytes_GET_SIZE</code>	<code>HPyBytes_GET_SIZE()</code>
<code>PyBytes_Size</code>	<code>HPyBytes_Size()</code>
<code>PyCallable_Check</code>	<code>HPyCallable_Check()</code>
<code>PyCapsule_IsValid</code>	<code>HPyCapsule_IsValid()</code>
<code>PyContextVar_Get</code>	<code>HPyContextVar_Get()</code>
<code>PyContextVar_New</code>	<code>HPyContextVar_New()</code>
<code>PyContextVar_Set</code>	<code>HPyContextVar_Set()</code>
<code>PyDict_Check</code>	<code>HPyDict_Check()</code>
<code>PyDict_Copy</code>	<code>HPyDict_Copy()</code>
<code>PyDict_Keys</code>	<code>HPyDict_Keys()</code>
<code>PyDict_New</code>	<code>HPyDict_New()</code>
<code>PyErr_Clear</code>	<code>HPyErr_Clear()</code>
<code>PyErr_ExceptionMatches</code>	<code>HPyErr_ExceptionMatches()</code>

continues on next page

Table 1 – continued from previous page

C API function	HPy API function
PyErr_NewException	<i>HPyErr_NewException()</i>
PyErr_NewExceptionWithDoc	<i>HPyErr_NewExceptionWithDoc()</i>
PyErr_NoMemory	<i>HPyErr_NoMemory()</i>
PyErr_SetFromErrnoWithFilename	<i>HPyErr_SetFromErrnoWithFilename()</i>
PyErr_SetFromErrnoWithFilenameObjects	<i>HPyErr_SetFromErrnoWithFilenameObjects()</i>
PyErr_SetObject	<i>HPyErr_SetObject()</i>
PyErr_SetString	<i>HPyErr_SetString()</i>
PyErr_WarnEx	<i>HPyErr_WarnEx()</i>
PyErr_WriteUnraisable	<i>HPyErr_WriteUnraisable()</i>
PyEval_EvalCode	<i>HPy_EvalCode()</i>
PyEval_RestoreThread	<i>HPy_ReenterPythonExecution()</i>
PyEval_SaveThread	<i>HPy_LeavePythonExecution()</i>
PyFloat_AsDouble	<i>HPyFloat_AsDouble()</i>
PyFloat_FromDouble	<i>HPyFloat_FromDouble()</i>
PyImport_ImportModule	<i>HPyImport_ImportModule()</i>
PyList_Append	<i>HPyList_Append()</i>
PyList_Check	<i>HPyList_Check()</i>
PyList_New	<i>HPyList_New()</i>
PyLong_AsDouble	<i>HPyLong_AsDouble()</i>
PyLong_AsLong	<i>HPyLong_AsLong()</i>
PyLong_AsLongLong	<i>HPyLong_AsLongLong()</i>
PyLong_AsSize_t	<i>HPyLong_AsSize_t()</i>
PyLong_AsSsize_t	<i>HPyLong_AsSsize_t()</i>
PyLong_AsUnsignedLong	<i>HPyLong_AsUnsignedLong()</i>
PyLong_AsUnsignedLongLong	<i>HPyLong_AsUnsignedLongLong()</i>
PyLong_AsUnsignedLongLongMask	<i>HPyLong_AsUnsignedLongLongMask()</i>
PyLong_AsUnsignedLongMask	<i>HPyLong_AsUnsignedLongMask()</i>
PyLong_AsVoidPtr	<i>HPyLong_AsVoidPtr()</i>
PyLong_FromLong	<i>HPyLong_FromLong()</i>
PyLong_FromLongLong	<i>HPyLong_FromLongLong()</i>
PyLong_FromSize_t	<i>HPyLong_FromSize_t()</i>
PyLong_FromSsize_t	<i>HPyLong_FromSsize_t()</i>
PyLong_FromUnsignedLong	<i>HPyLong_FromUnsignedLong()</i>
PyLong_FromUnsignedLongLong	<i>HPyLong_FromUnsignedLongLong()</i>
PyNumber_Absolute	<i>HPy_Absolute()</i>
PyNumber_Add	<i>HPy_Add()</i>
PyNumber_And	<i>HPy_And()</i>
PyNumber_Check	<i>HPyNumber_Check()</i>
PyNumber_Divmod	<i>HPy_Divmod()</i>
PyNumber_Float	<i>HPy_Float()</i>
PyNumber_FloorDivide	<i>HPy_FloorDivide()</i>
PyNumber_InPlaceAdd	<i>HPy_InPlaceAdd()</i>
PyNumber_InPlaceAnd	<i>HPy_InPlaceAnd()</i>
PyNumber_InPlaceFloorDivide	<i>HPy_InPlaceFloorDivide()</i>
PyNumber_InPlaceLshift	<i>HPy_InPlaceLshift()</i>
PyNumber_InPlaceMatrixMultiply	<i>HPy_InPlaceMatrixMultiply()</i>
PyNumber_InPlaceMultiply	<i>HPy_InPlaceMultiply()</i>
PyNumber_InPlaceOr	<i>HPy_InPlaceOr()</i>
PyNumber_InPlacePower	<i>HPy_InPlacePower()</i>

continues on next page

Table 1 – continued from previous page

C API function	HPY API function
PyNumber_InPlaceRemainder	HPy_InPlaceRemainder()
PyNumber_InPlaceRshift	HPy_InPlaceRshift()
PyNumber_InPlaceSubtract	HPy_InPlaceSubtract()
PyNumber_InPlaceTrueDivide	HPy_InPlaceTrueDivide()
PyNumber_InPlaceXor	HPy_InPlaceXor()
PyNumber_Index	HPy_Index()
PyNumber_Invert	HPy_Invert()
PyNumber_Long	HPy_Long()
PyNumber_Lshift	HPy_Lshift()
PyNumber_MatrixMultiply	HPy_MatrixMultiply()
PyNumber_Multiply	HPy_Multiply()
PyNumber_Negative	HPy_Negative()
PyNumber_Or	HPy_Or()
PyNumber_Positive	HPy_Positive()
PyNumber_Power	HPy_Power()
PyNumber_Remainder	HPy_Remainder()
PyNumber_Rshift	HPy_Rshift()
PyNumber_Subtract	HPy_Subtract()
PyNumber_TrueDivide	HPy_TrueDivide()
PyNumber_Xor	HPy_Xor()
PyObject_ASCII	HPy_ASCII()
PyObject_Bytes	HPy_Bytes()
PyObject_Call	HPy_CallTupleDict()
PyObject_DelItem	HPy_DelItem()
PyObject_GetAttr	HPy_GetAttr()
PyObject_GetAttrString	HPy_GetAttr_s()
PyObject_GetItem	HPy_GetItem()
PyObject_HasAttr	HPy_HasAttr()
PyObject_HasAttrString	HPy_HasAttr_s()
PyObject_Hash	HPy_Hash()
PyObject_IsTrue	HPy_IsTrue()
PyObject_Length	HPy_Length()
PyObject_Repr	HPy_Repr()
PyObject_RichCompare	HPy_RichCompare()
PyObject_RichCompareBool	HPy_RichCompareBool()
PyObject_SetAttr	HPy_SetAttr()
PyObject_SetAttrString	HPy_SetAttr_s()
PyObject_SetItem	HPy_SetItem()
PyObject_Str	HPy_Str()
PyObject_Type	HPy_Type()
PyObject_TypeCheck	HPy_TypeCheck()
PyObject_Vectorcall	HPy_Call()
PyObject_VectorcallMethod	HPy_CallMethod()
PySequence_Contains	HPy_Contains()
PySlice_AdjustIndices	HPySlice_AdjustIndices()
PySlice_Unpack	HPySlice_Unpack()
PyTuple_Check	HPyTuple_Check()
PyType_IsSubtype	HPyType_IsSubtype()
PyUnicode_AsASCIIString	HPyUnicode_AsASCIIString()

continues on next page

Table 1 – continued from previous page

C API function	HPY API function
<code>PyUnicode_AsLatin1String</code>	<code>HPyUnicode_AsLatin1String()</code>
<code>PyUnicode_AsUTF8AndSize</code>	<code>HPyUnicode_AsUTF8AndSize()</code>
<code>PyUnicode_AsUTF8String</code>	<code>HPyUnicode_AsUTF8String()</code>
<code>PyUnicode_Check</code>	<code>HPyUnicode_Check()</code>
<code>PyUnicode_DecodeASCII</code>	<code>HPyUnicode_DecodeASCII()</code>
<code>PyUnicode_DecodeFSDefault</code>	<code>HPyUnicode_DecodeFSDefault()</code>
<code>PyUnicode_DecodeFSDefaultAndSize</code>	<code>HPyUnicode_DecodeFSDefaultAndSize()</code>
<code>PyUnicode_DecodeLatin1</code>	<code>HPyUnicode_DecodeLatin1()</code>
<code>PyUnicode_EncodeFSDefault</code>	<code>HPyUnicode_EncodeFSDefault()</code>
<code>PyUnicode_FromEncodedObject</code>	<code>HPyUnicode_FromEncodedObject()</code>
<code>PyUnicode_FromString</code>	<code>HPyUnicode_FromString()</code>
<code>PyUnicode_FromWideChar</code>	<code>HPyUnicode_FromWideChar()</code>
<code>PyUnicode_ReadChar</code>	<code>HPyUnicode_ReadChar()</code>
<code>PyUnicode_Substring</code>	<code>HPyUnicode_Substring()</code>
<code>Py_FatalError</code>	<code>HPy_FatalError()</code>

### 2.4.3 Reference Counting `Py_INCREF` and `Py_DECREF`

The equivalents of `Py_INCREF` and `Py_DECREF` are essentially `HPy_Dup()` and `HPy_Close()`, respectively. The main difference is that `HPy_Dup()` gives you a *new handle* to the same object which means that the two handles may be different if comparing them with `memcmp` but still reference the same object. As a consequence, you may close a handle only once, i.e., you cannot call `HPy_Close()` twice on the same `HPy` handle, even if returned from `HPy_Dup`. For examples, see also sections *Handles* and *Handles vs PyObject\**

### 2.4.4 Calling functions `PyObject_Call` and `PyObject_CallObject`

Both `PyObject_Call` and `PyObject_CallObject` are replaced by `HPy_CallTupleDict(callable, args, kwargs)` in which either or both of `args` and `kwargs` may be null handles.

`PyObject_Call(callable, args, kwargs)` becomes:

```
HPy result = HPy_CallTupleDict(ctx, callable, args, kwargs);
```

`PyObject_CallObject(callable, args)` becomes:

```
HPy result = HPy_CallTupleDict(ctx, callable, args, HPy_NULL);
```

If `args` is not a handle to a tuple or `kwargs` is not a handle to a dictionary, `HPy_CallTupleDict` will return `HPy_NULL` and raise a `TypeError`. This is different to `PyObject_Call` and `PyObject_CallObject` which may segfault instead.

## 2.4.5 Calling Protocol

Both the *tp\_call* and *vectorcall* calling protocols are replaced by HPy's calling protocol. This is done by defining slot `HPy_tp_call`. HPy uses only one calling convention which is similar to the *vectorcall* calling convention. In the following example, we implement a call function for a simple Euclidean vector type. The function computes the dot product of two vectors.

```
typedef struct {
    long x;
    long y;
} EuclideanVectorObject;
HPyType_HELPERS(EuclideanVectorObject)
```

```
HPyDef_SLOT(call, HPy_tp_call)
static HPy
call_impl(HPyContext *ctx, HPy self, const HPy *args, size_t nargs,
          HPy kwnames)
{
    static const char *keywords[] = { "x1", "y1", NULL };
    long x1, y1;
    HPyTracker ht;
    if (!HPyArg_ParseKeywords(ctx, &ht, args, nargs, kwnames, "ll", keywords,
                             &x1, &y1)) {
        return HPy_NULL;
    }
    EuclideanVectorObject *data = EuclideanVectorObject_AsStruct(ctx, self);
    return HPyLong_FromLong(ctx, data->x * x1 + data->y * y1);
}
```

Positional and keyword arguments are passed as C array `args`. Argument `nargs` specifies the number of positional arguments. Argument `kwnames` is a tuple containing the names of the keyword arguments. The keyword argument values are appended to positional arguments and start at `args[nargs]` (if there are any).

In the above example, function `call_impl` will be used by default to call all instances of the corresponding type. It is also possible to install (maybe specialized) call function implementations per instances by using function `HPy_SetCallFunction()`. This needs to be done in the constructor of an object. For example:

```
HPyDef_CALL_FUNCTION(special_call)
static HPy
special_call_impl(HPyContext *ctx, HPy self, const HPy *args, size_t nargs,
                 HPy kwnames)
{
    HPy tmp = call_impl(ctx, self, args, nargs, kwnames);
    HPy res = HPy_Negative(ctx, tmp);
    HPy_Close(ctx, tmp);
    return res;
}

HPyDef_SLOT(new, HPy_tp_new)
static HPy
new_impl(HPyContext *ctx, HPy cls, const HPy *args, HPy_ssize_t nargs, HPy kw)
{
    static const char *keywords[] = { "x", "y", "use_special_call", NULL };
    HPyTracker ht;
    long x, y;
    HPy use_special_call = ctx->h_False;
    if (!HPyArg_ParseKeywordsDict(ctx, &ht, args, nargs, kw, "ll|O", keywords,
```

(continues on next page)



(continued from previous page)

```

        &x, &y, &use_special_call)) {
    return HPy_NULL;
}
EuclideanVectorObject *vector;
HPy h_point = HPy_New(ctx, cls, &vector);
if (HPy_IsNull(h_point)) {
    HPyTracker_Close(ctx, ht);
    return HPy_NULL;
}
if (HPy_IsTrue(ctx, use_special_call) &&
    HPy_SetCallFunction(ctx, h_point, &special_call) < 0) {
    HPyTracker_Close(ctx, ht);
    HPy_Close(ctx, h_point);
    return HPy_NULL;
}
HPyTracker_Close(ctx, ht);
vector->x = x;
vector->y = y;
return h_point;
}

```

## Limitations

1. It is not possible to use slot `HPy_tp_call` for a *var object* (i.e. if `HPyType_Spec.itemsize` is greater 0). Reason: HPy installs a hidden field in the object's data to store the call function pointer which is appended to everything else. In case of `EuclideanVectorObject`, a field is implicitly appended after member `y`. This is not possible for var objects because the variable part will also start after the fixed members.
2. It is also not possible to use slot `HPy_tp_call` with a legacy type that inherits the `basicsize` (i.e. if `HPyType_Spec.basicsize` is 0) for the same reason as above.

To overcome these limitations, it is still possible to manually embed a field for the call function pointer in a type's C struct and tell HPy where this field is. In this case, it is always necessary to set the call function pointer using `HPy_SetCallFunction()` in the object's constructor. This procedure is less convenient than just using slot `HPy_tp_call` but still not hard to use. Consider following example. We define a struct `FooObject` and declare field `HPyCallFunction call_func` which will be used to store the call function's pointer. We need to register the offset of that field with member `__vectorcalloffset__` and in the constructor `Foo_new`, we assign the call function `Foo_call_func`.

```

typedef struct {
    void *a;
    HPyCallFunction call_func;
    void *b;
} FooObject;
HPyType_HELPERS(FooObject)

```

```

HPyDef_MEMBER(Foo_call_func_offset, "__vectorcalloffset__", HPyMember_HPYSIZET,
    offsetof(FooObject, call_func), .readonly=1)

HPyDef_CALL_FUNCTION(Foo_call_func)
static HPy
Foo_call_func_impl(HPyContext *ctx, HPy self, const HPy *args, size_t nargs,
    HPy kwnames)
{
    return HPyUnicode_FromString(ctx,

```

(continues on next page)

(continued from previous page)

```

        "hello manually initialized call function");
    }

HPyDef_SLOT(Foo_new, HPy_tp_new)
static HPy Foo_new_impl(HPyContext *ctx, HPy cls, const HPy *args,
                        HPy_ssize_t nargs, HPy kw)
{
    FooObject *data;
    HPy h_obj = HPy_New(ctx, cls, &data);
    if (HPy_IsNull(h_obj))
        return HPy_NULL;
    data->call_func = Foo_call_func;
    return h_obj;
}

```

**Note:** In contrast to CPython's vectorcall protocol, `nargs` will never have flag `PY_VECTORCALL_ARGUMENTS_OFFSET` set. It will **only** be the positional argument count.

## Incremental Migration to HPy's Calling Protocol

In order to support incremental migration, HPy provides helper function `HPyHelpers_PackArgsAndKeywords()` that converts from HPy's calling convention to CPython's `tp_call` calling convention. Consider following example:

```

// function using legacy 'tp_call' calling convention
static HPy
Pack_call_legacy(HPyContext *ctx, HPy self, HPy args, HPy kwd)
{
    // use 'args' and 'kwd'
    return HPy_Dup(ctx, ctx->h_None);
}

// function using HPy calling convention
HPyDef_SLOT(Pack_call, HPy_tp_call)
static HPy
Pack_call_impl(HPyContext *ctx, HPy self, const HPy *args, size_t nargs,
               HPy kwnames)
{
    HPy args_tuple, kwd;
    HPy result;
    if (!HPyHelpers_PackArgsAndKeywords(ctx, args, nargs, kwnames,
                                         &args_tuple, &kwd)) {
        return HPy_NULL;
    }
    result = Pack_call_legacy(ctx, self, args_tuple, kwd);
    HPy_Close(ctx, args_tuple);
    HPy_Close(ctx, kwd);
    return result;
}

```

In this example, `args`, `nargs`, and `kwnames` are used to create a tuple of positional arguments `args_tuple` and a keyword arguments dictionary `kwd`.

## 2.4.6 PyModule\_AddObject

`PyModule_AddObject` is replaced with a regular `HPy_SetAttr_s()`. There is no `HPyModule_AddObject` function because it has an unusual refcount behavior (stealing a reference but only when it returns 0).

## 2.4.7 Deallocator slot `Py_tp_dealloc`

`Py_tp_dealloc` essentially becomes `HPy_tp_destroy`. The name intentionally differs because there are major differences: while the slot function of `Py_tp_dealloc` receives the full object (which makes it possible to resurrect it) and while there are no restrictions on what you may call in the C API deallocator, you must not do that in HPy's deallocator.

The two major restrictions apply to the slot function of `HPy_tp_destroy`:

1. The function must be **thread-safe**.
2. The function **must not** call into the interpreter.

The idea is, that `HPy_tp_destroy` just releases native resources (e.g. by using C lib's `free` function). Therefore, it only receives a pointer to the object's native data (and not a handle to the object) and it does not receive an `HPyContext` pointer argument.

For the time being, HPy will support the `HPy_tp_finalize` slot where those tight restrictions do not apply at the (significant) cost of performance.

## 2.4.8 Special slots `Py_tp_methods`, `Py_tp_members`, and `Py_tp_getset`

There is no direct replacement for C API slots `Py_tp_methods`, `Py_tp_members`, and `Py_tp_getset` because they are no longer needed. Methods, members, and get/set descriptors are specified *flatly* together with the other slots, using the standard mechanisms of `HPyDef_METH`, `HPyDef_MEMBER`, and `HPyDef_GETSET`. The resulting `HPyDef` structures are then accumulated in `HPyType_Spec.defines`.

## 2.4.9 Creating lists and tuples

The C API way of creating lists and tuples is to create an empty list or tuple object using `PyList_New(n)` or `PyTuple_New(n)`, respectively, and then to fill the empty object using `PyList_SetItem` / `PyList_SET_ITEM` or `PyTuple_SetItem` / `PyTuple_SET_ITEM`, respectively.

This is in particular problematic for tuples because they are actually immutable. HPy goes a different way and provides a dedicated *builder* API to avoid the (temporary) inconsistent state during object initialization.

Long story short, doing the same in HPy with builders is still very simple and straight forward. Following an example for creating a list:

```
PyObject *list = PyList_New(5);
if (list == NULL)
    return NULL; /* error */
PyList_SET_ITEM(list, 0, item0);
PyList_SET_ITEM(list, 1, item0);
...
PyList_SET_ITEM(list, 4, item0);
/* now 'list' is ready to use */
```

becomes

```
HPyListBuilder builder = HPyListBuilder_New(ctx, 5);
HPyListBuilder_Set(ctx, builder, 0, h_item0);
HPyListBuilder_Set(ctx, builder, 1, h_item1);
...
HPyListBuilder_Set(ctx, builder, 4, h_item4);
HPy h_list = HPyListBuilder_Build(ctx, builder);
if (HPy_IsNull(h_list))
    return HPy_NULL; /* error */
```

---

**Note:** In contrast to `PyList_SetItem`, `PyList_SET_ITEM`, `PyTuple_SetItem`, and `PyTuple_SET_ITEM`, the builder functions `HPyListBuilder_Set()` and `HPyTupleBuilder_Set()` are **NOT** stealing references. It is necessary to close the passed item handles (e.g. `h_item0` in the above example) if they are no longer needed.

---

If an error occurs during building the list or tuple, it is necessary to call `HPyListBuilder_Cancel()` or `HPyTupleBuilder_Cancel()`, respectively, to avoid memory leaks.

For details, see the API reference documentation *Building tuples and lists*.

## 2.4.10 Buffers

The buffer API in HPy is implemented using the `HPy_buffer` struct, which looks very similar to `Py_buffer` (refer to the [CPython documentation](#) for the meaning of the fields):

```
typedef struct {
    void *buf;
    HPy obj;
    HPy_ssize_t len;
    HPy_ssize_t itemsize;
    int readonly;
    int ndim;
    char *format;
    HPy_ssize_t *shape;
    HPy_ssize_t *strides;
    HPy_ssize_t *suboffsets;
    void *internal;
} HPy_buffer;
```

Buffer slots for HPy types are specified using slots `HPy_bf_getbuffer` and `HPy_bf_releasebuffer` on all supported Python versions, even though the matching `PyType_Spec` slots, `Py_bf_getbuffer` and `Py_bf_releasebuffer`, are only available starting from CPython 3.9.

## 2.4.11 Multi-phase Module Initialization

HPy supports only multi-phase module initialization (PEP 451). This means that the module object is typically created by interpreter from the `HPyModuleDef` specification and there is no “init” function. However, the module can define one or more `HPy_mod_exec` slots, which will be executed just after the module object is created. Inside the code of those slots, one can usually perform the same initialization as before.

Example of legacy single phase module initialization that uses Python/C API:

```
static struct PyModuleDef mod_def = {
    PyModuleDef_HEAD_INIT,
    .m_name = "legacyinit",
    .m_size = -1
};

PyMODINIT_FUNC
PyInit_legacyinit(void)
{
    PyObject *mod = PyModule_Create(&mod_def);
    if (mod == NULL) return NULL;

    // Some initialization: add types, constants, ...

    return mod;
}
```

The same code structure ported to HPy and multi-phase module initialization:

```
HPyDef_SLOT(my_exec, HPy_mod_exec)
int my_exec_impl(HPyContext *ctx, HPy mod) {

    // Some initialization: add types, constants, ...

    return 0; // success
}

static HPyDef *Methods[] = {
    &my_exec, // HPyDef_SLOT macro generated `my_exec` for us
    NULL,
};

static HPyModuleDef mod_def = {
    .defines = Methods
};

HPy_MODINIT(hpyinit, mod_def)
```

## 2.5 Porting Example

HPy supports *incrementally* porting an existing C extension from the original Python C API to the HPy API and to have the extension compile and run at each step along the way.

Here we walk through porting a small C extension that implements a Point type with some simple methods (a norm and a dot product). The Point type is minimal, but does contain additional C attributes (the x and y values of the point) and an attribute (obj) that contains a Python object (that we will need to convert from a `PyObject *` to an `HPyField`).

There is a separate C file illustrating each step of the incremental port:

- `steps/step_00_c_api`: The original C API version that we are going to port.
- `steps/step_01_hpy_legacy`: A possible first step where all methods still receive `PyObject *` arguments and may still cast them to `PyPointObject *` if they are instances of `Point`.
- `steps/step_02_hpy_legacy`: Shows how to transition some methods to HPy methods that receive HPy handles as arguments while still supporting legacy methods that receive `PyObject *` arguments.

- `steps/step_03_hpy_final`: The completed port to HPy where all methods receive HPy handles and `PyObject_HEAD` has been removed.

Take a moment to read through `steps/step_00_c_api`. Then, once you're ready, keep reading.

Each section below corresponds to one of the three porting steps above:

- *Step 01: Converting the module to a (legacy) HPy module*
- *Step 02: Transition some methods to HPy*
- *Step 03: Complete the port to HPy*

**Note:** The steps used here are one approach to porting a module. The specific steps are not required. They're just an example approach.

### 2.5.1 Step 01: Converting the module to a (legacy) HPy module

First for the easy bit – let's include `hpy.h`:

```
3 #include <hpy.h>
```

We'd like to differentiate between references to `PyObject` that have been ported to HPy and those that haven't, so let's rename it to `PyObject` and alias `PyObject` to `PyObject`. We'll keep `PyObject` for the instances that haven't been ported yet (the legacy ones) and use `PyObject` where we have ported the references:

```
16 typedef struct {
17     // PyObject_HEAD is required while legacy_slots are still used
18     // but can (and should) be removed once the port to HPy is completed.
19     PyObject_HEAD
20     double x;
21     double y;
22     PyObject *obj;
23 } PyObject;
```

```
29 typedef PyObject PyObject;
```

For this step, all references will be to `PyObject` – we'll only start porting references in the next step.

Let's also call `HPyType_LEGACY_HELPERS` to define some helper functions for use with the `PyObject` struct:

```
37 HPyType_LEGACY_HELPERS(PyObject)
```

Again, we won't use these helpers in this step – we're just setting things up for later.

Now for the big steps.

We need to replace `PyType_Spec` for the `Point` type with the equivalent `HPyType_Spec`:

```
131 // HPy type methods and slots (no methods or slots have been ported yet)
132 static HPyDef *point_defines[] = {
133     NULL
```

(continues on next page)

(continued from previous page)

```

134 };
135
136 static HPyType_Spec Point_Type_spec = {
137     .name = "point_hpy_legacy_1.Point",
138     .basicsize = sizeof(PointObject),
139     .itemsz = 0,
140     .flags = HPy_TPFLAGS_DEFAULT,
141     .builtin_shape = SHAPE(PointObject),
142     .legacy_slots = Point_legacy_slots,
143     .defines = point_defines,
144 };
145
146 // HPy supports only multiphase module initialization, so we must migrate the
147 // single phase initialization by extracting the code that populates the module
148 // object with attributes into a separate 'exec' slot. The module is not
149 // created manually by calling API like PyModule_Create, but the runtime creates
150 // the module for us from the specification in HPyModuleDef, and we can provide
151 // additional slots to populate the module before its initialization is finalized
152 HPyDef_SLOT(module_exec, HPy_mod_exec)
153 static int module_exec_impl(HPyContext *ctx, HPy mod)
154 {
155     HPy point_type = HPyType_FromSpec(ctx, &Point_Type_spec, NULL);
156     if (HPy_IsNull(point_type))
157         return -1;
158     HPy_SetAttr_s(ctx, mod, "Point", point_type);
159     return 0;
160 }

```

Initially the list of ported methods in `point_defines` is empty and all of the methods are still in `Point_slots` which we have renamed to `Point_legacy_slots` for clarity.

`SHAPE(PointObject)` is a macro that retrieves the shape of `PointObject` as it was defined by the `HPyType_LEGACY_HELPERS` macro and will be set to `HPyType_BuiltinShape_Legacy` until we replace the legacy macro with the `HPyType_HELPERS` one. Any type with `legacy_slots` or that still includes `PyObject_HEAD` in its struct should have `.builtin_shape` set to `HPyType_BuiltinShape_Legacy`.

Similarly we replace `PyModuleDef` with `HPyModuleDef`:

```

162 // Legacy module methods (the "dot" method is still a PyCFunction)
163 static PyMethodDef PointModuleLegacyMethods[] = {
164     {"dot", (PyCFunction)dot, METH_VARARGS, "Dot product."},
165     {NULL, NULL, 0, NULL}
166 };
167
168 // HPy module methods: no regular methods have been ported yet,
169 // but we add the module execute slot
170 static HPyDef *module_defines[] = {
171     &module_exec,
172     NULL
173 };
174
175 static HPyModuleDef moduledef = {
176     // .name = "step_01_hpy_legacy",
177     // ^-- .name is not needed for multiphase module initialization,
178     // it is always taken from the ModuleSpec
179     .doc = "Point module (Step 1; All legacy methods)",
180     .size = 0,

```

(continues on next page)

(continued from previous page)

```

181     .legacy_methods = PointModuleLegacyMethods,
182     .defines = module_defines,
183 };

```

Like the type, the list of ported methods in `module_defines` is initially almost empty: all the regular methods are still in `PointModuleMethods` which has been renamed to `PointModuleLegacyMethods`. However, because HPy supports only multiphase module initialization, we must convert our module initialization code to an “exec” slot on the module and add that slot to `module_defines`.

Now all that is left is to replace the module initialization function with one that uses `HPy_MODINIT`. The first argument is the name of the extension, i.e., what was `XXX` in `PyInit_XXX`, and the second argument is the `HPyModuleDef`.

```

189 HPy_MODINIT(step_01_hpy_legacy, moduledef)

```

And we’re done!

Instead of the `PyInit_XXX`, we now have an “exec” slot on the module. We implement it with a C function that takes an `HPyContext *ctx` and `HPy mod` as arguments. The `ctx` must be forwarded as the first argument to calls to HPy API methods. The `mod` argument is a handle for the module object. The runtime creates the module for us from the provided `HPyModuleDef`. There is no need to call API like `PyModule_Create` explicitly.

Next step is to replace `PyType_FromSpec` by `HPyType_FromSpec`.

`HPy_SetAttr_s` is used to add the `Point` class to the module. HPy requires no special `PyModule_AddObject` method.

```

152 HPyDef_SLOT(module_exec, HPy_mod_exec)
153 static int module_exec_impl(HPyContext *ctx, HPy mod)
154 {
155     HPy point_type = HPyType_FromSpec(ctx, &Point_Type_spec, NULL);
156     if (HPy_IsNull(point_type))
157         return -1;
158     HPy_SetAttr_s(ctx, mod, "Point", point_type);
159     return 0;
160 }

```

## 2.5.2 Step 02: Transition some methods to HPy

In the previous step we put in place the type and module definitions required to create an HPy extension module. In this step we will port some individual methods.

Let us start by migrating `Point_traverse`. First we need to change `PyObject *obj` in the `PointObject` struct to `HPyField obj`:

```

16 typedef struct {
17     // PyObject_HEAD is required while legacy methods still access
18     // PointObject and should be removed once the port to HPy is completed.
19     PyObject_HEAD
20     double x;
21     double y;
22     // HPy handles are shortlived to support all GC strategies
23     // For that reason, PyObject* in C structs are replaced by HPyField
24     HPyField obj;
25 } PointObject;

```



HPy handles can only be short-lived – i.e. local variables, arguments to functions or return values. `HPyField` is the way to store long-lived references to Python objects. For more information, please refer to the documentation of [HPyField](#).

Now we can update `Point_traverse`:

```

40 HPyDef_SLOT(Point_traverse, HPy_tp_traverse)
41 int Point_traverse_impl(void *self, HPyFunc_visitproc visit, void *arg)
42 {
43     HPy_VISIT(&((PyObject*)self)->obj);
44     return 0;
45 }
```

In the first line we used the `HPyDef_SLOT` macro to define a small structure that describes the slot being implemented. The first argument, `Point_traverse`, is the name to assign the structure to. By convention, the `HPyDef_SLOT` macro expects a function called `Point_traverse_impl` implementing the slot. The second argument, `HPy_tp_traverse`, specifies the kind of slot.

This is a change from how slots are defined in the old C API. In the old API, the kind of slot is only specified much lower down in `Point_legacy_slots`. In HPy the implementation and kind are defined in one place using a syntax reminiscent of Python decorators.

The implementation of `traverse` is now a bit simpler than in the old C API. We no longer need to visit `Py_TYPE(self)` and need only `HPy_VISIT self->obj`. HPy ensures that interpreter knows that the type of the instance is still referenced.

Only struct members of type `HPyField` can be visited with `HPy_VISIT`, which is why we needed to convert `obj` to an `HPyField` before we implemented the HPy `traverse`.

Next we must update `Point_init` to store the value of `obj` as an `HPyField`:

```

48 HPyDef_SLOT(Point_init, HPy_tp_init)
49 int Point_init_impl(HPyContext *ctx, HPy self, const HPy *args,
50                    HPy_ssize_t nargs, HPy kw)
51 {
52     static const char *kwlist[] = {"x", "y", "obj", NULL};
53     PyObject *p = PyObject_AsStruct(ctx, self);
54     p->x = 0.0;
55     p->y = 0.0;
56     HPy obj = HPy_NULL;
57     HPyTracker ht;
58     if (!HPyArg_ParseKeywordsDict(ctx, &ht, args, nargs, kw, "|ddO", kwlist,
59                                &p->x, &p->y, &obj))
60         return -1;
61     if (HPy_IsNull(obj))
62         obj = ctx->h_None;
63     /* INCRREF not needed because HPyArg_ParseKeywordsDict does not steal a
64        reference */
65     HPyField_Store(ctx, self, &p->obj, obj);
66     HPyTracker_Close(ctx, ht);
67     return 0;
68 }
```

There are a few new HPy constructs used here:

- The kind of the slot passed to `HPyDef_SLOT` is `HPy_tp_init`.
- `PyObject_AsStruct` is defined by `HPyType_LEGACY_HELPERS` and returns an instance of the `PyObject` struct. Because we still include `PyObject_HEAD` at the start of the struct this is still a

valid `PyObject *` but once we finish the port the struct will no longer contain `PyObject_HEAD` and this will just be an ordinary C struct with no memory overhead!

- We use `HPyTracker` when parsing the arguments with `HPyArg_ParseKeywords`. The `HPyTracker` keeps track of open handles so that they can be closed easily at the end with `HPyTracker_Close`.
- `HPyArg_ParseKeywords` is the equivalent of `PyArg_ParseTupleAndKeywords`. Note that the HPy version does not steal a reference like the Python version.
- `HPyField_Store` is used to store a reference to `obj` in the struct. The arguments are the context (`ctx`), a handle to the object that owns the reference (`self`), the address of the `HPyField` (`&p->obj`), and the handle to the object (`obj`).

---

**Note:** An `HPyTracker` is not strictly needed for `HPyArg_ParseKeywords` in `Point_init`. The arguments `x` and `y` are C floats (so there are no handles to close) and the handle stored in `obj` was passed in to the `Point_init` as an argument and so should not be closed.

We showed the tracker here to demonstrate its use. You can read more about argument parsing in the [API docs](#).

If a tracker is needed and one is not provided, `HPyArg_ParseKeywords` will return an error.

---

The last update we need to make for the change to `HPyField` is to migrate `Point_obj_get` which retrieves `obj` from the stored `HPyField`:

```
71 HPyDef_GET(Point_obj, "obj", .doc="Associated object.")
72 HPy Point_obj_get(HPyContext *ctx, HPy self, void* closure)
73 {
74     PyObject *p = PyObject_AsStruct(ctx, self);
75     return HPyField_Load(ctx, self, p->obj);
76 }
```

Above we have used `PyObject_AsStruct` again, and then `HPyField_Load` to retrieve the value of `obj` from the `HPyField`.

We've now finished all of the changes needed by introducing `HPyField`. We could stop here, but let's migrate one ordinary method, `Point_norm`, to end off this stage of the port:

```
79 HPyDef_METH(Point_norm, "norm", HPyFunc_NOARGS, .doc="Distance from origin.")
80 HPy Point_norm_impl(HPyContext *ctx, HPy self)
81 {
82     PyObject *p = PyObject_AsStruct(ctx, self);
83     double norm;
84     norm = sqrt(p->x * p->x + p->y * p->y);
85     return HPyFloat_FromDouble(ctx, norm);
86 }
```

To define a method we use `HPyDef_METH` instead of `HPyDef_SLOT`. `HPyDef_METH` creates a small structure defining the method. The first argument is the name to assign to the structure (`Point_norm`). The second is the Python name of the method (`norm`). The third specifies the method signature (`HPyFunc_NOARGS` – i.e. no additional arguments in this case). The last provides the docstring. The macro then expects a function named `Point_norm_impl` implementing the method.

The rest of the implementation remains similar, except that we use `HPyFloat_FromDouble` to create a handle to a Python float containing the result (i.e. the distance of the point from the origin).

Now we are done and just have to remove the old implementations from `Point_legacy_slots` and add them to `point_defines`:

```

121 static HPyDef *point_defines[] = {
122     &Point_init,
123     &Point_norm,
124     &Point_obj,
125     &Point_traverse,
126     NULL
127 };

```

### 2.5.3 Step 03: Complete the port to HPy

In this step we'll complete the port. We'll no longer include `Python`, remove `PyObject_HEAD` from the `PyObject` struct, and port the remaining methods.

First, let's remove the import of `Python.h`:

```

2 // #include <Python.h> // disallow use of the old C API

```

And `PyObject_HEAD` from the struct:

```

15 typedef struct {
16     // PyObject_HEAD is no longer available in PyObject. In CPython,
17     // of course, it still exists but is inaccessible from HPy_AsStruct. In
18     // other Python implementations (e.g. PyPy) it might no longer exist at
19     // all.
20     double x;
21     double y;
22     HPyField obj;
23 } PyObject;

```

And the typedef of `PyObject` to `PyPyObject`:

```

29 // typedef PyObject PyPyObject;

```

Now any code that has not been ported should result in a compilation error.

We must also change the type helpers from `HPyType_LEGACY_HELPERS` to `HPyType_HELPERS` so that `PyObject_AsStruct` knows that `PyObject_HEAD` has been removed:

```

35 HPyType_HELPERS(PyObject)

```

There is one more method to port, the `dot` method which is a module method that implements the dot product between two points:

```

86 HPyDef_METH(dot, "dot", HPyFunc_VARARGS, .doc="Dot product.")
87 HPy dot_impl(HPyContext *ctx, HPy self, const HPy *args, size_t nargs)
88 {
89     HPy point1, point2;
90     if (!HPyArg_Parse(ctx, NULL, args, nargs, "OO", &point1, &point2))
91         return HPy_NULL;
92     PyObject *p1 = PyObject_AsStruct(ctx, point1);
93     PyObject *p2 = PyObject_AsStruct(ctx, point2);
94     double dp;
95     dp = p1->x * p2->x + p1->y * p2->y;
96     return HPyFloat_FromDouble(ctx, dp);
97 }

```

The changes are similar to those used in porting the `norm` method, except:

- We use `HPyArg_Parse` instead of `HPyArg_ParseKeywordsDict`.
- We opted not to use an `HPyTracker` by passing `NULL` as the pointer to the tracker when calling `HPyArg_Parse`. There is no reason not to use a tracker here, but the handles to the two points are passed in as arguments to `dot_impl` and thus there is no need to close them (and they should not be closed).

We use `PyObject_AsStruct` and `HPyFloat_FromDouble` as before.

Now that we have ported everything we can remove `PointMethods`, `Point_legacy_slots` and `PointModuleLegacyMethods`. The resulting type definition is much cleaner:

```
113 static HPyDef *point_defines[] = {
114     &Point_init,
115     &Point_norm,
116     &Point_obj,
117     &Point_traverse,
118     NULL
119 };
120
121 static HPyType_Spec Point_Type_spec = {
122     .name = "point_hpy_final.Point",
123     .doc = "Point (Step 03)",
124     .basicsize = sizeof(PointObject),
125     .itemsized = 0,
126     .flags = HPy_TPFLAGS_DEFAULT,
127     .defines = point_defines
128 };
129
130 HPyDef_SLOT(module_exec, HPy_mod_exec)
131 static int module_exec_impl(HPyContext *ctx, HPy mod)
132 {
133     HPy point_type = HPyType_FromSpec(ctx, &Point_Type_spec, NULL);
134     if (HPy_IsNull(point_type))
135         return -1;
136     HPy_SetAttr_s(ctx, mod, "Point", point_type);
137     return 0;
138 }
```

and the module definition is simpler too:

```
141 static HPyDef *module_defines[] = {
142     &module_exec,
143     &dot,
144     NULL
145 };
146
147 static HPyModuleDef moduledef = {
148     .doc = "Point module (Step 3; Porting complete)",
149     .size = 0,
150     .defines = module_defines,
151 };
```

Now that the port is complete, when we compile our extension in HPy universal mode, we obtain a built extension that depends only on the HPy ABI and not on the CPython ABI at all!

## 2.6 Debug Mode

HPy includes a debug mode which does useful run-time checks to ensure that C extensions use the API correctly. Its features include:

1. No special compilation flags are required: it is enough to compile the extension with the Universal ABI.
2. Debug mode can be activated at *import time*, and it can be activated per-extension.
3. You pay the overhead of debug mode only if you use it. Extensions loaded without the debug mode run at full speed.

This is possible because the whole of the HPy API is provided as part of the HPy context, so debug mode can pass in a special debugging context without affecting the performance of the regular context at all.

---

**Note:** The debug mode is only available if the module (you want to use it for) was built for *HPy Universal ABI*.

---

The debugging context can already check for:

- Leaked handles.
- Handles used after they are closed.
- Tuple and list builder used after they were *closed* (i.e. cancelled or the tuple/list was built).
- Reading from a memory which is no longer guaranteed to be still valid, for example, the buffer returned by `HPyUnicode_AsUTF8AndSize()`, `HPyBytes_AsString()`, and `HPyBytes_AS_STRING()`, after the corresponding HPy handle was closed.
- Writing to memory which should be read-only, for example the buffer returned by `HPyUnicode_AsUTF8AndSize()`, `HPyBytes_AsString()`, and `HPyBytes_AS_STRING()`

### 2.6.1 Activating Debug Mode

Debug mode works *only* for extensions built with HPy universal ABI.

To enable debug mode, use environment variable `HPY`. If `HPY=debug`, then all HPy modules are loaded with the trace context. Alternatively, it is also possible to specify the mode per module like this: `HPY=modA:debug, modB:debug`.

In order to verify that your extension is being loaded in debug mode, use environment variable `HPY_LOG`. If this variable is set, then all HPy extensions built in universal ABI mode print a message when loaded, such as:

```
> import snippets
Loading 'snippets' in HPy universal mode with a debug context
```

If the extension is built in CPython ABI mode, then the `HPY_LOG` environment variable has no effect.

An HPy extension module may be also explicitly loaded in debug mode using:

```
from hpy.universal import load, MODE_DEBUG
mod = load(module_name, so_filename, mode=MODE_DEBUG)
```

When loading HPy extensions explicitly, environment variables `HPY_LOG` and `HPY` have no effect for that extension.

## 2.6.2 Using Debug Mode

By default, when debug mode detects an error it will either abort the process (using `HPy_FatalError()`) or raise a fatal exception. This may sound very strict but in general, it is not safe to continue the execution.

When testing, aborting the process is unwanted. Module `hpy.debug` exposes the `LeakDetector` class to detect leaked HPy handles. For example:

```
def test_leak_detector():
    from hpy.debug.pytest import LeakDetector
    with LeakDetector() as ld:
        # add_ints is an HPy C function. If it forgets to close a handle,
        # LeakDetector will complain
        assert mixed.add_ints(40, 2) == 42
```

Additionally, the debug module also provides a pytest fixture, `hpy_debug`, that for the time being, enables the `LeakDetector`. In the future, it may also enable other useful debugging facilities.

```
from hpy.debug.pytest import hpy_debug
def test_that_uses_leak_detector_fixture(hpy_debug):
    # Run some HPy extension code
```

**Warning:** The usage of `LeakDetector` or `hpy_debug` by itself does not enable HPy debug mode! If debug mode is not enabled for any extension, then those features have no effect.

When dealing with handle leaks, it is useful to get a stack trace of the allocation of the leaked handle. This feature has large memory requirements and is therefore opt-in. It can be activated by:

```
hpy.debug.set_handle_stack_trace_limit(16)
```

and disabled by:

```
hpy.debug.disable_handle_stack_traces()
```

## 2.6.3 Example

Following HPy function leaks a handle:

```
HPyDef_METH(test_leak_stacktrace, "test_leak_stacktrace", HPyFunc_NOARGS)
static HPy test_leak_stacktrace_impl(HPyContext *ctx, HPy self)
{
    HPy num = HPyLong_FromLong(ctx, 42);
    if (HPy_IsNull(num)) {
        return HPy_NULL;
    }
    // No HPy_Close(ctx, num);
    return HPy_Dup(ctx, ctx->h_None);
}
```

When this script is executed in debug mode:

```
# Run with HPY=debug
import hpy.debug
import snippets
```

(continues on next page)

(continued from previous page)

```

hpy.debug.set_handle_stack_trace_limit(16)
from hpy.debug.pytest import LeakDetector
with LeakDetector() as ld:
    snippets.test_leak_stacktrace()

```

The output is:

```

Traceback (most recent call last):
  File "/path/to/hpy/docs/examples/debug-example.py", line 7, in <module>
    snippets.test_leak_stacktrace()
  File "/path/to/hpy/debug/leakdetector.py", line 43, in __exit__
    self.stop()
  File "/path/to/hpy/debug/leakdetector.py", line 36, in stop
    raise HPyLeakError(leaks)
hpy.debug.leakdetector.HPyLeakError: 1 unclosed handle:
  <DebugHandle 0x5556bbcf907c0 for 42>
Allocation stacktrace:
/path/to/site-packages/hpy-0.0.4.dev227+gd7eeec6.d20220510-py3.8-linux-x86_64.egg/hpy/
↳ universal.cpython-38d-x86_64-linux-gnu.so (debug_ctx_Long_FromLong+0x45)
↳ [0x7f1d928c48c4]
/path/to/site-packages/hpy_snippets-0.0.0-py3.8-linux-x86_64.egg/snippets.hpy.
↳ so(+0x122c) [0x7f1d921a622c]
/path/to/site-packages/hpy_snippets-0.0.0-py3.8-linux-x86_64.egg/snippets.hpy.
↳ so(+0x14b1) [0x7f1d921a64b1]
/path/to/site-packages/hpy-0.0.4.dev227+gd7eeec6.d20220510-py3.8-linux-x86_64.egg/hpy/
↳ universal.cpython-38d-x86_64-linux-gnu.so (debug_ctx_
↳ CallRealFunctionFromTrampoline+0xca) [0x7f1d928bde1e]
/path/to/site-packages/hpy_snippets-0.0.0-py3.8-linux-x86_64.egg/snippets.hpy.
↳ so(+0x129b) [0x7f1d921a629b]
/path/to/site-packages/hpy_snippets-0.0.0-py3.8-linux-x86_64.egg/snippets.hpy.
↳ so(+0x1472) [0x7f1d921a6472]
/path/to/libpython3.8d.so.1.0(+0x10a022) [0x7f1d93807022]
/path/to/libpython3.8d.so.1.0(+0x1e986b) [0x7f1d938e686b]
/path/to/libpython3.8d.so.1.0(+0x2015e9) [0x7f1d938fe5e9]
/path/to/libpython3.8d.so.1.0(_PyEval_EvalFrameDefault+0x1008c) [0x7f1d938f875a]
/path/to/libpython3.8d.so.1.0(PyEval_EvalFrameEx+0x64) [0x7f1d938e86b8]
/path/to/libpython3.8d.so.1.0(_PyEval_EvalCodeWithName+0xfaa) [0x7f1d938fc8af]
/path/to/libpython3.8d.so.1.0(PyEval_EvalCodeEx+0x86) [0x7f1d938fca25]
/path/to/libpython3.8d.so.1.0(PyEval_EvalCode+0x4b) [0x7f1d938e862b]

```

For the time being, HPy uses the `glibc` `backtrace` and `backtrace_symbols` functions. Therefore all their caveats and limitations apply. Usual recommendations to get more symbols in the traces and not only addresses, such as `snippets.hpy.so(+0x122c)`, are:

- link your native code with `-rdynamic` flag (`LDFLAGS="-rdynamic"`)
- build your code without optimizations and with debug symbols (`CFLAGS="-O0 -g"`)
- use `addr2line` command line utility, e.g.: `addr2line -e /path/to/snippets.hpy.so -C -f +0x122c`

## 2.7 Trace Mode

HPy's trace mode allows you to analyze the usage of the HPy API. The two fundamental metrics are `call_count` and `duration`. As the name already suggests, `call_count` tells you how often a certain HPy API function was called and `duration` uses a monotonic clock to measure how much (accumulated) time was spent in a certain HPy API function. It is further possible to register custom *on-enter* and *on-exit* Python functions.

As with the debug mode, the trace mode can be activated at *import time*, so no recompilation is required.

### 2.7.1 Activating Trace Mode

Similar to how the *debug mode is activated*, use environment variable `HPY`. If `HPY=trace`, then all HPy modules are loaded with the trace context. Alternatively, it is also possible to specify the mode per module like this: `HPY=modA:trace,modB:trace`. Environment variable `HPY_LOG` also works.

### 2.7.2 Using Trace Mode

The trace mode can be accessed via the shipped module `hpy.trace`. It provides following functions:

- `get_call_counts()` returns a dict. The HPy API function names are used as keys and the corresponding call count is the value.
- `get_durations()` also returns a dict similar to `get_call_counts` but the value is the accumulated time spent in the corresponding HPy API function (in nanoseconds). Note, the used clock does not necessarily have a nanosecond resolution which means that the least significant digits may not be accurate.
- `set_trace_functions(on_enter=None, on_exit=None)` allows the user to register custom trace functions. The function provided for `on_enter` and `on_exit` functions will be executed before and after and HPy API function is and was executed, respectively. Passing `None` to any of the two arguments or omitting one will clear the corresponding function.
- `get_frequency()` returns the resolution of the used clock to measure the time in Hertz. For example, a value of 10000000 corresponds to 10 MHz. In that case, the two least significant digits of the durations are inaccurate.

### 2.7.3 Example

Following HPy function uses `HPy_Add`:

```
HPyDef_METH(add, "add", HPyFunc_VARARGS)
static HPy add_impl(HPyContext *ctx, HPy self, const HPy *args, size_t nargs)
{
    if (nargs != 2) {
        HPyErr_SetString(ctx, ctx->h_TypeError, "expected exactly two args");
        return HPy_NULL;
    }
    return HPy_Add(ctx, args[0], args[1]);
}
```

When this script is executed in trace mode:

```
# Run with HPY=trace
from hpy.trace import get_call_counts
import snippets
```

(continues on next page)



(continued from previous page)

```

add_count_0 = get_call_counts() ["ctx_Add"]
snippets.add(1, 2) == 3
add_count_1 = get_call_counts() ["ctx_Add"]

print('get_call_counts() ["ctx_Add"] == %d' % (add_count_1 - add_count_0))

```

The output is `get_call_counts() ["ctx_Add"] == 1`.

## 2.8 API Reference

HPy's public API consists of three parts:

1. The **Core API** as defined in the *Public API Header*
2. **HPy Helper** functions
3. **Inline Helper** functions

### 2.8.1 Core API

The **Core API** consists of inline functions that call into the Python interpreter. Those functions will be implemented by each Python interpreter. In *CPython ABI* mode, many of these inline functions will just delegate to a C API functions. In *HPy Universal ABI* mode, they will call a function pointer from the HPy context. This is the source of the performance change between the modes.

#### HPy Core API Function Index

- `HPyBool_FromBool()`
- `HPyBytes_AS_STRING()`
- `HPyBytes_AsString()`
- `HPyBytes_Check()`
- `HPyBytes_FromString()`
- `HPyBytes_FromStringAndSize()`
- `HPyBytes_GET_SIZE()`
- `HPyBytes_Size()`
- `HPyCallable_Check()`
- `HPyCapsule_Get()`
- `HPyCapsule_IsValid()`
- `HPyCapsule_New()`
- `HPyCapsule_Set()`
- `HPyContextVar_Get()`
- `HPyContextVar_New()`
- `HPyContextVar_Set()`

- `HPyDict_Check()`
- `HPyDict_Copy()`
- `HPyDict_Keys()`
- `HPyDict_New()`
- `HPyErr_Clear()`
- `HPyErr_ExceptionMatches()`
- `HPyErr_NewException()`
- `HPyErr_NewExceptionWithDoc()`
- `HPyErr_NoMemory()`
- `HPyErr_Occurred()`
- `HPyErr_SetFromErrnoWithFilename()`
- `HPyErr_SetFromErrnoWithFilenameObjects()`
- `HPyErr_SetObject()`
- `HPyErr_SetString()`
- `HPyErr_WarnEx()`
- `HPyErr_WriteUnraisable()`
- `HPyField_Load()`
- `HPyField_Store()`
- `HPyFloat_AsDouble()`
- `HPyFloat_FromDouble()`
- `HPyGlobal_Load()`
- `HPyGlobal_Store()`
- `HPyImport_ImportModule()`
- `HPyListBuilder_Build()`
- `HPyListBuilder_Cancel()`
- `HPyListBuilder_New()`
- `HPyListBuilder_Set()`
- `HPyList_Append()`
- `HPyList_Check()`
- `HPyList_New()`
- `HPyLong_AsDouble()`
- `HPyLong_AsInt32_t()`
- `HPyLong_AsInt64_t()`
- `HPyLong_AsSize_t()`
- `HPyLong_AsSsize_t()`
- `HPyLong_AsUInt32_t()`

- `HPyLong_AsUInt32_tMask()`
- `HPyLong_AsUInt64_t()`
- `HPyLong_AsUInt64_tMask()`
- `HPyLong_AsVoidPtr()`
- `HPyLong_FromInt32_t()`
- `HPyLong_FromInt64_t()`
- `HPyLong_FromSize_t()`
- `HPyLong_FromSsize_t()`
- `HPyLong_FromUInt32_t()`
- `HPyLong_FromUInt64_t()`
- `HPyNumber_Check()`
- `HPySlice_Unpack()`
- `HPyTracker_Add()`
- `HPyTracker_Close()`
- `HPyTracker_ForgetAll()`
- `HPyTracker_New()`
- *`HPyTupleBuilder_Build()`*
- *`HPyTupleBuilder_Cancel()`*
- *`HPyTupleBuilder_New()`*
- *`HPyTupleBuilder_Set()`*
- `HPyTuple_Check()`
- `HPyTuple_FromArray()`
- *`HPyType_FromSpec()`*
- `HPyType_GenericNew()`
- *`HPyType_GetName()`*
- *`HPyType_IsSubtype()`*
- `HPyUnicode_AsASCIIString()`
- `HPyUnicode_AsLatin1String()`
- `HPyUnicode_AsUTF8AndSize()`
- `HPyUnicode_AsUTF8String()`
- `HPyUnicode_Check()`
- `HPyUnicode_DecodeASCII()`
- `HPyUnicode_DecodeFSDefault()`
- `HPyUnicode_DecodeFSDefaultAndSize()`
- `HPyUnicode_DecodeLatin1()`
- `HPyUnicode_EncodeFSDefault()`

- `HPyUnicode_FromEncodedObject()`
- `HPyUnicode_FromString()`
- `HPyUnicode_FromWideChar()`
- `HPyUnicode_ReadChar()`
- `HPyUnicode_Substring()`
- `HPy_ASCII()`
- `HPy_Absolute()`
- `HPy_Add()`
- `HPy_And()`
- `HPy_AsPyObject()`
- `HPy_Bytes()`
- `HPy_Call()`
- `HPy_CallMethod()`
- `HPy_CallTupleDict()`
- `HPy_Close()`
- `HPy_Compile_s()`
- `HPy_Contains()`
- `HPy_DelItem()`
- `HPy_DelItem_i()`
- `HPy_DelItem_s()`
- `HPy_Divmod()`
- `HPy_Dup()`
- `HPy_EvalCode()`
- `HPy_FatalError()`
- `HPy_Float()`
- `HPy_FloorDivide()`
- `HPy_FromPyObject()`
- `HPy_GetAttr()`
- `HPy_GetAttr_s()`
- `HPy_GetItem()`
- `HPy_GetItem_i()`
- `HPy_GetItem_s()`
- `HPy_HasAttr()`
- `HPy_HasAttr_s()`
- `HPy_Hash()`
- `HPy_InPlaceAdd()`

- `HPy_InPlaceAnd()`
- `HPy_InPlaceFloorDivide()`
- `HPy_InPlaceLshift()`
- `HPy_InPlaceMatrixMultiply()`
- `HPy_InPlaceMultiply()`
- `HPy_InPlaceOr()`
- `HPy_InPlacePower()`
- `HPy_InPlaceRemainder()`
- `HPy_InPlaceRshift()`
- `HPy_InPlaceSubtract()`
- `HPy_InPlaceTrueDivide()`
- `HPy_InPlaceXor()`
- `HPy_Index()`
- `HPy_Invert()`
- `HPy_Is()`
- `HPy_IsTrue()`
- `HPy_LeavePythonExecution()`
- `HPy_Length()`
- `HPy_Long()`
- `HPy_Lshift()`
- `HPy_MatrixMultiply()`
- `HPy_Multiply()`
- `HPy_Negative()`
- `HPy_Or()`
- `HPy_Positive()`
- `HPy_Power()`
- `HPy_ReenterPythonExecution()`
- `HPy_Remainder()`
- `HPy_Repr()`
- `HPy_RichCompare()`
- `HPy_RichCompareBool()`
- `HPy_Rshift()`
- `HPy_SetAttr()`
- `HPy_SetAttr_s()`
- `HPy_SetCallFunction()`
- `HPy_SetItem()`

- `HPy_SetItem_i()`
- `HPy_SetItem_s()`
- `HPy_Str()`
- `HPy_Subtract()`
- `HPy_TrueDivide()`
- `HPy_Type()`
- `HPy_TypeCheck()`
- `HPy_Xor()`

## HPy Context

The `HPyContext` structure is also part of the API since it provides handles for built-in objects. For a high-level description of the context, please also read [\*HPyContext\*](#).

**struct \_HPyContext\_s**

```
const char *name
int abi_version
HPy h_None
HPy h_True
HPy h_False
HPy h_NotImplemented
HPy h_Ellipsis
HPy h_BaseException
HPy h_Exception
HPy h_StopAsyncIteration
HPy h_StopIteration
HPy h_GeneratorExit
HPy h_ArithmeticError
HPy h_LookupError
HPy h_AssertionError
HPy h_AttributeError
HPy h_BufferError
HPy h_EOFError
HPy h_FloatingPointError
HPy h_OSError
HPy h_ImportError
HPy h_ModuleNotFoundError
HPy h_IndexError
```

---

HPy h\_KeyError  
HPy h\_KeyboardInterrupt  
HPy h\_MemoryError  
HPy h\_NameError  
HPy h\_OverflowError  
HPy h\_RuntimeError  
HPy h\_RecursionError  
HPy h\_NotImplementedError  
HPy h\_SyntaxError  
HPy h\_IndentationError  
HPy h\_TabError  
HPy h\_ReferenceError  
HPy h\_SystemError  
HPy h\_SystemExit  
HPy h\_TypeError  
HPy h\_UnboundLocalError  
HPy h\_UnicodeError  
HPy h\_UnicodeEncodeError  
HPy h\_UnicodeDecodeError  
HPy h\_UnicodeTranslateError  
HPy h\_ValueError  
HPy h\_ZeroDivisionError  
HPy h\_BlockingIOError  
HPy h\_BrokenPipeError  
HPy h\_ChildProcessError  
HPy h\_ConnectionError  
HPy h\_ConnectionAbortedError  
HPy h\_ConnectionRefusedError  
HPy h\_ConnectionResetError  
HPy h\_FileExistsError  
HPy h\_FileNotFoundError  
HPy h\_InterruptedError  
HPy h\_IsADirectoryError  
HPy h\_NotADirectoryError  
HPy h\_PermissionError  
HPy h\_ProcessLookupError

HPy **h\_TimeoutError**  
HPy **h\_Warning**  
HPy **h\_UserWarning**  
HPy **h\_DeprecationWarning**  
HPy **h\_PendingDeprecationWarning**  
HPy **h\_SyntaxWarning**  
HPy **h\_RuntimeWarning**  
HPy **h\_FutureWarning**  
HPy **h\_ImportWarning**  
HPy **h\_UnicodeWarning**  
HPy **h\_BytesWarning**  
HPy **h\_ResourceWarning**  
HPy **h\_BaseObjectType**  
HPy **h\_TypeType**  
HPy **h\_BoolType**  
HPy **h\_LongType**  
HPy **h\_FloatType**  
HPy **h\_UnicodeType**  
HPy **h\_TupleType**  
HPy **h\_ListType**  
HPy **h\_ComplexType**  
HPy **h\_BytesType**  
HPy **h\_MemoryViewType**  
HPy **h\_CapsuleType**  
HPy **h\_SliceType**  
HPy **h\_Builtins**

## HPy Object

int **HPy\_IsTrue** (HPyContext \**ctx*, HPy *h*)  
HPy **HPy\_GetAttr** (HPyContext \**ctx*, HPy *obj*, HPy *name*)  
HPy **HPy\_GetAttr\_s** (HPyContext \**ctx*, HPy *obj*, const char \**utf8\_name*)  
int **HPy\_HasAttr** (HPyContext \**ctx*, HPy *obj*, HPy *name*)  
int **HPy\_HasAttr\_s** (HPyContext \**ctx*, HPy *obj*, const char \**utf8\_name*)  
int **HPy\_SetAttr** (HPyContext \**ctx*, HPy *obj*, HPy *name*, HPy *value*)  
int **HPy\_SetAttr\_s** (HPyContext \**ctx*, HPy *obj*, const char \**utf8\_name*, HPy *value*)  
HPy **HPy\_GetItem** (HPyContext \**ctx*, HPy *obj*, HPy *key*)



HPy **HPy\_GetItem\_s** (HPyContext \*ctx, HPy obj, const char \*utf8\_key)

HPy **HPy\_GetItem\_i** (HPyContext \*ctx, HPy obj, HPy\_ssize\_t idx)

int **HPy\_SetItem** (HPyContext \*ctx, HPy obj, HPy key, HPy value)

int **HPy\_SetItem\_s** (HPyContext \*ctx, HPy obj, const char \*utf8\_key, HPy value)

int **HPy\_SetItem\_i** (HPyContext \*ctx, HPy obj, HPy\_ssize\_t idx, HPy value)

int **HPy\_DelItem** (HPyContext \*ctx, HPy obj, HPy key)

int **HPy\_DelItem\_s** (HPyContext \*ctx, HPy obj, const char \*utf8\_key)

int **HPy\_DelItem\_i** (HPyContext \*ctx, HPy obj, HPy\_ssize\_t idx)

HPy **HPy\_Type** (HPyContext \*ctx, HPy obj)

Returns the type of the given object obj.

On failure, raises `SystemError` and returns `HPy_NULL`. This is equivalent to the Python expression `type(obj)`.

#### Parameters

- **ctx** – The execution context.
- **obj** – a Python object (must not be `HPy_NULL`)

**Returns** The type of obj or `HPy_NULL` in case of errors.

int **HPy\_TypeCheck** (HPyContext \*ctx, HPy obj, HPy type)

Checks if obj is an instance of type or any subtype of type.

#### Parameters

- **ctx** – The execution context.
- **obj** – a Python object (must not be `HPy_NULL`)
- **type** – A Python type object. This argument must not be `HPy_NULL` and must be a type (i.e. it must inherit from Python `type`). If this is not the case, the behavior is undefined (verification of the argument is only done in debug mode).

**Returns** Non-zero if object obj is an instance of type type or an instance of a subtype of type, and 0 otherwise.

int **HPy\_Is** (HPyContext \*ctx, HPy obj, HPy other)

HPy **HPy\_Repr** (HPyContext \*ctx, HPy obj)

HPy **HPy\_Str** (HPyContext \*ctx, HPy obj)

HPy **HPy\_ASCII** (HPyContext \*ctx, HPy obj)

HPy **HPy\_Bytes** (HPyContext \*ctx, HPy obj)

HPy **HPy\_RichCompare** (HPyContext \*ctx, HPy v, HPy w, int op)

int **HPy\_RichCompareBool** (HPyContext \*ctx, HPy v, HPy w, int op)

HPy\_hash\_t **HPy\_Hash** (HPyContext \*ctx, HPy obj)

int **HPy\_SetCallFunction** (HPyContext \*ctx, HPy h, HPyCallFunction \*func)

Set the call function for the given object.

By defining slot `HPy_tp_call` for some type, instances of this type will be callable objects. The specified call function will be used by default for every instance. This should account for the most common case (every instance of an object uses the same call function) but to still provide the necessary flexibility, function

`HPy_SetCallFunction` allows to set different (maybe specialized) call functions for each instance. This must be done in the constructor of an object.

A more detailed description on how to use that function can be found in section *Calling Protocol*.

#### Parameters

- **ctx** – The execution context.
- **h** – A handle to an object implementing the call protocol, i.e., the object's type must have slot `HPy_tp_call`. Otherwise, a `TypeError` will be raised. This argument must not be `HPy_NULL`.
- **def** – A pointer to the call function definition to set (must not be `NULL`). The definition is usually created using `HPyDef_CALL_FUNCTION`

**Returns** 0 in case of success and -1 in case of an error.

## HPy Types and Modules

Types, modules and their attributes (i.e. methods, members, slots, get-set descriptors) are defined in a similar way. Section *HPy Type* documents the type-specific and *HPy Module* documents the module-specific part. Section *HPy Definition* documents how to define attributes for both, types and modules.

### HPy Type

#### Definition

**struct HPyType\_Spec**

**const char \*name**

The Python name of type (UTF-8 encoded)

**int basicsize**

The size in bytes of the types associated native structure. Usually, you define some C structure, e.g., `typedef struct { int a; } MyObject;`, and then this field is set to `sizeof(MyObject)`.

**int itemsize**

The size of embedded elements (currently not supported).

**unsigned long flags**

Type flags (see `HPy_TPFLAGS_DEFAULT`, `HPy_TPFLAGS_BASETYPE`, `HPy_TPFLAGS_HAVE_GC`, and others if available).

*HPyType\_BuiltinShape* **builtin\_shape**

The internal *shape* of the type. The shape gives the necessary hint to compute the offset to the data pointer of the object's underlying struct that should be returned when calling `MyObject_AsStruct`. **ATTENTION:** It is also necessary to specify the right base class in the type's specification parameters (see *HPyType\_SpecParam*). Assuming that the type's C structure is called `MyObject`, this field should be initialized with `.builtin_shape = SHAPE(MyObject)`. Note: This requires that you use *HPyType\_HELPERS* or *HPyType\_LEGACY\_HELPERS*. Some more explanation: It would be possible to reduce this information to a Boolean that specifies if the type is a *legacy* type or not. Everything else could be determined by looking at the base classes. However, with this information it is possible to do the data pointer computation statically and thus is performance critical. Types that do not define a struct of their own, should set the value of `.builtin_shape` to the same value as the type they inherit from. If they inherit from a built-in type, they must set the corresponding `.builtin_shape`.

```

void *legacy_slots
    Pointer to a NULL-terminated array of legacy (i.e. PyType_Slot) slots. A type with .legacy_slots
    != NULL is required to have HPyType_BuiltinShape_Legacy and to include PyObject_HEAD
    at the start of its struct. It would be easy to relax this requirement on CPython (where the
    PyObject_HEAD fields are always present) but a large burden on other implementations (e.g. PyPy,
    GraalPy) where a struct starting with PyObject_HEAD might not exist.

int **defines
    Pointer to a NULL-terminated array of pointers to HPy defines (i.e. HPyDef *).

const char *doc
    Docstring of the type (UTF-8 encoded; may be NULL)

```

**enum HPyType\_BuiltinShape**

```

enumerator HPyType_BuiltinShape_Legacy = -1
    A type whose struct starts with PyObject_HEAD or equivalent is a legacy type. A legacy type must set .
    builtin_shape = HPyType_BuiltinShape_Legacy in its HPyType_Spec. A type is a non-
    legacy type, also called HPy pure type, if its struct does not include PyObject_HEAD. Using pure types
    should be preferred. Legacy types are available to allow gradual porting of existing CPython extensions. A
    type with .legacy_slots != NULL (see HPyType_Spec.legacy_slots) is required to have
    HPyType_BuiltinShape_Legacy and to include PyObject_HEAD at the start of its struct. It
    would be easy to relax this requirement on CPython (where the PyObject_HEAD fields are always
    present) but a large burden on other implementations (e.g. PyPy, GraalPy) where a struct starting with
    PyObject_HEAD might not exist. Types created via the old Python C API are automatically legacy
    types.

enumerator HPyType_BuiltinShape_Object = 0
    The type inherits from built-in type object (default).

enumerator HPyType_BuiltinShape_Type = 1
    The type inherits from built-in type type. This can be used to create metaclasses. If using this shape, you
    need to specify base class ctx->h_TypeType.

enumerator HPyType_BuiltinShape_Long = 2
    The type inherits from built-in type int (aka. long object). If using this shape, you need to specify base
    class ctx->h_LongType.

enumerator HPyType_BuiltinShape_Float = 3
    The type inherits from built-in type float. If using this shape, you need to specify base class
    ctx->h_FloatType.

enumerator HPyType_BuiltinShape_Unicode = 4
    The type inherits from built-in type str (aka. unicode object). If using this shape, you need to specify
    base class ctx->h_UnicodeType.

enumerator HPyType_BuiltinShape_Tuple = 5
    The type inherits from built-in type tuple. If using this shape, you need to specify base class
    ctx->h_TupleType.

enumerator HPyType_BuiltinShape_List = 6
    The type inherits from built-in type list. If using this shape, you need to specify base class
    ctx->h_ListType.

```

**struct HPyType\_SpecParam**

```

HPyType_SpecParam_Kind kind
    The kind of the type spec param.

```

int **object**

The value of the type spec param (an HPy handle).

enum **HPyType\_SpecParam\_Kind**

enumerator **HPyType\_SpecParam\_Base** = 1

Specify a base class. This parameter may be repeated but cannot be used together with *HPyType\_SpecParam\_Kind.HPyType\_SpecParam\_BasesTuple*.

enumerator **HPyType\_SpecParam\_BasesTuple** = 2

Specify a tuple of base classes. Cannot be used together with *HPyType\_SpecParam\_Kind.HPyType\_SpecParam\_Base*

enumerator **HPyType\_SpecParam\_Metaclass** = 3

Specify a meta class for the type.

**HPyType\_HELPERS()**

A macro for creating (static inline) helper functions for custom types.

Two versions of the helper exist. One for legacy types and one for pure HPy types.

Example for a pure HPy custom type:

```
HPyType_HELPERS(PointObject)
```

It is also possible to inherit from some built-in types. The list of available built-in base types is given in enum *HPyType\_BuiltinShape*. In case you want to inherit from one of those, it is necessary to specify the base built-in type in the *HPyType\_HELPERS* macro. Here is an example for a pure HPy custom type inheriting from a built-in type 'tuple':

```
HPyType_HELPERS(PointObject, HPyType_BuiltinShape_Tuple)
```

This would generate the following:

- `PointObject * PointObject_AsStruct(HPyContext *ctx, HPy h)`: a static inline function that uses `HPy_AsStruct` to return the `PointObject` struct associated with a given handle. The behaviour is undefined if `h` is associated with an object that is not an instance of `PointObject`. However, debug mode will catch an incorrect usage.
- `SHAPE(PointObject)`: a macro that is meant to be used as static initializer in the corresponding `HPyType_Spec`. It is recommended to write `.builtin_shape = SHAPE(PointObject)` such that you don't have to remember to update the spec when the helpers used changes.

Example for a legacy custom type:

```
HPyType_LEGACY_HELPERS(PointObject)
```

This would generate the same functions and constants as above, except:

- `_HPy_AsStruct_Legacy` is used instead of `_HPy_AsStruct_Object`.
- `SHAPE(PointObject)` would be `HPyType_BuiltinShape_Legacy`.

### Parameters

- **STRUCT** – The C structure of the HPy type.
- **SHAPE** – Optional. The built-in shape of the type. This defaults to *HPyType\_BuiltinShape\_Object*. Possible values are all enumerators of *HPyType\_BuiltinShape*.

**HPyType\_LEGACY\_HELPERS** (*TYPE*)

Convenience macro which is equivalent to: `HPyType_HELPERS (TYPE, HPyType_BuiltinShape_Legacy)`

**HPy\_TPFLAGS\_DEFAULT**

Default type flags for HPy types.

**HPy\_TPFLAGS\_BASETYPE**

Set if the type allows subclassing

**HPy\_TPFLAGS\_HAVE\_GC**

If set, the object will be tracked by CPython's GC. Probably irrelevant for GC-based alternative implementations.

## Construction and More

**HPy HPyType\_FromSpec** (*HPyContext \*ctx, HPyType\_Spec \*spec, HPyType\_SpecParam \*params*)

Create a type from a *HPyType\_Spec* and an additional list of specification parameters.

**Parameters**

- **ctx** – The execution context.
- **spec** – The type spec to use to create the type.
- **params** – A 0-terminated list of type specification parameters or NULL.

**Returns** a handle of the created type on success, `HPy_NULL` on failure.

**const char \*HPyType\_GetName** (*HPyContext \*ctx, HPy type*)

Return the type's name.

Equivalent to getting the type's `__name__` attribute. If you want to retrieve the type's name as a handle that refers to a `str`, then just use `HPy_GetAttr_s (ctx, type, "__name__")`.

**Parameters**

- **ctx** – The execution context.
- **type** – A Python type object. This argument must not be `HPy_NULL` and must be a type (i.e. it must inherit from Python `type`). If this is not the case, the behavior is undefined (verification of the argument is only done in debug mode).

**Returns** The name of the type as C string (UTF-8 encoded) or NULL in case of an error. The returned pointer is read-only and guaranteed to be valid as long as the handle `type` is valid.

**int HPyType\_IsSubtype** (*HPyContext \*ctx, HPy sub, HPy type*)

Checks if `sub` is a subtype of `type`.

This function only checks for actual subtypes, which means that `__subclasscheck__()` is not called on `type`.

**Parameters**

- **ctx** – The execution context.
- **sub** – A Python type object. This argument must not be `HPy_NULL` and must be a type (i.e. it must inherit from Python `type`). If this is not the case, the behavior is undefined (verification of the argument is only done in debug mode).
- **type** – A Python type object. This argument must not be `HPy_NULL` and must be a type (i.e. it must inherit from Python `type`). If this is not the case, the behavior is undefined (verification of the argument is only done in debug mode).

**Returns** Non-zero if `sub` is a subtype of `type`.

## HPy Module

### HPY\_EMBEDDED\_MODULES

If `HPY_EMBEDDED_MODULES` is defined, this means that there will be several embedded HPy modules (and so, several `HPY_MODINIT` usages) in the same binary. In this case, some restrictions apply:

1. all of the module's methods/member/slots/... must be defined in the same file
2. the embedder **MUST** declare the module to be *embeddable* by using macro `HPY_MOD_EMBEDDABLE`.

### HPY\_MOD\_EMBEDDABLE (*modname*)

Declares a module to be *embeddable* which means that it and its members can be compiled/linked into a binary together with other embeddable HPy modules.

You may declare a module to be *embeddable* if all of its member definitions are in the same file.

### struct HPyModuleDef

Definition of a Python module. Pointer to this struct is returned from the HPy initialization function `HPyInit_{extname}` and the Python interpreter creates a Python module from it. HPy supports only the multi-phase module initialization approach (PEP 451).

There is no HPy API to create a Python module manually, i.e., equivalent of `PyModule_Create` or `PyModule_FromDefAndSpec`, for the time being, but may be added if a use-case arises.

Note: unlike Python/C API, HPy module definition does not specify module name. The name is always taken from the `ModuleSpec`, which is also the case in multi-phase module initialization on Python/C API.

#### const char \*doc

Docstring of the type (UTF-8 encoded; may be NULL)

#### int size

The size (in bytes) of the module state structure. If set to zero, then the module will not get allocated and assigned any HPy module state. Negative size, unlike in Python/C API, does not have any specific meaning and will produce a runtime error.

#### int \*legacy\_methods

NULL-terminated list of legacy module-level methods. In order to enable incremental migration from C API to HPy, it is possible to still add *legacy* method definitions. Those methods have a C API signature which means that they still receive `PyObject *` and similar arguments. If legacy methods are defined, you cannot create a *universal binary* (i.e. a binary that will run on all Python engines).

#### int \*\*defines

Pointer to a NULL-terminated array of pointers to HPy defines (i.e. `HPyDef *`). Note, that some kinds of HPy definitions don't make sense for a module. In particular, anything else than methods.

#### int \*\*globals

Pointer to a NULL-terminated array of pointers to `HPyGlobal` variables. For details, see [HPyGlobal](#).

### HPY\_MODINIT (*ext\_name*, *mod\_def*)

Convenience macro for generating the module initialization code. This will generate three functions that are used by to verify and initialize the module when loading:

**get\_required\_hpy\_major\_version** <modname> The HPy major version this module was built with.

**get\_required\_hpy\_minor\_version** <modname> The HPy minor version this module was built with.

**HPyModuleDef\*** **HPyInit\_<extname>** The init function that will be called by the interpreter. This function does not have an access to `HPyContext` and thus cannot call any HPy APIs. The purpose of this function is to return a pointer to a `HPyModuleDef` structure that will serve as a specification of the module that should be created by the interpreter. HPy supports only multi-phase module initialization (PEP 451). Any module initialization code can be added to the `HPy_mod_execute` slot of the module if needed.

Example:

```
HPy_MODINIT(myextension_shared_library_filename, my_hpy_module_def)
```

## HPy Definition

Defining slots, methods, members, and get-set descriptors for types and modules is done with HPy definition (represented by C struct *HPyDef*).

### **struct HPyDef**

Generic structure of an HPy definition.

This struct can be used to define a slot, method, member, or get/set descriptor. For details, see embedded structures *HPySlot*, *HPyMeth*, *HPyMember*, or *HPyGetSet*.

#### *HPyDef\_Kind* **kind**

The kind of this definition. The value of this field determines which one of the embedded members `slot`, `meth`, `member`, or `getset` is used. Since those are combined in a union, only one can be used at a time.

### **enum HPyDef\_Kind**

Enum to identify an HPy definition's kind.

**enumerator** `HPyDef_Kind_Slot`

**enumerator** `HPyDef_Kind_Meth`

**enumerator** `HPyDef_Kind_Member`

**enumerator** `HPyDef_Kind_GetSet`

### **struct HPySlot**

C structure to define an HPy slot.

It is perfectly fine to fill this structure manually. However, the recommended and easier way is to use macro *HPyDef\_SLOT*.

**int** `slot`

The slot to fill.

**HPyCFunction** `impl`

Function pointer to the slot's implementation

**int** `cpy_trampoline`

Function pointer to the CPython trampoline function which is used by CPython to call the actual HPy function `impl`.

### **struct HPyMeth**

C structure to define an HPy method.

It is perfectly fine to fill this structure manually. However, the recommended and easier way is to use macro *HPyDef\_METH*.

**const** `char *name`

The name of Python attribute (UTF-8 encoded)

HPyCFunction **impl**  
Function pointer of the C function implementation

int **cpy\_trampoline**  
Function pointer to the CPython trampoline function which is used by CPython to call the actual HPy function `impl`.

int **signature**  
Indicates the C function's expected signature

const char \***doc**  
Docstring of the method (UTF-8 encoded; may be NULL)

enum **HPyMember\_FieldType**  
Describes the type (and therefore also the size) of an HPy member.

enumerator **HPyMember\_SHORT**

enumerator **HPyMember\_INT**

enumerator **HPyMember\_LONG**

enumerator **HPyMember\_FLOAT**

enumerator **HPyMember\_DOUBLE**

enumerator **HPyMember\_STRING**

enumerator **HPyMember\_OBJECT**

enumerator **HPyMember\_CHAR**

enumerator **HPyMember\_BYTE**

enumerator **HPyMember\_UBYTE**

enumerator **HPyMember\_USHORT**

enumerator **HPyMember\_UINT**

enumerator **HPyMember\_ULONG**

enumerator **HPyMember\_STRING\_INPLACE**

enumerator **HPyMember\_BOOL**

enumerator **HPyMember\_OBJECT\_EX**

enumerator **HPyMember\_LONGLONG**

enumerator **HPyMember\_ULONGLONG**

enumerator **HPyMember\_HPYSSIZET**

enumerator **HPyMember\_NONE**

struct **HPyMember**  
C structure to define an HPy member.

It is perfectly fine to fill this structure manually. However, the recommended and easier way is to use macro `HPyDef_MEMBER`.

const char \***name**  
The name of Python attribute (UTF-8 encoded)

*HPyMember\_FieldType* **type**  
The type of the HPy member (see enum `HPyMember_FieldType`).



**int offset**

The location (byte offset) of the member. Usually computed with `offsetof(type, field)`.

**int readonly**

Flag indicating if the member is read-only

**const char \*doc**

Docstring of the member (UTF-8 encoded; may be NULL)

**struct HPyGetSet**

C structure to define an HPy get/set descriptor.

It is perfectly fine to fill this structure manually. However, the recommended and easier way is to use macros `HPyDef_GET` (to create a get descriptor only), `HPyDef_SET` (to create a set descriptor only), or `HPyDef_GETSET` (to create both).

**const char \*name**

The name of Python attribute (UTF-8 encoded)

**HPyCFunction getter\_impl**

Function pointer of the C getter function (may be NULL)

**HPyCFunction setter\_impl**

Function pointer of the C setter function (may be NULL)

**int getter\_cpy\_trampoline**

Function pointer to the CPython trampoline function for the getter (may be NULL if (and only if) `getter_impl == NULL`)

**int setter\_cpy\_trampoline**

Function pointer to the CPython trampoline function for the setter (may be NULL if (and only if) `setter_impl == NULL`)

**const char \*doc**

Docstring of the get/set descriptor (UTF-8 encoded; may be NULL)

**void \*closure**

A value that will be passed to the `getter_impl/setter_impl` functions.

**HPyDef\_SLOT** (*SYM*, *SLOT*)

A convenience macro and recommended way to create a definition for an HPy slot.

The macro generates a C global variable and an appropriate CPython trampoline function. It will fill an `HPyDef` structure appropriately and store it in the global variable.

This macro expects a C function `SYM_impl` that will be used as the implementing slot function.

#### Parameters

- **SYM** – A C symbol name of the resulting global variable that will contain the generated HPy definition. The variable is defined as `static`.
- **SLOT** – The HPy slot identifier.

**HPyDef\_METH** (*SYM*, *NAME*, *SIG*)

A convenience macro and recommended way to create a definition for an HPy method.

The macro generates a C global variable and an appropriate CPython trampoline function. It will fill an `HPyDef` structure appropriately and store it in the global variable.

This macro expects a C function `SYM_impl` that will be used as the implementing C function.

#### Parameters

- **SYM** – A C symbol name of the resulting global variable that will contain the generated HPy definition. The variable is defined as `static`.
- **NAME** – The Python attribute name (UTF-8 encoded).
- **SIG** – The implementation's C signature (see `HPyFunc_Signature`).

**HPyDef\_MEMBER** (*SYM, NAME, TYPE, OFFSET*)

A convenience macro and recommended way to create a definition for an HPy member.

The macro generates a C global variable. It will fill an *HPyDef* structure appropriately and store it in the global variable.

**Parameters**

- **SYM** – A C symbol name of the resulting global variable that will contain the generated HPy definition. The variable is defined as `static`.
- **NAME** – The Python attribute name (UTF-8 encoded).
- **TYPE** – The implementation's C signature (see `HPyFunc_Signature`).
- **OFFSET** – The Python attribute name (UTF-8 encoded).
- **.readonly** – Optional flag indicating if the member is read-only.
- **.doc** – Optional docstring (UTF-8 encoded).

**HPyDef\_GET** (*SYM, NAME*)

A convenience macro and recommended way to create a definition for an HPy get descriptor.

The macro generates a C global variable. It will fill an *HPyDef* structure appropriately and store it in the global variable.

**Parameters**

- **SYM** – A C symbol name of the resulting global variable that will contain the generated HPy definition. The variable is defined as `static`.
- **NAME** – The Python attribute name (UTF-8 encoded).
- **.doc** – Optional docstring (UTF-8 encoded).
- **.closure** – Optional pointer, providing additional data for the getter.

**HPyDef\_SET** (*SYM, NAME*)

A convenience macro and recommended way to create a definition for an HPy set descriptor.

The macro generates a C global variable. It will fill an *HPyDef* structure appropriately and store it in the global variable.

**Parameters**

- **SYM** – A C symbol name of the resulting global variable that will contain the generated HPy definition. The variable is defined as `static`.
- **NAME** – The Python attribute name (UTF-8 encoded).
- **.doc** – Optional docstring (UTF-8 encoded).
- **.closure** – Optional pointer, providing additional data for the setter.

**HPyDef\_GETSET** (*SYM, NAME*)

A convenience macro and recommended way to create a definition for an HPy get/set descriptor.

The macro generates a C global variable. It will fill an *HPyDef* structure appropriately and store it in the global variable.

**Parameters**

- **SYM** – A C symbol name of the resulting global variable that will contain the generated HPy definition. The variable is defined as `static`.
- **NAME** – The Python attribute name (UTF-8 encoded).
- **.doc** – Optional docstring (UTF-8 encoded).
- **.closure** – Optional pointer, providing additional data for the getter and setter.

**HPyDef\_CALL\_FUNCTION (SYM)**

A convenience macro and the recommended way to create a call function definition.

The macro generates a C global variable with name `SYM`. It will fill an `HPyCallFunction` structure appropriately and store it in the global variable.

This macro expects a C function `SYM_impl` that will be used as the implementing C function.

**Parameters**

- **SYM** – A C symbol name of the resulting global variable that will contain the generated call function definition. The variable is defined as `static`.

**HPy Call API**

HPy **HPy\_Call** (HPyContext \*ctx, HPy callable, **const** HPy \*args, size\_t nargs, HPy kwnames)

Call a Python object.

**Parameters**

- **ctx** – The execution context.
- **callable** – A handle to the Python object to call (must not be `HPy_NULL`).
- **args** – A pointer to an array of positional and keyword arguments. This argument must not be `NULL` if `nargs > 0` or `HPy_Length(ctx, kwnames) > 0`.
- **nargs** – The number of positional arguments in `args`.
- **kwnames** – A handle to the tuple of keyword argument names (may be `HPy_NULL`). The values of the keyword arguments are also passed in `args` appended to the positional arguments. Argument `nargs` does not include the keyword argument count.

**Returns** The result of the call on success, or `HPy_NULL` in case of an error.

HPy **HPy\_CallMethod** (HPyContext \*ctx, HPy name, **const** HPy \*args, size\_t nargs, HPy kwnames)

Call a method of a Python object.

**Parameters**

- **ctx** – The execution context.
- **name** – A handle to the name (a Unicode object) of the method. Must not be `HPy_NULL`.
- **args** – A pointer to an array of the arguments. The receiver is `args[0]`, and the positional and keyword arguments are starting at `args[1]`. This argument must not be `NULL` since a receiver is always required.
- **nargs** – The number of positional arguments in `args` including the receiver at `args[0]` (therefore, `nargs` must be at least 1).
- **kwnames** – A handle to the tuple of keyword argument names (may be `HPy_NULL`). The values of the keyword arguments are also passed in `args` appended to the positional arguments. Argument `nargs` does not include the keyword argument count.

**Returns** The result of the call on success, or `HPy_NULL` in case of an error.

HPy **HPy\_CallTupleDict** (HPyContext \*ctx, HPy callable, HPy args, HPy kw)  
 Call a Python object.

**Parameters**

- **ctx** – The execution context.
- **callable** – A handle to the Python object to call (must not be `HPy_NULL`).
- **args** – A handle to a tuple containing the positional arguments (must not be `HPy_NULL` but can, of course, be empty).
- **kw** – A handle to a Python dictionary containing the keyword arguments (may be `HPy_NULL`).

**Returns** The result of the call on success, or `HPy_NULL` in case of an error.

## HPyField

HPy **HPyField\_Load** (HPyContext \*ctx, HPy source\_object, HPyField source\_field)

void **HPyField\_Store** (HPyContext \*ctx, HPy target\_object, HPyField \*target\_field, HPy h)

HPyFields should be used ONLY in parts of memory which is known to the GC, e.g. memory allocated by `HPy_New`:

- NEVER declare a local variable of type `HPyField`
- NEVER use `HPyField` on a struct allocated by e.g. `malloc()`

**CPython's note:** contrary to `PyObject*`, you don't need to manually manage refcounting when using `HPyField`: if you use `HPyField_Store` to overwrite an existing value, the old object will be automatically decref. This means that you CANNOT use `HPyField_Store` to write memory which contains uninitialized values, because it would try to decref a dangling pointer.

Note that `HPy_New` automatically zeroes the memory it allocates, so everything works well out of the box. In case you are using manually allocated memory, you should initialize the `HPyField` to `HPyField_NULL`.

Note the difference:

- `obj->f = HPyField_NULL`: this should be used only to initialize uninitialized memory. If you use it to overwrite a valid `HPyField`, you will cause a memory leak (at least on CPython)
- `HPyField_Store(ctx, &obj->f, HPy_NULL)`: this does the right thing and decref the old value. However, you CANNOT use it if the memory is not initialized.

Note: `target_object` and `source_object` are there in case an implementation needs to add write and/or read barriers on the objects. They are ignored by CPython but e.g. PyPy needs a write barrier.

## HPyGlobal

void **HPyGlobal\_Store** (HPyContext \*ctx, HPyGlobal \*global, HPy h)

`HPyGlobal` is an alternative to module state. `HPyGlobal` must be a statically allocated C global variable registered in `HPyModuleDef.globals` array. A `HPyGlobal` can be used only after the HPy module where it is registered was created using `HPyModule_Create`.

`HPyGlobal` serves as an identifier of a Python object that should be globally available per one Python interpreter. Python objects referenced by `HPyGlobals` are destroyed automatically on the interpreter exit (not necessarily the process exit).

HPyGlobal instance does not allow anything else but loading and storing a HPy handle using a HPyContext. Even if the HPyGlobal C variable may be shared between threads or different interpreter instances within one process, the API to load and store a handle from HPyGlobal is thread-safe (but like any other HPy API must not be called in HPy\_LeavePythonExecution blocks).

Given that a handle to object X1 is stored to HPyGlobal using HPyContext of Python interpreter I1, then loading a handle from the same HPyGlobal using HPyContext of Python interpreter I1 should give a handle to the same object X1. Another Python interpreter I2 running within the same process and using the same HPyGlobal variable will not be able to load X1 from it, it will have its own view on what is stored in the given HPyGlobal.

Python interpreters may use indirection to isolate different interpreter instances, but alternative techniques such as copy-on-write or immortal objects can be used to avoid that indirection (even selectively on per object basis using tagged pointers).

CPython HPy implementation may even provide configuration option that switches between a faster version that directly stores PyObject\* to HPyGlobal but does not support subinterpreters, or a version that supports subinterpreters. For now, CPython HPy always stores PyObject\* directly to HPyGlobal.

While the standard implementation does not fully enforce the documented contract, the HPy debug mode will enforce it (not implemented yet).

**Implementation notes:** All Python interpreters running in one process must be compatible, because they will share all HPyGlobal C level variables. The internal data stored in HPyGlobal are specific for each HPy implementation, each implementation is also responsible for handling thread-safety when initializing the internal data in HPyModule\_Create. Note that HPyModule\_Create may be called concurrently depending on the semantics of the Python implementation (GIL vs no GIL) and also depending on the whether there may be multiple instances of given Python interpreter running within the same process. In the future, HPy ABI may include a contract that internal data of each HPyGlobal must be initialized to its address using atomic write and HPy implementations will not be free to choose what to store in HPyGlobal, however, this will allow multiple different HPy implementations within one process. This contract may also be activated only by some runtime option, letting the HPy implementation use more optimized HPyGlobal implementation otherwise.

HPy **HPyGlobal\_Load** (HPyContext \*ctx, HPyGlobal global)

## HPy Dict

int **HPyDict\_Check** (HPyContext \*ctx, HPy h)

Tests if an object is an instance of a Python dict.

### Parameters

- **ctx** – The execution context.
- **h** – A handle to an arbitrary object (must not be HPy\_NULL).

**Returns** Non-zero if object h is an instance of type dict or an instance of a subtype of dict, and 0 otherwise.

HPy **HPyDict\_New** (HPyContext \*ctx)

Creates a new empty Python dictionary.

### Parameters

- **ctx** – The execution context.

**Returns** A handle to the new and empty Python dictionary or HPy\_NULL in case of an error.

HPy **HPyDict\_Keys** (HPyContext \*ctx, HPy h)

Returns a list of all keys from the dictionary.

Note: This function will directly access the storage of the dict object and therefore ignores if method `keys` was overwritten.

#### Parameters

- **ctx** – The execution context.
- **h** – A Python dict object. If this argument is `HPy_NULL` or not an instance of a Python dict, a `SystemError` will be raised.

**Returns** A Python list object containing all keys of the given dictionary or `HPy_NULL` in case of an error.

HPy **HPyDict\_Copy** (HPyContext \*ctx, HPy h)  
Creates a copy of the provided Python dict object.

#### Parameters

- **ctx** – The execution context.
- **h** – A Python dict object. If this argument is `HPy_NULL` or not an instance of a Python dict, a `SystemError` will be raised.

**Returns** Return a new dictionary that contains the same key-value pairs as `h` or `HPy_NULL` in case of an error.

## Leave/enter Python execution (GIL)

HPyThreadState **HPy\_LeavePythonExecution** (HPyContext \*ctx)

void **HPy\_ReenterPythonExecution** (HPyContext \*ctx, HPyThreadState state)

Leaving Python execution: for releasing GIL and other use-cases.

In most situations, users should prefer using convenience macros: `HPy_BEGIN_LEAVE_PYTHON(context)/HPy_END_LEAVE_PYTHON(context)`

HPy extensions may leave Python execution when running Python independent code: long-running computations or blocking operations. When an extension has left the Python execution it must not call any HPy API other than `HPy_ReenterPythonExecution`. It can access pointers returned by HPy API, e.g., `HPyUnicode_AsUTF8String`, provided that they are valid at the point of calling `HPy_LeavePythonExecution`.

Python execution must be reentered on the same thread as where it was left. The leave/enter calls must not be nested. Debug mode will, in the future, enforce these constraints.

Python implementations may use this knowledge however they wish. The most obvious use case is to release the GIL, in which case the `HPy_BEGIN_LEAVE_PYTHON/HPy_END_LEAVE_PYTHON` becomes equivalent to `Py_BEGIN_ALLOW_THREADS/Py_END_ALLOW_THREADS`.

## Exception Handling

HPy **HPyErr\_SetFromErrnoWithFilename** (HPyContext \*ctx, HPy h\_type, const char \*filename\_fsencoded)

Similar to `HPyErr_SetFromErrnoWithFilenameObjects()` but takes one filename (a C string) that will be decoded using `HPyUnicode_DecodeFSDefault()`.

#### Parameters

- **ctx** – The execution context.
- **h\_type** – The exception type to raise.
- **filename\_fsencoded** – a filename; may be `NULL`

**Returns** always returns `HPy_NULL`

**HPy HPyErr\_SetFromErrnoWithFilenameObjects** (HPyContext \*ctx, HPy h\_type, HPy filename1, HPy filename2)

A convenience function to raise an exception when a C library function has returned an error and set the C variable `errno`. It constructs an instance of the provided exception type `h_type` by calling `h_type(errno, strerror(errno), filename1, 0, filename2)`. The exception instance is then raised.

**Parameters**

- **ctx** – The execution context.
- **h\_type** – The exception type to raise.
- **filename1** – A filename; may be `HPy_NULL`. In the case of `h_type` is the `OSError` exception, this is used to define the filename attribute of the exception instance.
- **filename2** – another filename argument; may be `HPy_NULL`

**Returns** always returns `HPy_NULL`

**void HPy\_FatalError** (HPyContext \*ctx, **const** char \*message)

**HPy HPyErr\_SetString** (HPyContext \*ctx, HPy h\_type, **const** char \*utf8\_message)

**HPy HPyErr\_SetObject** (HPyContext \*ctx, HPy h\_type, HPy h\_value)

**int HPyErr\_Occurred** (HPyContext \*ctx)

**int HPyErr\_ExceptionMatches** (HPyContext \*ctx, HPy exc)

**HPy HPyErr\_NoMemory** (HPyContext \*ctx)

**void HPyErr\_Clear** (HPyContext \*ctx)

**HPy HPyErr\_NewException** (HPyContext \*ctx, **const** char \*utf8\_name, HPy base, HPy dict)

**HPy HPyErr\_NewExceptionWithDoc** (HPyContext \*ctx, **const** char \*utf8\_name, **const** char \*utf8\_doc, HPy base, HPy dict)

**int HPyErr\_WarnEx** (HPyContext \*ctx, HPy category, **const** char \*utf8\_message, HPy\_ssize\_t stack\_level)

**void HPyErr\_WriteUnraisable** (HPyContext \*ctx, HPy obj)

## Building tuples and lists

**HPyTupleBuilder HPyTupleBuilder\_New** (HPyContext \*ctx, HPy\_ssize\_t size)

Create a new tuple builder for `size` elements. The builder is then able to take at most `size` elements. This function does not raise any exception (even if running out of memory).

**Parameters**

- **ctx** – The execution context.
- **size** – The number of elements to hold.

**void HPyTupleBuilder\_Set** (HPyContext \*ctx, HPyTupleBuilder builder, HPy\_ssize\_t index, HPy h\_item)

Assign an element to a certain index of the builder. Valid indices are in range  $0 \leq \text{index} < \text{size}$  where `size` is the value passed to `HPyTupleBuilder_New()`. This function does not raise any exception.

**Parameters**

- **ctx** – The execution context.
- **builder** – A tuple builder handle.

- **index** – The index to assign the object to.
- **h\_item** – An HPy handle of the object to store or HPy\_NULL. Please note that HPy **never** steals handles and so, **h\_item** needs to be closed by the caller.

HPy **HPyTupleBuilder\_Build** (HPyContext \**ctx*, HPyTupleBuilder *builder*)

Build a tuple from a tuple builder.

**Parameters**

- **ctx** – The execution context.
- **builder** – A tuple builder handle.

**Returns** An HPy handle to a tuple containing the values inserted with *HPyTupleBuilder\_Set()* or HPy\_NULL in case an error occurred during building or earlier when creating the builder or setting the items.

void **HPyTupleBuilder\_Cancel** (HPyContext \**ctx*, HPyTupleBuilder *builder*)

Cancel building of a tuple and free any acquired resources. This function ignores if any error occurred previously when using the tuple builder.

**Parameters**

- **ctx** – The execution context.
- **builder** – A tuple builder handle.

HPyListBuilder **HPyListBuilder\_New** (HPyContext \**ctx*, HPy\_ssize\_t *size*)

Create a new list builder for *size* elements. The builder is then able to take at most *size* elements. This function does not raise any exception (even if running out of memory).

**Parameters**

- **ctx** – The execution context.
- **size** – The number of elements to hold.

void **HPyListBuilder\_Set** (HPyContext \**ctx*, HPyListBuilder *builder*, HPy\_ssize\_t *index*, HPy *h\_item*)

Assign an element to a certain index of the builder. Valid indices are in range  $0 \leq \text{index} < \text{size}$  where *size* is the value passed to *HPyListBuilder\_New()*. This function does not raise any exception.

**Parameters**

- **ctx** – The execution context.
- **builder** – A list builder handle.
- **index** – The index to assign the object to.
- **h\_item** – An HPy handle of the object to store or HPy\_NULL. Please note that HPy **never** steals handles and so, **h\_item** needs to be closed by the caller.

HPy **HPyListBuilder\_Build** (HPyContext \**ctx*, HPyListBuilder *builder*)

Build a list from a list builder.

**Parameters**

- **ctx** – The execution context.
- **builder** – A list builder handle.

**Returns** An HPy handle to a list containing the values inserted with *HPyListBuilder\_Set()* or HPy\_NULL in case an error occurred during building or earlier when creating the builder or setting the items.



void **HPyListBuilder\_Cancel** (HPyContext \**ctx*, HPyListBuilder *builder*)

Cancel building of a tuple and free any acquired resources. This function ignores if any error occurred previously when using the tuple builder.

#### Parameters

- **ctx** – The execution context.
- **builder** – A tuple builder handle.

## HPy Eval

enum **HPy\_SourceKind**

An enumeration of the different kinds of source code strings.

**enumerator HPy\_SourceKind\_Expr = 0**

Parse isolated expressions (e.g. `a + b`).

**enumerator HPy\_SourceKind\_File = 1**

Parse sequences of statements as read from a file or other source. This is the symbol to use when compiling arbitrarily long Python source code.

**enumerator HPy\_SourceKind\_Single = 2**

Parse a single statement. This is the mode used for the interactive interpreter loop.

HPy **HPy\_Compile\_s** (HPyContext \**ctx*, **const** char \**utf8\_source*, **const** char \**utf8\_filename*, *HPy\_SourceKind* kind)

Parse and compile the Python source code.

#### Parameters

- **ctx** – The execution context.
- **utf8\_source** – Python source code given as UTF-8 encoded C string (must not be NULL).
- **utf8\_filename** – The filename (UTF-8 encoded C string) to use for construction of the code object. It may appear in tracebacks or in `SyntaxError` exception messages.
- **kind** – The source kind which tells the parser if a single expression, statement, or a whole file should be parsed (see enum *HPy\_SourceKind*).

**Returns** A Python code object resulting from the parsed and compiled Python source code or `HPy_NULL` in case of errors.

HPy **HPy\_EvalCode** (HPyContext \**ctx*, HPy *code*, HPy *globals*, HPy *locals*)

Evaluate a precompiled code object.

Code objects can be compiled from a string using *HPy\_Compile\_s()*.

#### Parameters

- **ctx** – The execution context.
- **code** – The code object to evaluate.
- **globals** – A Python dictionary defining the global variables for the evaluation.
- **locals** – A mapping object defining the local variables for the evaluation.

**Returns** The result produced by the executed code. May be `HPy_NULL` in case of errors.

## Public API Header

The core API is defined in `public_api.h`:

```

1  /* HPy public API */
2
3  /*
4   * IMPORTANT: In order to ensure backwards compatibility of HPyContext, it is
5   * necessary to define the order of the context members. To do so, use macro
6   * 'HPy_ID(idx)' for context handles and functions. When adding members, it
7   * doesn't matter where they are located in this file. It's just important that
8   * the maximum context index is incremented by exactly one.
9   */
10
11 #ifndef AUTOGEN
12
13 /* Constants */
14 HPy_ID(0) HPy h_None;
15 HPy_ID(1) HPy h_True;
16 HPy_ID(2) HPy h_False;
17 HPy_ID(3) HPy h_NotImplemented;
18 HPy_ID(4) HPy h_Ellipsis;
19
20 /* Exceptions */
21 HPy_ID(5) HPy h_BaseException;
22 HPy_ID(6) HPy h_Exception;
23 HPy_ID(7) HPy h_StopAsyncIteration;
24 HPy_ID(8) HPy h_StopIteration;
25 HPy_ID(9) HPy h_GeneratorExit;
26 HPy_ID(10) HPy h_ArithmeticError;
27 HPy_ID(11) HPy h_LookupError;
28 HPy_ID(12) HPy h_AssertionError;
29 HPy_ID(13) HPy h_AttributeError;
30 HPy_ID(14) HPy h_BufferError;
31 HPy_ID(15) HPy h_EOFError;
32 HPy_ID(16) HPy h_FloatingPointError;
33 HPy_ID(17) HPy h_OSError;
34 HPy_ID(18) HPy h_ImportError;
35 HPy_ID(19) HPy h_ModuleNotFoundError;
36 HPy_ID(20) HPy h_IndexError;
37 HPy_ID(21) HPy h_KeyError;
38 HPy_ID(22) HPy h_KeyboardInterrupt;
39 HPy_ID(23) HPy h_MemoryError;
40 HPy_ID(24) HPy h_NameError;
41 HPy_ID(25) HPy h_OverflowError;
42 HPy_ID(26) HPy h_RuntimeError;
43 HPy_ID(27) HPy h_RecursionError;
44 HPy_ID(28) HPy h_NotImplementedError;
45 HPy_ID(29) HPy h_SyntaxError;
46 HPy_ID(30) HPy h_IndentationError;
47 HPy_ID(31) HPy h_TabError;
48 HPy_ID(32) HPy h_ReferenceError;
49 HPy_ID(33) HPy h_SystemError;
50 HPy_ID(34) HPy h_SystemExit;
51 HPy_ID(35) HPy h_TypeError;
52 HPy_ID(36) HPy h_UnboundLocalError;
53 HPy_ID(37) HPy h_UnicodeError;
54 HPy_ID(38) HPy h_UnicodeEncodeError;

```

(continues on next page)

(continued from previous page)

```

55 HPy_ID(39) HPy h_UnicodeDecodeError;
56 HPy_ID(40) HPy h_UnicodeTranslateError;
57 HPy_ID(41) HPy h_ValueError;
58 HPy_ID(42) HPy h_ZeroDivisionError;
59 HPy_ID(43) HPy h_BlockingIOError;
60 HPy_ID(44) HPy h_BrokenPipeError;
61 HPy_ID(45) HPy h_ChildProcessError;
62 HPy_ID(46) HPy h_ConnectionError;
63 HPy_ID(47) HPy h_ConnectionAbortedError;
64 HPy_ID(48) HPy h_ConnectionRefusedError;
65 HPy_ID(49) HPy h_ConnectionResetError;
66 HPy_ID(50) HPy h_FileExistsError;
67 HPy_ID(51) HPy h_FileNotFoundError;
68 HPy_ID(52) HPy h_InterruptedError;
69 HPy_ID(53) HPy h_IsADirectoryError;
70 HPy_ID(54) HPy h_NotADirectoryError;
71 HPy_ID(55) HPy h_PermissionError;
72 HPy_ID(56) HPy h_ProcessLookupError;
73 HPy_ID(57) HPy h_TimeoutError;
74 // EnvironmentError, IOError and WindowsError are intentionally omitted (they
75 // are all aliases of OSError since Python 3.3).
76
77 /* Warnings */
78 HPy_ID(58) HPy h_Warning;
79 HPy_ID(59) HPy h_UserWarning;
80 HPy_ID(60) HPy h_DeprecationWarning;
81 HPy_ID(61) HPy h_PendingDeprecationWarning;
82 HPy_ID(62) HPy h_SyntaxWarning;
83 HPy_ID(63) HPy h_RuntimeWarning;
84 HPy_ID(64) HPy h_FutureWarning;
85 HPy_ID(65) HPy h_ImportWarning;
86 HPy_ID(66) HPy h_UnicodeWarning;
87 HPy_ID(67) HPy h_BytesWarning;
88 HPy_ID(68) HPy h_ResourceWarning;
89
90 /* Types */
91 HPy_ID(69) HPy h_BaseObjectType; /* built-in 'object' */
92 HPy_ID(70) HPy h_TypeType; /* built-in 'type' */
93 HPy_ID(71) HPy h_BoolType; /* built-in 'bool' */
94 HPy_ID(72) HPy h_LongType; /* built-in 'int' */
95 HPy_ID(73) HPy h_FloatType; /* built-in 'float' */
96 HPy_ID(74) HPy h_UnicodeType; /* built-in 'str' */
97 HPy_ID(75) HPy h_TupleType; /* built-in 'tuple' */
98 HPy_ID(76) HPy h_ListType; /* built-in 'list' */
99 HPy_ID(238) HPy h_ComplexType; /* built-in 'complex' */
100 HPy_ID(239) HPy h_BytesType; /* built-in 'bytes' */
101 HPy_ID(240) HPy h_MemoryViewType; /* built-in 'memoryview' */
102 HPy_ID(241) HPy h_CapsuleType; /* built-in 'capsule' */
103 HPy_ID(242) HPy h_SliceType; /* built-in 'slice' */
104
105 /* Reflection */
106 HPy_ID(243) HPy h_Builtins; /* dict of builtins */
107
108 #endif
109
110 HPy_ID(77)
111 HPy HPy_Dup(HPyContext *ctx, HPy h);

```

(continues on next page)

(continued from previous page)

```

112 HPy_ID(78)
113 void HPy_Close(HPyContext *ctx, HPy h);
114
115 HPy_ID(79)
116 HPy HPyLong_FromInt32_t(HPyContext *ctx, int32_t value);
117 HPy_ID(80)
118 HPy HPyLong_FromUInt32_t(HPyContext *ctx, uint32_t value);
119 HPy_ID(81)
120 HPy HPyLong_FromInt64_t(HPyContext *ctx, int64_t v);
121 HPy_ID(82)
122 HPy HPyLong_FromUInt64_t(HPyContext *ctx, uint64_t v);
123 HPy_ID(83)
124 HPy HPyLong_FromSize_t(HPyContext *ctx, size_t value);
125 HPy_ID(84)
126 HPy HPyLong_FromSsize_t(HPyContext *ctx, HPy_ssize_t value);
127
128 HPy_ID(85)
129 int32_t HPyLong_AsInt32_t(HPyContext *ctx, HPy h);
130 HPy_ID(86)
131 uint32_t HPyLong_AsUInt32_t(HPyContext *ctx, HPy h);
132 HPy_ID(87)
133 uint32_t HPyLong_AsUInt32_tMask(HPyContext *ctx, HPy h);
134 HPy_ID(88)
135 int64_t HPyLong_AsInt64_t(HPyContext *ctx, HPy h);
136 HPy_ID(89)
137 uint64_t HPyLong_AsUInt64_t(HPyContext *ctx, HPy h);
138 HPy_ID(90)
139 uint64_t HPyLong_AsUInt64_tMask(HPyContext *ctx, HPy h);
140 HPy_ID(91)
141 size_t HPyLong_AsSize_t(HPyContext *ctx, HPy h);
142 HPy_ID(92)
143 HPy_ssize_t HPyLong_AsSsize_t(HPyContext *ctx, HPy h);
144 HPy_ID(93)
145 void* HPyLong_AsVoidPtr(HPyContext *ctx, HPy h);
146 HPy_ID(94)
147 double HPyLong_AsDouble(HPyContext *ctx, HPy h);
148
149 HPy_ID(95)
150 HPy HPyFloat_FromDouble(HPyContext *ctx, double v);
151 HPy_ID(96)
152 double HPyFloat_AsDouble(HPyContext *ctx, HPy h);
153
154 HPy_ID(97)
155 HPy HPyBool_FromBool(HPyContext *ctx, bool v);
156
157
158 /* abstract.h */
159 HPy_ID(98)
160 HPy_ssize_t HPy_Length(HPyContext *ctx, HPy h);
161
162 HPy_ID(99)
163 int HPyNumber_Check(HPyContext *ctx, HPy h);
164 HPy_ID(100)
165 HPy HPy_Add(HPyContext *ctx, HPy h1, HPy h2);
166 HPy_ID(101)
167 HPy HPy_Subtract(HPyContext *ctx, HPy h1, HPy h2);
168 HPy_ID(102)

```

(continues on next page)

(continued from previous page)

```

169 HPy HPy_Multiply(HPyContext *ctx, HPy h1, HPy h2);
170 HPy_ID(103)
171 HPy HPy_MatrixMultiply(HPyContext *ctx, HPy h1, HPy h2);
172 HPy_ID(104)
173 HPy HPy_FloorDivide(HPyContext *ctx, HPy h1, HPy h2);
174 HPy_ID(105)
175 HPy HPy_TrueDivide(HPyContext *ctx, HPy h1, HPy h2);
176 HPy_ID(106)
177 HPy HPy_Remainder(HPyContext *ctx, HPy h1, HPy h2);
178 HPy_ID(107)
179 HPy HPy_Divmod(HPyContext *ctx, HPy h1, HPy h2);
180 HPy_ID(108)
181 HPy HPy_Power(HPyContext *ctx, HPy h1, HPy h2, HPy h3);
182 HPy_ID(109)
183 HPy HPy_Negative(HPyContext *ctx, HPy h1);
184 HPy_ID(110)
185 HPy HPy_Positive(HPyContext *ctx, HPy h1);
186 HPy_ID(111)
187 HPy HPy_Absolute(HPyContext *ctx, HPy h1);
188 HPy_ID(112)
189 HPy HPy_Invert(HPyContext *ctx, HPy h1);
190 HPy_ID(113)
191 HPy HPy_Lshift(HPyContext *ctx, HPy h1, HPy h2);
192 HPy_ID(114)
193 HPy HPy_Rshift(HPyContext *ctx, HPy h1, HPy h2);
194 HPy_ID(115)
195 HPy HPy_And(HPyContext *ctx, HPy h1, HPy h2);
196 HPy_ID(116)
197 HPy HPy_Xor(HPyContext *ctx, HPy h1, HPy h2);
198 HPy_ID(117)
199 HPy HPy_Or(HPyContext *ctx, HPy h1, HPy h2);
200 HPy_ID(118)
201 HPy HPy_Index(HPyContext *ctx, HPy h1);
202 HPy_ID(119)
203 HPy HPy_Long(HPyContext *ctx, HPy h1);
204 HPy_ID(120)
205 HPy HPy_Float(HPyContext *ctx, HPy h1);
206
207 HPy_ID(121)
208 HPy HPy_InPlaceAdd(HPyContext *ctx, HPy h1, HPy h2);
209 HPy_ID(122)
210 HPy HPy_InPlaceSubtract(HPyContext *ctx, HPy h1, HPy h2);
211 HPy_ID(123)
212 HPy HPy_InPlaceMultiply(HPyContext *ctx, HPy h1, HPy h2);
213 HPy_ID(124)
214 HPy HPy_InPlaceMatrixMultiply(HPyContext *ctx, HPy h1, HPy h2);
215 HPy_ID(125)
216 HPy HPy_InPlaceFloorDivide(HPyContext *ctx, HPy h1, HPy h2);
217 HPy_ID(126)
218 HPy HPy_InPlaceTrueDivide(HPyContext *ctx, HPy h1, HPy h2);
219 HPy_ID(127)
220 HPy HPy_InPlaceRemainder(HPyContext *ctx, HPy h1, HPy h2);
221 HPy_ID(128)
222 HPy HPy_InPlacePower(HPyContext *ctx, HPy h1, HPy h2, HPy h3);
223 HPy_ID(129)
224 HPy HPy_InPlaceLshift(HPyContext *ctx, HPy h1, HPy h2);
225 HPy_ID(130)

```

(continues on next page)

(continued from previous page)

```

226 HPy HPy_InPlaceRshift(HPyContext *ctx, HPy h1, HPy h2);
227 HPy_ID(131)
228 HPy HPy_InPlaceAnd(HPyContext *ctx, HPy h1, HPy h2);
229 HPy_ID(132)
230 HPy HPy_InPlaceXor(HPyContext *ctx, HPy h1, HPy h2);
231 HPy_ID(133)
232 HPy HPy_InPlaceOr(HPyContext *ctx, HPy h1, HPy h2);
233
234 HPy_ID(134)
235 int HPyCallable_Check(HPyContext *ctx, HPy h);
236
237 /**
238  * Call a Python object.
239  *
240  * :param ctx:
241  *     The execution context.
242  * :param callable:
243  *     A handle to the Python object to call (must not be ``HPy_NULL``).
244  * :param args:
245  *     A handle to a tuple containing the positional arguments (must not be
246  *     ``HPy_NULL`` but can, of course, be empty).
247  * :param kw:
248  *     A handle to a Python dictionary containing the keyword arguments (may be
249  *     ``HPy_NULL``).
250  *
251  * :returns:
252  *     The result of the call on success, or ``HPy_NULL`` in case of an error.
253  */
254 HPy_ID(135)
255 HPy HPy_CallTupleDict(HPyContext *ctx, HPy callable, HPy args, HPy kw);
256
257 /**
258  * Call a Python object.
259  *
260  * :param ctx:
261  *     The execution context.
262  * :param callable:
263  *     A handle to the Python object to call (must not be ``HPy_NULL``).
264  * :param args:
265  *     A pointer to an array of positional and keyword arguments. This argument
266  *     must not be ``NULL`` if ``nargs > 0`` or
267  *     ``HPy_Length(ctx, kwnames) > 0``.
268  * :param nargs:
269  *     The number of positional arguments in ``args``.
270  * :param kwnames:
271  *     A handle to the tuple of keyword argument names (may be ``HPy_NULL``).
272  *     The values of the keyword arguments are also passed in ``args`` appended
273  *     to the positional arguments. Argument ``nargs`` does not include the
274  *     keyword argument count.
275  *
276  * :returns:
277  *     The result of the call on success, or ``HPy_NULL`` in case of an error.
278  */
279 HPy_ID(261)
280 HPy HPy_Call(HPyContext *ctx, HPy callable, const HPy *args, size_t nargs, HPy_
↳ kwnames);
281

```

(continues on next page)

(continued from previous page)

```

282  /**
283   * Call a method of a Python object.
284   *
285   * :param ctx:
286   *     The execution context.
287   * :param name:
288   *     A handle to the name (a Unicode object) of the method. Must not be
289   *     ``HPy_NULL``.
290   * :param args:
291   *     A pointer to an array of the arguments. The receiver is ``args[0]``, and
292   *     the positional and keyword arguments are starting at ``args[1]``. This
293   *     argument must not be ``NULL`` since a receiver is always required.
294   * :param nargs:
295   *     The number of positional arguments in ``args`` including the receiver at
296   *     ``args[0]`` (therefore, ``nargs`` must be at least ``1``).
297   * :param kwnames:
298   *     A handle to the tuple of keyword argument names (may be ``HPy_NULL``).
299   *     The values of the keyword arguments are also passed in ``args`` appended
300   *     to the positional arguments. Argument ``nargs`` does not include the
301   *     keyword argument count.
302   *
303   * :returns:
304   *     The result of the call on success, or ``HPy_NULL`` in case of an error.
305   */
306  HPy_ID(262)
307  HPy HPy_CallMethod(HPyContext *ctx, HPy name, const HPy *args, size_t nargs, HPy_
↳ kwnames);
308
309  /* pyerrors.h */
310  HPy_ID(136)
311  void HPy_FatalError(HPyContext *ctx, const char *message);
312  HPy_ID(137)
313  HPy HPyErr_SetString(HPyContext *ctx, HPy h_type, const char *utf8_message);
314  HPy_ID(138)
315  HPy HPyErr_SetObject(HPyContext *ctx, HPy h_type, HPy h_value);
316
317  /**
318   * Similar to :c:func:`HPyErr_SetFromErrnoWithFilenameObjects` but takes one
319   * filename (a C string) that will be decoded using
320   * :c:func:`HPyUnicode_DecodeFSDefault`.
321   *
322   * :param ctx:
323   *     The execution context.
324   * :param h_type:
325   *     The exception type to raise.
326   * :param filename_fsencoded:
327   *     a filename; may be ``NULL``
328   *
329   * :return:
330   *     always returns ``HPy_NULL``
331   */
332  HPy_ID(139)
333  HPy HPyErr_SetFromErrnoWithFilename(HPyContext *ctx, HPy h_type, const char *filename_
↳ fsencoded);
334
335  /**
336   * A convenience function to raise an exception when a C library function has

```

(continues on next page)

(continued from previous page)

```

337 * returned an error and set the C variable ``errno``. It constructs an
338 * instance of the provided exception type ``h_type`` by calling
339 * ``h_type(errno, strerror(errno), filename1, 0, filename2)``. The exception
340 * instance is then raised.
341 *
342 * :param ctx:
343 *     The execution context.
344 * :param h_type:
345 *     The exception type to raise.
346 * :param filename1:
347 *     A filename; may be ``HPy_NULL``. In the case of ``h_type`` is the
348 *     ``OSError`` exception, this is used to define the filename attribute of
349 *     the exception instance.
350 * :param filename2:
351 *     another filename argument; may be ``HPy_NULL``
352 *
353 * :return:
354 *     always returns ``HPy_NULL``
355 */
356 HPy_ID(140)
357 HPy HPyErr_SetFromErrnoWithFilenameObjects(HPyContext *ctx, HPy h_type, HPy filename1,
358 ↪ HPy filename2);
359 /* note: HPyErr_Occurred() returns a flag 0-or-1, instead of a 'PyObject *' */
360 HPy_ID(141)
361 int HPyErr_Occurred(HPyContext *ctx);
362 HPy_ID(142)
363 int HPyErr_ExceptionMatches(HPyContext *ctx, HPy exc);
364 HPy_ID(143)
365 HPy HPyErr_NoMemory(HPyContext *ctx);
366 HPy_ID(144)
367 void HPyErr_Clear(HPyContext *ctx);
368 HPy_ID(145)
369 HPy HPyErr_NewException(HPyContext *ctx, const char *utf8_name, HPy base, HPy dict);
370 HPy_ID(146)
371 HPy HPyErr_NewExceptionWithDoc(HPyContext *ctx, const char *utf8_name, const char_
372 ↪ *utf8_doc, HPy base, HPy dict);
373 HPy_ID(147)
374 int HPyErr_WarnEx(HPyContext *ctx, HPy category, const char *utf8_message, HPy_ssize_
375 ↪ t stack_level);
376 HPy_ID(148)
377 void HPyErr_WriteUnraisable(HPyContext *ctx, HPy obj);
378
379 /* object.h */
380 HPy_ID(149)
381 int HPy_IsTrue(HPyContext *ctx, HPy h);
382
383 /**
384 * Create a type from a :c:struct:``HPyType_Spec`` and an additional list of
385 * specification parameters.
386 *
387 * :param ctx:
388 *     The execution context.
389 * :param spec:
390 *     The type spec to use to create the type.
391 * :param params:
392 *     A 0-terminated list of type specification parameters or ``NULL``.
393 */

```

(continues on next page)



(continued from previous page)

```

391  * :returns: a handle of the created type on success, ``HPy_NULL`` on failure.
392  */
393  HPy_ID(150)
394  HPy HPyType_FromSpec(HPyContext *ctx, HPyType_Spec *spec,
395                      HPyType_SpecParam *params);
396  HPy_ID(151)
397  HPy HPyType_GenericNew(HPyContext *ctx, HPy type, const HPy *args, HPy_ssize_t nargs,
398                      ↪HPy kw);
399  HPy_ID(152)
400  HPy HPy_GetAttr(HPyContext *ctx, HPy obj, HPy name);
401  HPy_ID(153)
402  HPy HPy_GetAttr_s(HPyContext *ctx, HPy obj, const char *utf8_name);
403
404  HPy_ID(154)
405  int HPy_HasAttr(HPyContext *ctx, HPy obj, HPy name);
406  HPy_ID(155)
407  int HPy_HasAttr_s(HPyContext *ctx, HPy obj, const char *utf8_name);
408
409  HPy_ID(156)
410  int HPy_SetAttr(HPyContext *ctx, HPy obj, HPy name, HPy value);
411  HPy_ID(157)
412  int HPy_SetAttr_s(HPyContext *ctx, HPy obj, const char *utf8_name, HPy value);
413
414  HPy_ID(158)
415  HPy HPy_GetItem(HPyContext *ctx, HPy obj, HPy key);
416  HPy_ID(159)
417  HPy HPy_GetItem_i(HPyContext *ctx, HPy obj, HPy_ssize_t idx);
418  HPy_ID(160)
419  HPy HPy_GetItem_s(HPyContext *ctx, HPy obj, const char *utf8_key);
420
421  HPy_ID(161)
422  int HPy_Contains(HPyContext *ctx, HPy container, HPy key);
423
424  HPy_ID(162)
425  int HPy_SetItem(HPyContext *ctx, HPy obj, HPy key, HPy value);
426  HPy_ID(163)
427  int HPy_SetItem_i(HPyContext *ctx, HPy obj, HPy_ssize_t idx, HPy value);
428  HPy_ID(164)
429  int HPy_SetItem_s(HPyContext *ctx, HPy obj, const char *utf8_key, HPy value);
430
431  HPy_ID(235)
432  int HPy_DelItem(HPyContext *ctx, HPy obj, HPy key);
433  HPy_ID(236)
434  int HPy_DelItem_i(HPyContext *ctx, HPy obj, HPy_ssize_t idx);
435  HPy_ID(237)
436  int HPy_DelItem_s(HPyContext *ctx, HPy obj, const char *utf8_key);
437
438  /**
439   * Returns the type of the given object ``obj``.
440   *
441   * On failure, raises ``SystemError`` and returns ``HPy_NULL``. This is
442   * equivalent to the Python expression ``type(obj)``.
443   *
444   * :param ctx:
445   *     The execution context.
446   * :param obj:

```

(continues on next page)

(continued from previous page)

```

447 *     a Python object (must not be ``HPy_NULL``)
448 *
449 * :returns:
450 *     The type of ``obj`` or ``HPy_NULL`` in case of errors.
451 */
452 HPy_ID(165)
453 HPy HPy_Type(HPyContext *ctx, HPy obj);
454
455 /**
456 * Checks if ``ob`` is an instance of ``type`` or any subtype of ``type``.
457 *
458 * :param ctx:
459 *     The execution context.
460 * :param obj:
461 *     a Python object (must not be ``HPy_NULL``)
462 * :param type:
463 *     A Python type object. This argument must not be ``HPy_NULL`` and must be
464 *     a type (i.e. it must inherit from Python ``type``). If this is not the
465 *     case, the behavior is undefined (verification of the argument is only
466 *     done in debug mode).
467 *
468 * :returns:
469 *     Non-zero if object ``obj`` is an instance of type ``type`` or an instance
470 *     of a subtype of ``type``, and ``0`` otherwise.
471 */
472 HPy_ID(166)
473 int HPy_TypeCheck(HPyContext *ctx, HPy obj, HPy type);
474
475 /**
476 * Return the type's name.
477 *
478 * Equivalent to getting the type's ``__name__`` attribute. If you want to
479 * retrieve the type's name as a handle that refers to a ``str``, then just use
480 * ``HPy_GetAttr_s(ctx, type, "__name__")``.
481 *
482 * :param ctx:
483 *     The execution context.
484 * :param type:
485 *     A Python type object. This argument must not be ``HPy_NULL`` and must be
486 *     a type (i.e. it must inherit from Python ``type``). If this is not the
487 *     case, the behavior is undefined (verification of the argument is only
488 *     done in debug mode).
489 *
490 * :returns:
491 *     The name of the type as C string (UTF-8 encoded) or ``NULL`` in case of
492 *     an error. The returned pointer is read-only and guaranteed to be valid as
493 *     long as the handle ``type`` is valid.
494 */
495 HPy_ID(253)
496 const char *HPyType_GetName(HPyContext *ctx, HPy type);
497
498 /**
499 * Checks if ``sub`` is a subtype of ``type``.
500 *
501 * This function only checks for actual subtypes, which means that
502 * ``__subclasscheck__()`` is not called on ``type``.
503 */

```

(continues on next page)

(continued from previous page)

```

504 * :param ctx:
505 *     The execution context.
506 * :param sub:
507 *     A Python type object. This argument must not be ``HPy_NULL`` and must be
508 *     a type (i.e. it must inherit from Python ``type``). If this is not the
509 *     case, the behavior is undefined (verification of the argument is only
510 *     done in debug mode).
511 * :param type:
512 *     A Python type object. This argument must not be ``HPy_NULL`` and must be
513 *     a type (i.e. it must inherit from Python ``type``). If this is not the
514 *     case, the behavior is undefined (verification of the argument is only
515 *     done in debug mode).
516 *
517 * :returns:
518 *     Non-zero if ``sub`` is a subtype of ``type``.
519 */
520 HPy_ID(254)
521 int HPyType_IsSubtype(HPyContext *ctx, HPy sub, HPy type);
522
523 HPy_ID(167)
524 int HPy_Is(HPyContext *ctx, HPy obj, HPy other);
525
526 HPy_ID(168)
527 void* _HPy_AsStruct_Object(HPyContext *ctx, HPy h);
528 HPy_ID(169)
529 void* _HPy_AsStruct_Legacy(HPyContext *ctx, HPy h);
530 HPy_ID(228)
531 void* _HPy_AsStruct_Type(HPyContext *ctx, HPy h);
532 HPy_ID(229)
533 void* _HPy_AsStruct_Long(HPyContext *ctx, HPy h);
534 HPy_ID(230)
535 void* _HPy_AsStruct_Float(HPyContext *ctx, HPy h);
536 HPy_ID(231)
537 void* _HPy_AsStruct_Unicode(HPyContext *ctx, HPy h);
538 HPy_ID(232)
539 void* _HPy_AsStruct_Tuple(HPyContext *ctx, HPy h);
540 HPy_ID(233)
541 void* _HPy_AsStruct_List(HPyContext *ctx, HPy h);
542 HPy_ID(234)
543 HPyType_BuiltinShape _HPyType_GetBuiltinShape(HPyContext *ctx, HPy h_type);
544
545 HPy_ID(170)
546 HPy _HPy_New(HPyContext *ctx, HPy h_type, void **data);
547
548 HPy_ID(171)
549 HPy HPy_Repr(HPyContext *ctx, HPy obj);
550 HPy_ID(172)
551 HPy HPy_Str(HPyContext *ctx, HPy obj);
552 HPy_ID(173)
553 HPy HPy_ASCII(HPyContext *ctx, HPy obj);
554 HPy_ID(174)
555 HPy HPy_Bytes(HPyContext *ctx, HPy obj);
556
557 HPy_ID(175)
558 HPy HPy_RichCompare(HPyContext *ctx, HPy v, HPy w, int op);
559 HPy_ID(176)
560 int HPy_RichCompareBool(HPyContext *ctx, HPy v, HPy w, int op);

```

(continues on next page)

(continued from previous page)

```

561
562 HPy_ID(177)
563 HPy_hash_t HPy_Hash(HPyContext *ctx, HPy obj);
564
565 /* bytesobject.h */
566 HPy_ID(178)
567 int HPyBytes_Check(HPyContext *ctx, HPy h);
568 HPy_ID(179)
569 HPy_ssize_t HPyBytes_Size(HPyContext *ctx, HPy h);
570 HPy_ID(180)
571 HPy_ssize_t HPyBytes_GET_SIZE(HPyContext *ctx, HPy h);
572 HPy_ID(181)
573 const char* HPyBytes_AsString(HPyContext *ctx, HPy h);
574 HPy_ID(182)
575 const char* HPyBytes_AS_STRING(HPyContext *ctx, HPy h);
576 HPy_ID(183)
577 HPy HPyBytes_FromString(HPyContext *ctx, const char *bytes);
578 HPy_ID(184)
579 HPy HPyBytes_FromStringAndSize(HPyContext *ctx, const char *bytes, HPy_ssize_t len);
580
581 /* unicodeobject.h */
582 HPy_ID(185)
583 HPy HPyUnicode_FromString(HPyContext *ctx, const char *utf8);
584 HPy_ID(186)
585 int HPyUnicode_Check(HPyContext *ctx, HPy h);
586 HPy_ID(187)
587 HPy HPyUnicode_AsASCIIString(HPyContext *ctx, HPy h);
588 HPy_ID(188)
589 HPy HPyUnicode_AsLatin1String(HPyContext *ctx, HPy h);
590 HPy_ID(189)
591 HPy HPyUnicode_AsUTF8String(HPyContext *ctx, HPy h);
592 HPy_ID(190)
593 const char* HPyUnicode_AsUTF8AndSize(HPyContext *ctx, HPy h, HPy_ssize_t *size);
594 HPy_ID(191)
595 HPy HPyUnicode_FromWideChar(HPyContext *ctx, const wchar_t *w, HPy_ssize_t size);
596 HPy_ID(192)
597 HPy HPyUnicode_DecodeFSDefault(HPyContext *ctx, const char *v);
598 HPy_ID(193)
599 HPy HPyUnicode_DecodeFSDefaultAndSize(HPyContext *ctx, const char *v, HPy_ssize_t
↳ size);
600 HPy_ID(194)
601 HPy HPyUnicode_EncodeFSDefault(HPyContext *ctx, HPy h);
602 HPy_ID(195)
603 HPy_UCS4 HPyUnicode_ReadChar(HPyContext *ctx, HPy h, HPy_ssize_t index);
604 HPy_ID(196)
605 HPy HPyUnicode_DecodeASCII(HPyContext *ctx, const char *ascii, HPy_ssize_t size,
↳ const char *errors);
606 HPy_ID(197)
607 HPy HPyUnicode_DecodeLatin1(HPyContext *ctx, const char *latin1, HPy_ssize_t size,
↳ const char *errors);
608
609 /**
610  * Decode a bytes-like object to a Unicode object.
611  *
612  * The bytes of the bytes-like object are decoded according to the given
613  * encoding and using the error handling defined by ``errors``.
614  *

```

(continues on next page)

(continued from previous page)

```

615 * :param ctx:
616 *     The execution context.
617 * :param obj:
618 *     A bytes-like object. This can be, for example, Python *bytes*,
619 *     *bytearray*, *memoryview*, *array.array* and objects that support the
620 *     Buffer protocol. If this argument is HPy_NULL, a SystemError will
621 *     be raised. If the argument is not a bytes-like object, a TypeError
622 *     will be raised.
623 * :param encoding:
624 *     The name (UTF-8 encoded C string) of the encoding to use. If the encoding
625 *     does not exist, a LookupError will be raised. If this argument is
626 *     NULL, the default encoding UTF-8 will be used.
627 * :param errors:
628 *     The error handling (UTF-8 encoded C string) to use when decoding. The
629 *     possible values depend on the used encoding. This argument may be
630 *     NULL in which case it will default to "strict".
631 *
632 * :returns:
633 *     A handle to a str object created from the decoded bytes or
634 *     HPy_NULL in case of errors.
635 */
636 HPy_ID(255)
637 HPy HPyUnicode_FromEncodedObject(HPyContext *ctx, HPy obj, const char *encoding,
638 ↪const char *errors);
639
640 /**
641 * Return a substring of str, from character index start (included) to
642 * character index end (excluded).
643 *
644 * Indices start and end must not be negative, otherwise an
645 * IndexError will be raised. If start >= len(str) or if
646 * end < start, an empty string will be returned. If end > len(str) then
647 * end == len(str) will be assumed.
648 *
649 * :param ctx:
650 *     The execution context.
651 * :param str:
652 *     A Python Unicode object (must not be HPy_NULL). Otherwise, the
653 *     behavior is undefined (verification of the argument is only done in
654 *     debug mode).
655 * :param start:
656 *     The non-negative start index (inclusive).
657 * :param end:
658 *     The non-negative end index (exclusive).
659 *
660 * :returns:
661 *     The requested substring or HPy_NULL in case of an error.
662 */
663 HPy_ID(256)
664 HPy HPyUnicode_Substring(HPyContext *ctx, HPy str, HPy_ssize_t start, HPy_ssize_t
665 ↪end);
666
667 /* listobject.h */
668 HPy_ID(198)
669 int HPyList_Check(HPyContext *ctx, HPy h);
670 HPy_ID(199)
671 HPy HPyList_New(HPyContext *ctx, HPy_ssize_t len);

```

(continues on next page)

(continued from previous page)

```

670 HPy_ID(200)
671 int HPyList_Append(HPyContext *ctx, HPy h_list, HPy h_item);
672
673 /* dictobject.h */
674
675 /**
676  * Tests if an object is an instance of a Python dict.
677  *
678  :param ctx:
679      The execution context.
680  :param h:
681      A handle to an arbitrary object (must not be ``HPy_NULL``).
682  *
683  :returns:
684      Non-zero if object ``h`` is an instance of type ``dict`` or an instance
685      of a subtype of ``dict``, and ``0`` otherwise.
686  */
687 HPy_ID(201)
688 int HPyDict_Check(HPyContext *ctx, HPy h);
689
690 /**
691  * Creates a new empty Python dictionary.
692  *
693  :param ctx:
694      The execution context.
695  *
696  :returns:
697      A handle to the new and empty Python dictionary or ``HPy_NULL`` in case
698      of an error.
699  */
700 HPy_ID(202)
701 HPy HPyDict_New(HPyContext *ctx);
702
703 /**
704  * Returns a list of all keys from the dictionary.
705  *
706  * Note: This function will directly access the storage of the dict object and
707  * therefore ignores if method ``keys`` was overwritten.
708  *
709  :param ctx:
710      The execution context.
711  :param h:
712      A Python dict object. If this argument is ``HPy_NULL`` or not an
713      instance of a Python dict, a ``SystemError`` will be raised.
714  *
715  :returns:
716      A Python list object containing all keys of the given dictionary or
717      ``HPy_NULL`` in case of an error.
718  */
719 HPy_ID(257)
720 HPy HPyDict_Keys(HPyContext *ctx, HPy h);
721
722 /**
723  * Creates a copy of the provided Python dict object.
724  *
725  :param ctx:
726      The execution context.

```

(continues on next page)

(continued from previous page)

```

727 * :param h:
728 *     A Python dict object. If this argument is ``HPy_NULL`` or not an
729 *     instance of a Python dict, a ``SystemError`` will be raised.
730 *
731 * :returns:
732 *     Return a new dictionary that contains the same key-value pairs as ``h``
733 *     or ``HPy_NULL`` in case of an error.
734 */
735 HPy_ID(258)
736 HPy HPyDict_Copy(HPyContext *ctx, HPy h);
737
738 /* tupleobject.h */
739 HPy_ID(203)
740 int HPyTuple_Check(HPyContext *ctx, HPy h);
741 HPy_ID(204)
742 HPy HPyTuple_FromArray(HPyContext *ctx, HPy items[], HPy_ssize_t n);
743 // note: HPyTuple_Pack is implemented as a macro in common/macros.h
744
745 /* sliceobject.h */
746
747 /**
748 * Extract the start, stop and step data members from a slice object as C
749 * integers.
750 *
751 * The slice members may be arbitrary int-like objects. If they are not Python
752 * int objects, they will be coerced to int objects by calling their
753 * ``__index__`` method.
754 *
755 * If a slice member value is out of bounds, it will be set to the maximum value
756 * of ``HPy_ssize_t`` if the member was a positive number, or to the minimum
757 * value of ``HPy_ssize_t`` if it was a negative number.
758 *
759 * :param ctx:
760 *     The execution context.
761 * :param slice:
762 *     A handle to a Python slice object. This argument must be a slice object
763 *     and must not be ``HPy_NULL``. Otherwise, behavior is undefined.
764 * :param start:
765 *     A pointer to a variable where to write the unpacked slice start. Must not
766 *     be ``NULL``.
767 * :param end:
768 *     A pointer to a variable where to write the unpacked slice end. Must not
769 * :param step:
770 *     A pointer to a variable where to write the unpacked slice step. Must not
771 *     be ``NULL``.
772 *
773 * :returns:
774 *     ``-1`` on error, ``0`` on success
775 */
776 HPy_ID(259)
777 int HPySlice_Unpack(HPyContext *ctx, HPy slice, HPy_ssize_t *start, HPy_ssize_t *stop,
778 ↪ HPy_ssize_t *step);
779
780 /* import.h */
781 HPy_ID(205)
782 HPy HPyImport_ImportModule(HPyContext *ctx, const char *utf8_name);
783

```

(continues on next page)

(continued from previous page)

```

783  /* pycapsule.h */
784  HPy_ID(244)
785  HPy HPyCapsule_New(HPyContext *ctx, void *pointer, const char *utf8_name, HPyCapsule_
↳Destructor *destructor);
786  HPy_ID(245)
787  void* HPyCapsule_Get(HPyContext *ctx, HPy capsule, _HPyCapsule_key key, const char_
↳*utf8_name);
788  HPy_ID(246)
789  int HPyCapsule_IsValid(HPyContext *ctx, HPy capsule, const char *utf8_name);
790  HPy_ID(247)
791  int HPyCapsule_Set(HPyContext *ctx, HPy capsule, _HPyCapsule_key key, void *value);
792
793  /* integration with the old CPython API */
794  HPy_ID(206)
795  HPy HPy_FromPyObject(HPyContext *ctx, cpy_PyObject *obj);
796  HPy_ID(207)
797  cpy_PyObject *HPy_AsPyObject(HPyContext *ctx, HPy h);
798
799  /* internal helpers which need to be exposed to modules for practical reasons :( */
800  HPy_ID(208)
801  void _HPy_CallRealFunctionFromTrampoline(HPyContext *ctx,
802                                           HPyFunc_Signature sig,
803                                           HPyCFunction func,
804                                           void *args);
805
806  /* Builders */
807
808  /**
809   * Create a new list builder for ``size`` elements. The builder is then able to
810   * take at most ``size`` elements. This function does not raise any
811   * exception (even if running out of memory).
812   *
813   * :param ctx:
814   *     The execution context.
815   * :param size:
816   *     The number of elements to hold.
817   */
818  HPy_ID(209)
819  HPyListBuilder HPyListBuilder_New(HPyContext *ctx, HPy_ssize_t size);
820
821  /**
822   * Assign an element to a certain index of the builder. Valid indices are in
823   * range ``0 <= index < size`` where ``size`` is the value passed to
824   * :c:func:`HPyListBuilder_New`. This function does not raise any exception.
825   *
826   * :param ctx:
827   *     The execution context.
828   * :param builder:
829   *     A list builder handle.
830   * :param index:
831   *     The index to assign the object to.
832   * :param h_item:
833   *     An HPy handle of the object to store or ``HPy_NULL``. Please note that
834   *     HPy **never** steals handles and so, ``h_item`` needs to be closed by
835   *     the caller.
836   */
837  HPy_ID(210)

```

(continues on next page)



(continued from previous page)

```

838 void HPyListBuilder_Set(HPyContext *ctx, HPyListBuilder builder,
839                        HPy_ssize_t index, HPy h_item);
840
841 /**
842  * Build a list from a list builder.
843  *
844  * :param ctx:
845  *     The execution context.
846  * :param builder:
847  *     A list builder handle.
848  *
849  * :returns:
850  *     An HPy handle to a list containing the values inserted with
851  *     :c:func:`HPyListBuilder_Set` or ``HPy_NULL`` in case an error occurred
852  *     during building or earlier when creating the builder or setting the
853  *     items.
854  */
855 HPy_ID(211)
856 HPy HPyListBuilder_Build(HPyContext *ctx, HPyListBuilder builder);
857
858 /**
859  * Cancel building of a tuple and free any acquired resources.
860  * This function ignores if any error occurred previously when using the tuple
861  * builder.
862  *
863  * :param ctx:
864  *     The execution context.
865  * :param builder:
866  *     A tuple builder handle.
867  */
868 HPy_ID(212)
869 void HPyListBuilder_Cancel(HPyContext *ctx, HPyListBuilder builder);
870
871 /**
872  * Create a new tuple builder for ``size`` elements. The builder is then able
873  * to take at most ``size`` elements. This function does not raise any
874  * exception (even if running out of memory).
875  *
876  * :param ctx:
877  *     The execution context.
878  * :param size:
879  *     The number of elements to hold.
880  */
881 HPy_ID(213)
882 HPyTupleBuilder HPyTupleBuilder_New(HPyContext *ctx, HPy_ssize_t size);
883
884 /**
885  * Assign an element to a certain index of the builder. Valid indices are in
886  * range ``0 <= index < size`` where ``size`` is the value passed to
887  * :c:func:`HPyTupleBuilder_New`. This function does not raise any exception.
888  *
889  * :param ctx:
890  *     The execution context.
891  * :param builder:
892  *     A tuple builder handle.
893  * :param index:
894  *     The index to assign the object to.

```

(continues on next page)

(continued from previous page)

```

895  * :param h_item:
896  *     An HPy handle of the object to store or ``HPy_NULL``. Please note that
897  *     HPy never steals handles and so, ``h_item`` needs to be closed by
898  *     the caller.
899  */
900  HPy_ID(214)
901  void HPyTupleBuilder_Set(HPyContext *ctx, HPyTupleBuilder builder,
902                          HPy_ssize_t index, HPy h_item);
903
904  /**
905   * Build a tuple from a tuple builder.
906   *
907   * :param ctx:
908   *     The execution context.
909   * :param builder:
910   *     A tuple builder handle.
911   *
912   * :returns:
913   *     An HPy handle to a tuple containing the values inserted with
914   *     :c:func:`HPyTupleBuilder_Set` or ``HPy_NULL`` in case an error occurred
915   *     during building or earlier when creating the builder or setting the
916   *     items.
917   */
918  HPy_ID(215)
919  HPy HPyTupleBuilder_Build(HPyContext *ctx, HPyTupleBuilder builder);
920
921  /**
922   * Cancel building of a tuple and free any acquired resources.
923   * This function ignores if any error occurred previously when using the tuple
924   * builder.
925   *
926   * :param ctx:
927   *     The execution context.
928   * :param builder:
929   *     A tuple builder handle.
930   */
931  HPy_ID(216)
932  void HPyTupleBuilder_Cancel(HPyContext *ctx, HPyTupleBuilder builder);
933
934  /* Helper for correctly closing handles */
935
936  HPy_ID(217)
937  HPyTracker HPyTracker_New(HPyContext *ctx, HPy_ssize_t size);
938  HPy_ID(218)
939  int HPyTracker_Add(HPyContext *ctx, HPyTracker ht, HPy h);
940  HPy_ID(219)
941  void HPyTracker_ForgetAll(HPyContext *ctx, HPyTracker ht);
942  HPy_ID(220)
943  void HPyTracker_Close(HPyContext *ctx, HPyTracker ht);
944
945  /**
946   * HPyFields should be used ONLY in parts of memory which is known to the GC,
947   * e.g. memory allocated by HPy_New:
948   *
949   * - NEVER declare a local variable of type HPyField
950   * - NEVER use HPyField on a struct allocated by e.g. malloc()
951   */

```

(continues on next page)

(continued from previous page)

```

952 * **CPython's note**: contrary to PyObject*, you don't need to manually
953 * manage refcounting when using HPyField: if you use HPyField_Store to
954 * overwrite an existing value, the old object will be automatically decref.
955 * This means that you CANNOT use HPyField_Store to write memory which
956 * contains uninitialized values, because it would try to decref a dangling
957 * pointer.
958 *
959 * Note that HPy_New automatically zeroes the memory it allocates, so
960 * everything works well out of the box. In case you are using manually
961 * allocated memory, you should initialize the HPyField to HPyField_NULL.
962 *
963 * Note the difference:
964 *
965 * - ``obj->f = HPyField_NULL``: this should be used only to initialize
966 *   uninitialized memory. If you use it to overwrite a valid HPyField, you
967 *   will cause a memory leak (at least on CPython)
968 *
969 * - HPyField_Store(ctx, &obj->f, HPy_NULL): this does the right thing and
970 *   decref the old value. However, you CANNOT use it if the memory is not
971 *   initialized.
972 *
973 * Note: target_object and source_object are there in case an implementation
974 * needs to add write and/or read barriers on the objects. They are ignored by
975 * CPython but e.g. PyPy needs a write barrier.
976 */
977 HPy_ID(221)
978 void HPyField_Store(HPyContext *ctx, HPy target_object, HPyField *target_field, HPy_
979 ↪h);
980 HPy_ID(222)
981 HPy HPyField_Load(HPyContext *ctx, HPy source_object, HPyField source_field);
982
983 /**
984 * Leaving Python execution: for releasing GIL and other use-cases.
985 *
986 * In most situations, users should prefer using convenience macros:
987 * HPy_BEGIN_LEAVE_PYTHON(context)/HPy_END_LEAVE_PYTHON(context)
988 *
989 * HPy extensions may leave Python execution when running Python independent
990 * code: long-running computations or blocking operations. When an extension
991 * has left the Python execution it must not call any HPy API other than
992 * HPy_ReenterPythonExecution. It can access pointers returned by HPy API,
993 * e.g., HPyUnicode_AsUTF8String, provided that they are valid at the point
994 * of calling HPy_LeavePythonExecution.
995 *
996 * Python execution must be reentered on the same thread as where it was left.
997 * The leave/enter calls must not be nested. Debug mode will, in the future,
998 * enforce these constraints.
999 *
1000 * Python implementations may use this knowledge however they wish. The most
1001 * obvious use case is to release the GIL, in which case the
1002 * HPy_BEGIN_LEAVE_PYTHON/HPy_END_LEAVE_PYTHON becomes equivalent to
1003 * Py_BEGIN_ALLOW_THREADS/Py_END_ALLOW_THREADS.
1004 */
1005 HPy_ID(223)
1006 void HPy_ReenterPythonExecution(HPyContext *ctx, HPyThreadState state);
1007 HPy_ID(224)
1008 HPyThreadState HPy_LeavePythonExecution(HPyContext *ctx);

```

(continues on next page)

(continued from previous page)

```

1008
1009 /**
1010  * HPyGlobal is an alternative to module state. HPyGlobal must be a statically
1011  * allocated C global variable registered in HPyModuleDef.globals array.
1012  * A HPyGlobal can be used only after the HPy module where it is registered was
1013  * created using HPyModule_Create.
1014  *
1015  * HPyGlobal serves as an identifier of a Python object that should be globally
1016  * available per one Python interpreter. Python objects referenced by HPyGlobals
1017  * are destroyed automatically on the interpreter exit (not necessarily the
1018  * process exit).
1019  *
1020  * HPyGlobal instance does not allow anything else but loading and storing
1021  * a HPy handle using a HPyContext. Even if the HPyGlobal C variable may
1022  * be shared between threads or different interpreter instances within one
1023  * process, the API to load and store a handle from HPyGlobal is thread-safe (but
1024  * like any other HPy API must not be called in HPy_LeavePythonExecution blocks).
1025  *
1026  * Given that a handle to object X1 is stored to HPyGlobal using HPyContext of
1027  * Python interpreter I1, then loading a handle from the same HPyGlobal using
1028  * HPyContext of Python interpreter I1 should give a handle to the same object
1029  * X1. Another Python interpreter I2 running within the same process and using
1030  * the same HPyGlobal variable will not be able to load X1 from it, it will have
1031  * its own view on what is stored in the given HPyGlobal.
1032  *
1033  * Python interpreters may use indirection to isolate different interpreter
1034  * instances, but alternative techniques such as copy-on-write or immortal
1035  * objects can be used to avoid that indirection (even selectively on per
1036  * object basis using tagged pointers).
1037  *
1038  * CPython HPy implementation may even provide configuration option that
1039  * switches between a faster version that directly stores PyObject* to
1040  * HPyGlobal but does not support subinterpreters, or a version that supports
1041  * subinterpreters. For now, CPython HPy always stores PyObject* directly
1042  * to HPyGlobal.
1043  *
1044  * While the standard implementation does not fully enforce the documented
1045  * contract, the HPy debug mode will enforce it (not implemented yet).
1046  *
1047  * **Implementation notes:**
1048  * All Python interpreters running in one process must be compatible, because
1049  * they will share all HPyGlobal C level variables. The internal data stored
1050  * in HPyGlobal are specific for each HPy implementation, each implementation
1051  * is also responsible for handling thread-safety when initializing the
1052  * internal data in HPyModule_Create. Note that HPyModule_Create may be called
1053  * concurrently depending on the semantics of the Python implementation (GIL vs
1054  * no GIL) and also depending on the whether there may be multiple instances of
1055  * given Python interpreter running within the same process. In the future, HPy
1056  * ABI may include a contract that internal data of each HPyGlobal must be
1057  * initialized to its address using atomic write and HPy implementations will
1058  * not be free to choose what to store in HPyGlobal, however, this will allow
1059  * multiple different HPy implementations within one process. This contract may
1060  * also be activated only by some runtime option, letting the HPy implementation
1061  * use more optimized HPyGlobal implementation otherwise.
1062  */
1063 HPy_ID(225)
1064 void HPyGlobal_Store(HPyContext *ctx, HPyGlobal *global, HPy h);

```

(continues on next page)

(continued from previous page)

```

1065 HPy_ID(226)
1066 HPy HPyGlobal_Load(HPyContext *ctx, HPyGlobal global);
1067
1068 /* Debugging helpers */
1069 HPy_ID(227)
1070 void _HPy_Dump(HPyContext *ctx, HPy h);
1071
1072 /* Evaluating Python statements/expressions */
1073
1074 /**
1075  * Parse and compile the Python source code.
1076  *
1077  * :param ctx:
1078  *     The execution context.
1079  * :param utf8_source:
1080  *     Python source code given as UTF-8 encoded C string (must not be ``NULL``).
1081  * :param utf8_filename:
1082  *     The filename (UTF-8 encoded C string) to use for construction of the code
1083  *     object. It may appear in tracebacks or in ``SyntaxError`` exception
1084  *     messages.
1085  * :param kind:
1086  *     The source kind which tells the parser if a single expression, statement,
1087  *     or a whole file should be parsed (see enum :c:enum:`HPy_SourceKind`).
1088  *
1089  * :returns:
1090  *     A Python code object resulting from the parsed and compiled Python source
1091  *     code or ``HPy_NULL`` in case of errors.
1092  */
1093 HPy_ID(248)
1094 HPy HPy_Compile_s(HPyContext *ctx, const char *utf8_source, const char *utf8_filename,
1095 ↪ HPy_SourceKind kind);
1096
1097 /**
1098  * Evaluate a precompiled code object.
1099  *
1100  * Code objects can be compiled from a string using :c:func:`HPy_Compile_s`.
1101  *
1102  * :param ctx:
1103  *     The execution context.
1104  * :param code:
1105  *     The code object to evaluate.
1106  * :param globals:
1107  *     A Python dictionary defining the global variables for the evaluation.
1108  * :param locals:
1109  *     A mapping object defining the local variables for the evaluation.
1110  *
1111  * :returns:
1112  *     The result produced by the executed code. May be ``HPy_NULL`` in case of
1113  *     errors.
1114  */
1115 HPy_ID(249)
1116 HPy HPy_EvalCode(HPyContext *ctx, HPy code, HPy globals, HPy locals);
1117 HPy_ID(250)
1118 HPy HPyContextVar_New(HPyContext *ctx, const char *name, HPy default_value);
1119 HPy_ID(251)
1120 int32_t HPyContextVar_Get(HPyContext *ctx, HPy context_var, HPy default_value, HPy_
1121 ↪ *result);

```

(continues on next page)

(continued from previous page)

```

1120 HPy_ID(252)
1121 HPy HPyContextVar_Set(HPyContext *ctx, HPy context_var, HPy value);
1122
1123 /**
1124  * Set the call function for the given object.
1125  *
1126  * By defining slot ``HPy_tp_call`` for some type, instances of this type will
1127  * be callable objects. The specified call function will be used by default for
1128  * every instance. This should account for the most common case (every instance
1129  * of an object uses the same call function) but to still provide the necessary
1130  * flexibility, function ``HPy_SetCallFunction`` allows to set different (maybe
1131  * specialized) call functions for each instance. This must be done in the
1132  * constructor of an object.
1133  *
1134  * A more detailed description on how to use that function can be found in
1135  * section :ref:`porting-guide:calling protocol`.
1136  *
1137  * :param ctx:
1138  *     The execution context.
1139  * :param h:
1140  *     A handle to an object implementing the call protocol, i.e., the object's
1141  *     type must have slot ``HPy_tp_call``. Otherwise, a ``TypeError`` will be
1142  *     raised. This argument must not be ``HPy_NULL``.
1143  * :param def:
1144  *     A pointer to the call function definition to set (must not be
1145  *     ``NULL``). The definition is usually created using
1146  *     :c:macro:`HPyDef_CALL_FUNCTION`
1147  *
1148  * :returns:
1149  *     ``0`` in case of success and ``-1`` in case of an error.
1150  */
1151 HPy_ID(260)
1152 int HPy_SetCallFunction(HPyContext *ctx, HPy h, HPyCallFunction *func);
1153
1154 /* *****
1155    hpyfunc
1156    *****
1157
1158    These typedefs are used to generate the various macros used by
1159    include/common/hpyfunc.h
1160 */
1161 typedef HPy (*HPyFunc_noargs)(HPyContext *ctx, HPy self);
1162 typedef HPy (*HPyFunc_o)(HPyContext *ctx, HPy self, HPy arg);
1163 typedef HPy (*HPyFunc_varargs)(HPyContext *ctx, HPy self, const HPy *args, size_t_
↪nargs);
1164 typedef HPy (*HPyFunc_keywords)(HPyContext *ctx, HPy self, const HPy *args,
↪size_t nargs, HPy kwnames);
1165
1166 typedef HPy (*HPyFunc_unaryfunc)(HPyContext *ctx, HPy);
1167 typedef HPy (*HPyFunc_binaryfunc)(HPyContext *ctx, HPy, HPy);
1168 typedef HPy (*HPyFunc_ternaryfunc)(HPyContext *ctx, HPy, HPy, HPy);
1169 typedef int (*HPyFunc_inquiry)(HPyContext *ctx, HPy);
1170 typedef HPy_ssize_t (*HPyFunc_lenfunc)(HPyContext *ctx, HPy);
1171 typedef HPy (*HPyFunc_ssizeargfunc)(HPyContext *ctx, HPy, HPy_ssize_t);
1172 typedef HPy (*HPyFunc_ssizeobjargfunc)(HPyContext *ctx, HPy, HPy_ssize_t, HPy_ssize_
↪t);
1173
1174 typedef int (*HPyFunc_ssizeobjargproc)(HPyContext *ctx, HPy, HPy_ssize_t, HPy);

```

(continues on next page)

(continued from previous page)

```

1175 typedef int (*HPyFunc_ssize_tobjargproc)(HPyContext *ctx, HPy, HPy_ssize_t, HPy_
    ↪ssize_t, HPy);
1176 typedef int (*HPyFunc_objobjargproc)(HPyContext *ctx, HPy, HPy, HPy);
1177 typedef void (*HPyFunc_freefunc)(HPyContext *ctx, void *);
1178 typedef HPy (*HPyFunc_getattrfunc)(HPyContext *ctx, HPy, char *);
1179 typedef HPy (*HPyFunc_getattrofunc)(HPyContext *ctx, HPy, HPy);
1180 typedef int (*HPyFunc_setattrfunc)(HPyContext *ctx, HPy, char *, HPy);
1181 typedef int (*HPyFunc_setattrofunc)(HPyContext *ctx, HPy, HPy, HPy);
1182 typedef HPy (*HPyFunc_reprfunc)(HPyContext *ctx, HPy);
1183 typedef HPy_hash_t (*HPyFunc_hashfunc)(HPyContext *ctx, HPy);
1184 typedef HPy (*HPyFunc_richcmpfunc)(HPyContext *ctx, HPy, HPy, HPy_RichCmpOp);
1185 typedef HPy (*HPyFunc_getiterfunc)(HPyContext *ctx, HPy);
1186 typedef HPy (*HPyFunc_itternextfunc)(HPyContext *ctx, HPy);
1187 typedef HPy (*HPyFunc_descrgetfunc)(HPyContext *ctx, HPy, HPy, HPy);
1188 typedef int (*HPyFunc_descrsetfunc)(HPyContext *ctx, HPy, HPy, HPy);
1189 typedef int (*HPyFunc_initproc)(HPyContext *ctx, HPy self,
1190                                const HPy *args, HPy_ssize_t nargs, HPy kw);
1191 typedef HPy (*HPyFunc_newfunc)(HPyContext *ctx, HPy type, const HPy *args,
1192                                HPy_ssize_t nargs, HPy kw);
1193 typedef HPy (*HPyFunc_getter)(HPyContext *ctx, HPy, void *);
1194 typedef int (*HPyFunc_setter)(HPyContext *ctx, HPy, HPy, void *);
1195 typedef int (*HPyFunc_objobjproc)(HPyContext *ctx, HPy, HPy);
1196 typedef int (*HPyFunc_getbufferproc)(HPyContext *ctx, HPy, HPy_buffer *, int);
1197 typedef void (*HPyFunc_releasebufferproc)(HPyContext *ctx, HPy, HPy_buffer *);
1198 typedef int (*HPyFunc_traverseproc)(void *object, HPyFunc_visitproc visit, void *arg);
1199 typedef void (*HPyFunc_destructor)(HPyContext *ctx, HPy);
1200
1201 typedef void (*HPyFunc_destroyfunc)(void *);
1202
1203 // Note: separate type, because we need a different trampoline
1204 typedef HPy (*HPyFunc_mod_create)(HPyContext *ctx, HPy);
1205
1206
1207 /* ~~~ HPySlot_Slot ~~~
1208
1209     The following enum is used to generate autogen_hpyslot.h, which contains:
1210
1211         - The real definition of the enum HPySlot_Slot
1212
1213         - the macros #define _HPySlot_SIGNATURE_*
1214
1215 */
1216
1217 // NOTE: if you uncomment/enable a slot below, make sure to write a corresponding
1218 // test in test_slots.py
1219
1220 /* Note that the magic numbers are the same as CPython */
1221 typedef enum {
1222     HPy_bf_getbuffer = SLOT(1, HPyFunc_GETBUFFERPROC),
1223     HPy_bf_releasebuffer = SLOT(2, HPyFunc_RELEASEBUFFERPROC),
1224     HPy_mp_ass_subscript = SLOT(3, HPyFunc_OBJOBJARGPROC),
1225     HPy_mp_length = SLOT(4, HPyFunc_LENFUNC),
1226     HPy_mp_subscript = SLOT(5, HPyFunc_BINARYFUNC),
1227     HPy_nb_absolute = SLOT(6, HPyFunc_UNARYFUNC),
1228     HPy_nb_add = SLOT(7, HPyFunc_BINARYFUNC),
1229     HPy_nb_and = SLOT(8, HPyFunc_BINARYFUNC),
1230     HPy_nb_bool = SLOT(9, HPyFunc_INQUIRY),

```

(continues on next page)

(continued from previous page)

```

1231     HPy_nb_divmod = SLOT(10, HPyFunc_BINARYFUNC),
1232     HPy_nb_float = SLOT(11, HPyFunc_UNARYFUNC),
1233     HPy_nb_floor_divide = SLOT(12, HPyFunc_BINARYFUNC),
1234     HPy_nb_index = SLOT(13, HPyFunc_UNARYFUNC),
1235     HPy_nb_inplace_add = SLOT(14, HPyFunc_BINARYFUNC),
1236     HPy_nb_inplace_and = SLOT(15, HPyFunc_BINARYFUNC),
1237     HPy_nb_inplace_floor_divide = SLOT(16, HPyFunc_BINARYFUNC),
1238     HPy_nb_inplace_lshift = SLOT(17, HPyFunc_BINARYFUNC),
1239     HPy_nb_inplace_multiply = SLOT(18, HPyFunc_BINARYFUNC),
1240     HPy_nb_inplace_or = SLOT(19, HPyFunc_BINARYFUNC),
1241     HPy_nb_inplace_power = SLOT(20, HPyFunc_TERNARYFUNC),
1242     HPy_nb_inplace_remainder = SLOT(21, HPyFunc_BINARYFUNC),
1243     HPy_nb_inplace_rshift = SLOT(22, HPyFunc_BINARYFUNC),
1244     HPy_nb_inplace_subtract = SLOT(23, HPyFunc_BINARYFUNC),
1245     HPy_nb_inplace_true_divide = SLOT(24, HPyFunc_BINARYFUNC),
1246     HPy_nb_inplace_xor = SLOT(25, HPyFunc_BINARYFUNC),
1247     HPy_nb_int = SLOT(26, HPyFunc_UNARYFUNC),
1248     HPy_nb_invert = SLOT(27, HPyFunc_UNARYFUNC),
1249     HPy_nb_lshift = SLOT(28, HPyFunc_BINARYFUNC),
1250     HPy_nb_multiply = SLOT(29, HPyFunc_BINARYFUNC),
1251     HPy_nb_negative = SLOT(30, HPyFunc_UNARYFUNC),
1252     HPy_nb_or = SLOT(31, HPyFunc_BINARYFUNC),
1253     HPy_nb_positive = SLOT(32, HPyFunc_UNARYFUNC),
1254     HPy_nb_power = SLOT(33, HPyFunc_TERNARYFUNC),
1255     HPy_nb_remainder = SLOT(34, HPyFunc_BINARYFUNC),
1256     HPy_nb_rshift = SLOT(35, HPyFunc_BINARYFUNC),
1257     HPy_nb_subtract = SLOT(36, HPyFunc_BINARYFUNC),
1258     HPy_nb_true_divide = SLOT(37, HPyFunc_BINARYFUNC),
1259     HPy_nb_xor = SLOT(38, HPyFunc_BINARYFUNC),
1260     HPy_sq_ass_item = SLOT(39, HPyFunc_SSIZEOBJARGPROC),
1261     HPy_sq_concat = SLOT(40, HPyFunc_BINARYFUNC),
1262     HPy_sq_contains = SLOT(41, HPyFunc_OBJOBPROC),
1263     HPy_sq_inplace_concat = SLOT(42, HPyFunc_BINARYFUNC),
1264     HPy_sq_inplace_repeat = SLOT(43, HPyFunc_SSIZEARGFUNC),
1265     HPy_sq_item = SLOT(44, HPyFunc_SSIZEARGFUNC),
1266     HPy_sq_length = SLOT(45, HPyFunc_LENFUNC),
1267     HPy_sq_repeat = SLOT(46, HPyFunc_SSIZEARGFUNC),
1268     //HPy_tp_alloc = SLOT(47, HPyFunc_X),          NOT SUPPORTED
1269     //HPy_tp_base = SLOT(48, HPyFunc_X),
1270     //HPy_tp_bases = SLOT(49, HPyFunc_X),
1271     HPy_tp_call = SLOT(50, HPyFunc_KEYWORDS),
1272     //HPy_tp_clear = SLOT(51, HPyFunc_X),          NOT SUPPORTED, use tp_traverse
1273     //HPy_tp_dealloc = SLOT(52, HPyFunc_X),        NOT SUPPORTED
1274     //HPy_tp_del = SLOT(53, HPyFunc_X),
1275     //HPy_tp_descr_get = SLOT(54, HPyFunc_X),
1276     //HPy_tp_descr_set = SLOT(55, HPyFunc_X),
1277     //HPy_tp_doc = SLOT(56, HPyFunc_X),
1278     //HPy_tp_getattr = SLOT(57, HPyFunc_X),
1279     //HPy_tp_getattro = SLOT(58, HPyFunc_X),
1280     HPy_tp_hash = SLOT(59, HPyFunc_HASHFUNC),
1281     HPy_tp_init = SLOT(60, HPyFunc_INITPROC),
1282     //HPy_tp_is_gc = SLOT(61, HPyFunc_X),
1283     //HPy_tp_iter = SLOT(62, HPyFunc_X),
1284     //HPy_tp_iternext = SLOT(63, HPyFunc_X),
1285     //HPy_tp_methods = SLOT(64, HPyFunc_X),        NOT SUPPORTED
1286     HPy_tp_new = SLOT(65, HPyFunc_NEWFUNC),
1287     HPy_tp_repr = SLOT(66, HPyFunc_REPRFUNC),

```

(continues on next page)



(continued from previous page)

```

1288     HPy_tp_richcompare = SLOT(67, HPyFunc_RICHCMPPFUNC),
1289     //HPy_tp_setattr = SLOT(68, HPyFunc_X),
1290     //HPy_tp_setattro = SLOT(69, HPyFunc_X),
1291     HPy_tp_str = SLOT(70, HPyFunc_REPRFUNC),
1292     HPy_tp_traverse = SLOT(71, HPyFunc_TRAVERSEPROC),
1293     //HPy_tp_members = SLOT(72, HPyFunc_X),      NOT SUPPORTED
1294     //HPy_tp_getset = SLOT(73, HPyFunc_X),      NOT SUPPORTED
1295     //HPy_tp_free = SLOT(74, HPyFunc_X),        NOT SUPPORTED
1296     HPy_nb_matrix_multiply = SLOT(75, HPyFunc_BINARYFUNC),
1297     HPy_nb_inplace_matrix_multiply = SLOT(76, HPyFunc_BINARYFUNC),
1298     //HPy_am_await = SLOT(77, HPyFunc_X),
1299     //HPy_am_aiter = SLOT(78, HPyFunc_X),
1300     //HPy_am_anext = SLOT(79, HPyFunc_X),
1301     HPy_tp_finalize = SLOT(80, HPyFunc_DESTRUCTOR),
1302
1303     /* extra HPy slots */
1304     HPy_tp_destroy = SLOT(1000, HPyFunc_DESTROYFUNC),
1305
1306     /**
1307      * Module create slot: the function receives loader spec and should
1308      * return an HPy handle representing the module. Currently, creating
1309      * real module objects cannot be done by user code, so the only other
1310      * useful thing that this slot can do is to create another object that
1311      * can work as a module, such as SimpleNamespace.
1312      */
1313     HPy_mod_create = SLOT(2000, HPyFunc_MOD_CREATE),
1314     /**
1315      * Module exec slot: the function receives module object that was created
1316      * by the runtime from HPyModuleDef. This slot can do any initialization
1317      * of the module, such as adding types. There can be multiple exec slots
1318      * and they will be executed in the declaration order.
1319      */
1320     HPy_mod_exec = SLOT(2001, HPyFunc_INQUIRY),
1321
1322 } HPySlot_Slot;

```

## 2.8.2 HPy Helper Functions

**HPy Helper** functions are functions (written in C) that will be compiled together with the HPy extension's sources. The appropriate source files are automatically added to the extension sources. The helper functions will, of course, use the core API to interact with the interpreter. The main reason for having the helper functions in the HPy extension is to avoid compatibility problems due to different compilers.

### Argument Parsing

Implementation of `HPyArg_Parse` and `HPyArg_ParseKeywords`.

Note: those functions are runtime helper functions, i.e., they are not part of the HPy context, but are available to HPy extensions to incorporate at compile time.

`HPyArg_Parse` parses positional arguments and replaces `PyArg_ParseTuple`. `HPyArg_ParseKeywords` parses positional and keyword arguments and replaces `PyArg_ParseTupleAndKeywords`.

HPy intends to only support the simpler format string types (numbers, bools) and handles. More complex types (e.g. buffers) should be retrieved as handles and then processed further as needed.

## Supported Formatting Strings

### Numbers

- b** (int) [unsigned char] Convert a nonnegative Python integer to an unsigned tiny int, stored in a C unsigned char.
- B** (int) [unsigned char] Convert a Python integer to a tiny int without overflow checking, stored in a C unsigned char.
- h** (int) [short int] Convert a Python integer to a C short int.
- H** (int) [unsigned short int] Convert a Python integer to a C unsigned short int, without overflow checking.
- i** (int) [int] Convert a Python integer to a plain C int.
- I** (int) [unsigned int] Convert a Python integer to a C unsigned int, without overflow checking.
- l** (int) [long int] Convert a Python integer to a C long int.
- k** (int) [unsigned long] Convert a Python integer to a C unsigned long without overflow checking.
- L** (int) [long long] Convert a Python integer to a C long long.
- K** (int) [unsigned long long] Convert a Python integer to a C unsigned long long without overflow checking.
- n** (int) [HPy\_ssize\_t] Convert a Python integer to a C HPy\_ssize\_t.
- f** (float) [float] Convert a Python floating point number to a C float.
- d** (float) [double] Convert a Python floating point number to a C double.

### Strings and buffers

These formats allow accessing an object as a contiguous chunk of memory. You don't have to provide raw storage for the returned unicode or bytes area.

In general, when a format sets a pointer to a buffer, the pointer is valid only until the corresponding HPy handle is closed.

```
s (unicode) [const char*]
```

Convert a Unicode object to a C pointer to a character string. A pointer to an existing string is stored in the character pointer variable whose address you pass. The C string is NUL-terminated. The Python string must not contain embedded null code points; if it does, a *ValueError* exception is raised. Unicode objects are converted to C strings using 'utf-8' encoding. If this conversion fails, a *UnicodeError* is raised.

Note: This format does not accept bytes-like objects and is therefore not suitable for filesystem paths.

## Handles (Python Objects)

**O (object) [HPy]** Store a handle pointing to a generic Python object.

When using **O** with `HPyArg_ParseKeywords`, an `HPyTracker` is created and returned via the parameter *ht*. If `HPyArg_ParseKeywords` returns successfully, you must call `HPyTracker_Close` on *ht* once the returned handles are no longer needed. This will close all the handles created during argument parsing. There is no need to call `HPyTracker_Close` on failure – the argument parser does this for you.

## Miscellaneous

**p (bool) [int]** Tests the value passed in for truth (a boolean predicate) and converts the result to its equivalent C true/false integer value. Sets the int to 1 if the expression was true and 0 if it was false. This accepts any valid Python value. See [Truth Value Testing](#) for more information about how Python tests values for truth.

## Options

- | Indicates that the remaining arguments in the argument list are optional. The C variables corresponding to optional arguments should be initialized to their default value — when an optional argument is not specified, the contents of the corresponding C variable is not modified.
- \$ `HPyArg_ParseKeywords()` only: Indicates that the remaining arguments in the argument list are keyword-only. Currently, all keyword-only arguments must also be optional arguments, so | must always be specified before \$ in the format string.
- : The list of format units ends here; the string after the colon is used as the function name in error messages. : and ; are mutually exclusive and whichever occurs first takes precedence.
- ; The list of format units ends here; the string after the semicolon is used as the error message instead of the default error message. : and ; are mutually exclusive and whichever occurs first takes precedence.

## Argument Parsing API

int **HPyArg\_Parse** (HPyContext \*ctx, HPyTracker \*ht, const HPy \*args, size\_t nargs, const char \*fmt, ...)  
Parse positional arguments.

### Parameters

- **ctx** – The execution context.
- **ht** – An optional pointer to an `HPyTracker`. If the format string never results in new handles being created, *ht* may be `NULL`. Currently only the **O** formatting option to this function requires an `HPyTracker`.
- **args** – The array of positional arguments to parse.
- **nargs** – The number of elements in *args*.
- **fmt** – The format string to use to parse the arguments.
- ... – A va\_list of references to variables in which to store the parsed arguments. The number and types of the arguments should match the the format string, *fmt*.

**Returns** 0 on failure, 1 on success.

If a `NULL` pointer is passed to `ht` and an `HPyTracker` is required by the format string, a `SystemError` will be raised.

If a pointer is provided to `ht`, the `HPyTracker` will always be created and must be closed with `HPyTracker_Close` if parsing succeeds (after all handles returned are no longer needed). If parsing fails, this function will close the `HPyTracker` automatically.

Examples:

Using `HPyArg_Parse` without an `HPyTracker`:

```
long a, b;
if (!HPyArg_Parse(ctx, NULL, args, nargs, "ll", &a, &b))
    return HPy_NULL;
...
```

Using `HPyArg_Parse` with an `HPyTracker`:

```
long a, b;
HPyTracker ht;
if (!HPyArg_Parse(ctx, &ht, args, nargs, "ll", &a, &b))
    return HPy_NULL;
...
HPyTracker_Close(ctx, ht);
...
```

---

**Note:** Currently `HPyArg_Parse` never requires the use of an `HPyTracker`. The option exists only to support releasing temporary storage used by future format string codes (e.g. for character strings).

---

int **HPyArg\_ParseKeywords** (HPyContext \**ctx*, HPyTracker \**ht*, **const** HPy \**args*, size\_t *nargs*, HPy *kwnames*, **const** char \**fmt*, **const** char \**keywords*[], ...)  
Parse positional and keyword arguments.

#### Parameters

- **ctx** – The execution context.
- **ht** – An optional pointer to an `HPyTracker`. If the format string never results in new handles being created, `ht` may be `NULL`. Currently only the `O` formatting option to this function requires an `HPyTracker`.
- **args** – The array of positional arguments to parse.
- **nargs** – The number of elements in `args`.
- **kwnames** – A handle to the tuple of keyword argument names (may be `HPy_NULL`). The values of the keyword arguments are appended to `args`. Argument `nargs` does not include the keyword argument count.
- **fmt** – The format string to use to parse the arguments.
- **keywords** – A `NULL`-terminated array of argument names. The number of names should match the format string provided. Positional only arguments should have the name "" (i.e. the null-terminated empty string). Positional only arguments must precede all other arguments.
- **...** – A `va_list` of references to variables in which to store the parsed arguments. The number and types of the arguments should match the the format string, `fmt`.

**Returns** 0 on failure, 1 on success.

If a `NULL` pointer is passed to `ht` and an `HPyTracker` is required by the format string, a `SystemError` will be raised.

If a pointer is provided to `ht`, the `HPyTracker` will always be created and must be closed with `HPyTracker_Close` if parsing succeeds (after all handles returned are no longer needed). If parsing fails, this function will close the `HPyTracker` automatically.

Examples:

Using `HPyArg_ParseKeywords` without an `HPyTracker`:

```
long a, b;
if (!HPyArg_ParseKeywords(ctx, NULL, args, nargs, kwnames, "ll", &a, &b))
    return HPy_NULL;
...
```

Using `HPyArg_ParseKeywords` with an `HPyTracker`:

```
HPy a, b;
HPyTracker ht;
if (!HPyArg_ParseKeywords(ctx, &ht, args, nargs, kwnames, "OO", &a, &b))
    return HPy_NULL;
...
HPyTracker_Close(ctx, ht);
...
```

**Note:** Currently `HPyArg_ParseKeywords` only requires the use of an `HPyTracker` when the `O` format is used. In future other new format string codes (e.g. for character strings) may also require it.

int **HPyArg\_ParseKeywordsDict** (HPyContext \*ctx, HPyTracker \*ht, const HPy \*args, HPy\_ssize\_t nargs, HPy kw, const char \*fmt, const char \*keywords[], ...)  
Parse positional arguments and keyword arguments in a dict.

#### Parameters

- **ctx** – The execution context.
- **ht** – An optional pointer to an `HPyTracker`. If the format string never results in new handles being created, `ht` may be `NULL`. Currently only the `O` formatting option to this function requires an `HPyTracker`.
- **args** – The array of positional arguments to parse.
- **nargs** – The number of elements in `args`.
- **kw** – A handle to the dictionary of keyword arguments (may be `HPy_NULL`).
- **fmt** – The format string to use to parse the arguments.
- **keywords** – A `NULL`-terminated array of argument names. The number of names should match the format string provided. Positional only arguments should have the name "" (i.e. the null-terminated empty string). Positional only arguments must precede all other arguments.
- **...** – A `va_list` of references to variables in which to store the parsed arguments. The number and types of the arguments should match the the format string, `fmt`.

**Returns** 0 on failure, 1 on success.

If a `NULL` pointer is passed to `ht` and an `HPyTracker` is required by the format string, a `SystemError` will be raised.

If a pointer is provided to `ht`, the `HPyTracker` will always be created and must be closed with `HPyTracker_Close` if parsing succeeds (after all handles returned are no longer needed). If parsing fails, this function will close the `HPyTracker` automatically.

For examples, see `HPyArg_ParseKeywords()`.

## Building Complex Python Objects

Implementation of `HPy_BuildValue`.

Note: `HPy_BuildValue()` is a runtime helper functions, i.e., it is not a part of the `HPy` context, but is available to `HPy` extensions to incorporate at compile time.

`HPy_BuildValue` creates a new value based on a format string from the values passed in variadic arguments. Returns `HPY_NULL` in case of an error and raises an exception.

`HPy_BuildValue` does not always build a tuple. It builds a tuple only if its format string contains two or more format units. If the format string is empty, it returns `None`; if it contains exactly one format unit, it returns whatever object is described by that format unit. To force it to return a tuple of size 0 or one, parenthesize the format string.

Building complex values with `HPy_BuildValue` is more convenient than the equivalent code that uses more granular APIs with proper error handling and cleanup. Moreover, `HPy_BuildValue` provides straightforward way to port existing code that uses `Py_BuildValue`.

`HPy_BuildValue` always returns a new handle that will be owned by the caller. Even an artificial example `HPy_BuildValue(ctx, "O", h)` does not simply forward the value stored in `h` but duplicates the handle.

## Supported Formatting Strings

### Numbers

- i (int) [int]** Convert a plain C int to a Python integer object.
- l (int) [long int]** Convert a C long int to a Python integer object.
- I (int) [unsigned int]** Convert a C unsigned int to a Python integer object.
- k (int) [unsigned long]** Convert a C unsigned long to a Python integer object.
- L (int) [long long]** Convert a C long long to a Python integer object.
- K (int) [unsigned long long]** Convert a C unsigned long long to a Python integer object.
- n (int) [HPy\_ssize\_t]** Convert a C `HPy_ssize_t` to a Python integer object.
- f (float) [float]** Convert a C float to a Python floating point number.
- d (float) [double]** Convert a C double to a Python floating point number.

## Collections

- (items) (tuple) [matching-items]** Convert a sequence of C values to a Python tuple with the same number of items.
- [items] (list) [matching-items]** Convert a sequence of C values to a Python list with the same number of items.
- {key:value} (dict) [matching-items]** Convert a sequence of C values to a Python dict with the same number of items.

## Misc

- O (Python object) [HPy]** Pass an untouched Python object represented by the handle.

If the object passed in is a `HPy_NULL`, it is assumed that this was caused because the call producing the argument found an error and set an exception. Therefore, `HPy_BuildValue` will also immediately stop and return `HPy_NULL` but will not raise any new exception. If no exception has been raised yet, `SystemError` is set.

Any HPy handle passed to `HPy_BuildValue` is always owned by the caller. `HPy_BuildValue` never closes the handle nor transfers its ownership. If the handle is used, then `HPy_BuildValue` creates a duplicate of the handle.

- S (Python object) [HPy]** Alias for 'O'.

## API

**HPy HPy\_BuildValue** (HPyContext \*ctx, **const** char \*fmt, ...)

Creates a new value based on a format string from the values passed in variadic arguments.

### Parameters

- **ctx** – The execution context.
- **fmt** – The format string (ASCII only; must not be `NULL`). For details, see [Supported Formatting Strings](#).
- ... – Variable arguments according to the provided format string.

**Returns** A handle to the built Python value or `HPy_NULL` in case of errors.

## String Formatting Helpers

HPy string formatting helpers.

Note: these functions are runtime helper functions, i.e., they are not part of the HPy context ABI, but are available to HPy extensions to incorporate at compile time.

The formatting helper functions are: `HPyUnicode_FromFormat`, `HPyUnicode_FromFormatV`, and `HPyErr_Format`.

## Supported Formatting Units

**%%** - The literal % character.

### Compatible with C (s)printf:

**%c** [int]  
**%d** [int]  
**%u** [unsigned int]  
**%ld** [long]  
**%li** [long]  
**%lu** [unsigned long]  
**%lld** [long long]  
**%lli** [long long]  
**%llu** [unsigned long long]  
**%zd** [HPy\_ssize\_t]  
**%zi** [HPy\_ssize\_t]  
**%zu** [size\_t]  
**%i** [int]  
**%x** [int]  
**%s** [const char\*]

**%p** [**const void\***] Guaranteed to start with the literal '0x' regardless of what the platform's printf yields. However, there is no guarantee for zero-padding after the '0x' prefix. Some systems pad the pointer to 32 or 64 digits depending on the architecture, some do not zero pad at all. Moreover, there is no guarantee whether the letters will be capitalized or not.

### Python specific:

**%A** [**HPy**] The result of calling `HPy_Ascii`.

**%U** [**HPy**] A Unicode object.

**%V** [**HPy, const char\***] A Unicode object (which may be `HPy_NULL`) and a null-terminated C character array as a second parameter (which will be used, if the first parameter is `HPy_NULL`).

**%S** [**HPy**] The result of calling `HPy_Str`.

**%R** [**HPy**] The result of calling `HPy_Repr`.



### Additional flags:

The format is `%[0]{width}.{precision}{formatting-unit}`.

The `precision` flag for numbers gives the minimal number of digits (i.e., excluding the minus sign). Shorter numbers are padded with zeros. For strings it gives the maximum number of characters, i.e., the string may be shortened if it is longer than `precision`.

The `width` determines how many characters should be output. If the formatting result with `width` flag applied is shorter, then it is padded from left with spaces. If it is longer, the result will *not* be shortened.

The `0` flag is supported only for numeric units: if present, the number is padded to desired `width` with zeros instead of spaces. Unlike with spaces padding, the minus sign is shifted to the leftmost position with zero padding.

The `width` formatter unit is number of characters rather than bytes. The `precision` formatter unit is number of bytes for `%s` and `%V` (if the HPy argument is `HPY_NULL`), and a number of characters for `%A`, `%U`, `%S`, `%R` and `%V` (if the HPy argument is not `HPY_NULL`).

### Compatibility with CPython API

HPy is more strict in these cases:

CPython API ignores `width`, `precision`, zero-padding flag for formatting units that do not support them: `%c` and `%p`, but HPy raises a system error in such cases.

CPython API ignores zero-padding for “string” formatting units, while HPy raises a system error in such cases.

Note: users should not rely on these system errors, as HPy may choose to support some of those flags in the future.

### Struct Sequences

Struct sequences are subclasses of tuple. Similar to the API for creating tuples, HPy provides an API to create struct sequences. This is a builder API such that the struct sequence is guaranteed not to be written after it is created.

---

**Note:** There is no specific getter function for struct sequences. Just use one of `HPy_GetItem()`, `HPy_GetItem_i()`, or `HPy_GetItem_s()`.

---

#### **struct HPyStructSequence\_Field**

Describes a field of a struct sequence.

**const char \*name**

Name (UTF-8 encoded) for the field or `NULL` to end the list of named fields. Set the name to `HPyStructSequence_UnnamedField` to leave it unnamed.

**const char \*doc**

Docstring of the field (UTF-8 encoded); may be `NULL`.

#### **struct HPyStructSequence\_Desc**

Contains the meta information of a struct sequence type to create. Struct sequences are subclasses of tuple. The index in the `fields` array of the descriptor determines which field of the struct sequence is described.

**const char \*name**

Name of the struct sequence type (UTF-8 encoded; must not be `NULL`).

**const char \*doc**

Docstring of the type (UTF-8 encoded); may be `NULL`.

*HPyStructSequence\_Field* \*fields

Pointer to NULL-terminated array with field names of the new type (must not be NULL).

**extern const** char \*const **HPyStructSequence\_UnnamedField**

A marker that can be used as struct sequence field name to indicate that a field should be anonymous (i.e. cannot be accessed by a name but only by numeric index).

HPy **HPyStructSequence\_NewType** (HPyContext \*ctx, *HPyStructSequence\_Desc* \*desc)

Create a new struct sequence type from a descriptor. Instances of the resulting type can be created with *HPyStructSequence\_New()*.

#### Parameters

- **ctx** – The execution context.
- **desc** – The descriptor of the struct sequence type to create (must not be NULL):

**Returns** A handle to the new struct sequence type or `HPy_NULL` in case of errors.

HPy **HPyStructSequence\_New** (HPyContext \*ctx, HPy type, HPy\_ssize\_t nargs, HPy \*args)

Creates a new instance of type initializing it with the given arguments.

Since struct sequences are immutable objects, they need to be initialized at instantiation. This function will create a fresh instance of the provided struct sequence type. The type must have been created with *HPyStructSequence\_NewType()*.

#### Parameters

- **ctx** – The execution context.
- **type** – A struct sequence type (must not be `HPy_NULL`). If the passed object is not a type, the behavior is undefined. If the given type is not appropriate, a `TypeError` will be raised.
- **nargs** – The number of arguments in args. If this argument is not exactly the number of fields of the struct sequence, a `TypeError` will be raised.
- **args** – An array of HPy handles to Python objects to be used for initializing the struct sequence. If `nargs > 0` then this argument must not be NULL.

**Returns** A new instance of type or `HPy_NULL` if an error occurred.

## Misc Helpers

int **HPyHelpers\_AddType** (HPyContext \*ctx, HPy obj, **const** char \*name, *HPyType\_Spec* \*hpy-spec, *HPyType\_SpecParam* \*params)

Create a type and add it as an attribute on the given object. The type is created using *HPyType\_FromSpec()*. The object is often a module that the type is being added to.

#### Parameters

- **ctx** – The execution context.
- **obj** – A handle to the object the type is being added to (often a module).
- **name** – The name of the attribute on the object to assign the type to.
- **hpy-spec** – The type spec to use to create the type.
- **params** – The type spec parameters to use to create the type.

**Returns** 0 on failure, 1 on success.

Examples:

Using `HPyHelpers_AddType` without any *HPyType\_SpecParam* parameters:

```

if (!HPyHelpers_AddType(ctx, module, "MyType", hpyspec, NULL))
    return HPy_NULL;
...

```

Using *HPyHelpers\_AddType* with *HPyType\_SpecParam* parameters:

```

HPyType_SpecParam params[] = {
    { HPyType_SpecParam_Base, ctx->h_LongType },
    { 0 }
};

if (!HPyHelpers_AddType(ctx, module, "MyType", hpyspec, params))
    return HPy_NULL;
...

```

int **HPyHelpers\_PackArgsAndKeywords** (HPyContext \*ctx, const HPy \*args, size\_t nargs, HPy kw-names, HPy \*out\_pos\_args, HPy \*out\_kwd)

Convert positional/keyword argument vector to argument tuple and keywords dictionary.

This helper function is useful to convert arguments from HPy's calling convention to the legacy CPython *tp\_call* calling convention. HPy's calling convention is similar to CPython's fastcall/vectorcall calling convention where positional and keyword arguments are passed as a C array, the number of positional arguments is explicitly given by an argument and the names of the keyword arguments are provided in a tuple.

For an example on how to use this function, see section *Incremental Migration to HPy's Calling Protocol*.

#### Parameters

- **ctx** – The execution context.
- **args** – A pointer to an array of positional and keyword arguments. This argument must not be NULL if `nargs > 0` or `HPy_Length(ctx, kw-names) > 0`.
- **nargs** – The number of positional arguments in `args`.
- **kwnames** – A handle to the tuple of keyword argument names (may be `HPy_NULL`). The values of the keyword arguments are also passed in `args` appended to the positional arguments. Argument `nargs` does not include the keyword argument count.
- **out\_pos\_args** – A pointer to a variable where to write the created positional arguments tuple to. If there are no positional arguments (i.e. `nargs == 0`), then `HPy_NULL` will be written. The pointer will not be used if any error occurs during conversion.
- **out\_kwd** – A pointer to a variable where to write the created keyword arguments dictionary to. If there are not keyword arguments (i.e. `HPy_Length(ctx, kw-names) == 0`), then `HPy_NULL` will be written. The pointer will not be used if any error occurs during conversion.

**Returns** 0 on failure, 1 on success.

## 2.8.3 Inline Helper Functions

**Inline Helper** functions are `static inline` functions (written in C). Those functions are usually small convenience functions that everyone could write but in order to avoid duplicated effort, they are defined by HPy.

### Inline Helpers

**Inline Helper** functions are `static inline` functions (written in C). Those functions are usually small convenience functions that everyone could write but in order to avoid duplicated effort, they are defined by HPy.

One category of inline helpers are functions that convert the commonly used but not fixed width C types, such as `int`, or `long long`, to HPy API. The HPy API always uses well-defined fixed width types like `int32` or `unsigned int8`.

#### HPY\_INLINE\_HELPERS\_H

HPy **HPyErr\_SetFromErrno** (HPyContext \**ctx*, HPy *h\_type*)

Same as `HPyErr_SetFromErrnoWithFilenameObjects()` but passes `HPy_NULL` to the optional arguments.

##### Parameters

- **ctx** – The execution context.
- **h\_type** – The exception type to raise.

**Returns** always returns `HPy_NULL`

HPy **HPyErr\_SetFromErrnoWithFilenameObject** (HPyContext \**ctx*, HPy *h\_type*, HPy *filename*)

Same as `HPyErr_SetFromErrnoWithFilenameObjects()` but passes `HPy_NULL` to the last (optional) argument.

##### Parameters

- **ctx** – The execution context.
- **h\_type** – The exception type to raise.
- **filename** – a filename; may be `HPy_NULL`

**Returns** always returns `HPy_NULL`

HPy **HPyTuple\_Pack** (HPyContext \**ctx*, HPy\_ssize\_t *n*, ...)

Create a tuple from arguments.

A convenience function that will allocate a temporary array of HPy elements and use `HPyTuple_FromArray()` to create a tuple.

##### Parameters

- **ctx** – The execution context.
- **n** – The number of elements to pack into a tuple.
- ... – Variable number of HPy arguments.

**Returns** A new tuple with *n* elements or `HPy_NULL` in case of an error occurred.

int **HPy\_DelAttr** (HPyContext \**ctx*, HPy *obj*, HPy *name*)

Delete an attribute.

This is the equivalent of the Python statement `del o.attr_name`.

##### Parameters

- **ctx** – The execution context.
- **obj** – The object with the attribute.
- **name** – The name (an unicode object) of the attribute.

**Returns** 0 on success; -1 in case of an error.

int **HPy\_DelAttr\_s** (HPyContext \*ctx, HPy obj, **const** char \*utf8\_name)  
Delete an attribute.

This is the equivalent of the Python statement `del o.attr_name`.

#### Parameters

- **ctx** – The execution context.
- **obj** – The object with the attribute.
- **utf8\_name** – The name (an UTF-8 encoded C string) of the attribute.

**Returns** 0 on success; -1 in case of an error.

HPy **HPyLong\_FromLong** (HPyContext \*ctx, long l)  
Create a Python long object from a C long value.

#### Parameters

- **ctx** – The execution context.
- **l** – A C long value.

**Returns** A Python long object with the value of l or HPY\_NULL on failure.

HPy **HPyLong\_FromUnsignedLong** (HPyContext \*ctx, unsigned long l)  
Create a Python long object from a C unsigned long value.

#### Parameters

- **ctx** – The execution context.
- **l** – A C unsigned long value.

**Returns** A Python long object with the value of l or HPY\_NULL on failure.

HPy **HPyLong\_FromLongLong** (HPyContext \*ctx, long long l)  
Create a Python long object from a C long long value.

#### Parameters

- **ctx** – The execution context.
- **l** – A C long long value.

**Returns** A Python long object with the value of l or HPY\_NULL on failure.

HPy **HPyLong\_FromUnsignedLongLong** (HPyContext \*ctx, unsigned long long l)  
Create a Python long object from a C unsigned long long value.

#### Parameters

- **ctx** – The execution context.
- **l** – A C unsigned long long value.

**Returns** A Python long object with the value of l or HPY\_NULL on failure.

long **HPyLong\_AsLong** (HPyContext \*ctx, HPy h)

Return a C long representation of the given Python long object. If the object is not an instance of Python long, the object's `__index__` method (if present) will be used to convert it to a Python long object.

This function will raise an `OverflowError` if the value of the object is out of range for a C long.

This function will raise a `TypeError` if:

- The object is neither an instance of Python long nor it provides an `__index__` method.
- If the `__index__` method does not return an instance of Python long.

**Parameters**

- **ctx** – The execution context.
- **h** – Either an instance of Python long or an object that provides an `__index__` method (which returns a Python long).

**Returns** A C long value. Errors will be indicated with return value `-1`. In this case, use `HPyErr_Occurred()` to disambiguate.

unsigned long **HPyLong\_AsUnsignedLong** (HPyContext \*ctx, HPy h)

Return a C unsigned long representation of the given Python long object.

This function will raise a `TypeError` if the object is not an instance of Python long and it will raise an `OverflowError` if the object's value is negative or out of range for a C unsigned long.

**Parameters**

- **ctx** – The execution context.
- **h** – The object to convert to C unsigned long (must be an instance of Python long).

**Returns** A C unsigned long value. Errors will be indicated with return value (unsigned long) `-1`. In this case, use `HPyErr_Occurred()` to disambiguate.

unsigned long **HPyLong\_AsUnsignedLongMask** (HPyContext \*ctx, HPy h)

Return a C unsigned long representation of the given Python long object. If the object is not an instance of Python long, the object's `__index__` method (if present) will be used to convert it to a Python long object.

If the object's value is out of range for an unsigned long, return the reduction of that value modulo `ULONG_MAX + 1`. Therefore, this function will **NOT** raise an `OverflowError` if the value of the object is out of range for a C unsigned long.

**Parameters**

- **ctx** – The execution context.
- **h** – Either an instance of Python long or an object that provides an `__index__` method (which returns a Python long).

**Returns** A C unsigned long value. Errors will be indicated with return value (unsigned long) `-1`. In this case, use `HPyErr_Occurred()` to disambiguate.

long long **HPyLong\_AsLongLong** (HPyContext \*ctx, HPy h)

Return a C long long representation of the given Python long object. If the object is not an instance of Python long, the object's `__index__` method (if present) will be used to convert it to a Python long object.

This function will raise an `OverflowError` if the value of the object is out of range for a C long long.

This function will raise a `TypeError` if:

- The object is neither an instance of Python long nor it provides an `__index__` method.

- If the `__index__` method does not return an instance of Python long.

#### Parameters

- **ctx** – The execution context.
- **h** – Either an instance of Python long or an object that provides an `__index__` method (which returns a Python long).

**Returns** A C long long value. Errors will be indicated with return value `-1`. In this case, use `HPyErr_Occurred()` to disambiguate.

unsigned long long **HPyLong\_AsUnsignedLongLong** (HPyContext \*ctx, HPy h)

Return a C unsigned long long representation of the given Python long object.

This function will raise a `TypeError` if the object is not an instance of Python long and it will raise an `OverflowError` if the object's value is negative or out of range for a C unsigned long.

#### Parameters

- **ctx** – The execution context.
- **h** – The object to convert to C unsigned long long (must be an instance of Python long).

**Returns** A C unsigned long long value. Errors will be indicated with return value (unsigned long long) `-1`. In this case, use `HPyErr_Occurred()` to disambiguate.

unsigned long long **HPyLong\_AsUnsignedLongLongMask** (HPyContext \*ctx, HPy h)

Return a C unsigned long long representation of the given Python long object. If the object is not an instance of Python long, the object's `__index__` method (if present) will be used to convert it to a Python long object.

If the object's value is out of range for an unsigned long long, return the reduction of that value modulo `ULLONG_MAX + 1`. Therefore, this function will **NOT** raise an `OverflowError` if the value of the object is out of range for a C unsigned long long.

#### Parameters

- **ctx** – The execution context.
- **h** – Either an instance of Python long or an object that provides an `__index__` method (which returns a Python long).

**Returns** A C unsigned long value. Errors will be indicated with return value (unsigned long long) `-1`. In this case, use `HPyErr_Occurred()` to disambiguate.

HPy **HPyBool\_FromLong** (HPyContext \*ctx, long v)

Returns Python True or False depending on the truth value of v.

#### Parameters

- **ctx** – The execution context.
- **v** – A C long value.

**Returns** Python True if `v != 0`; Python False otherwise.

HPy\_ssize\_t **HPySlice\_AdjustIndices** (HPyContext \*\_HPy\_UNUSED\_ARG) ctx

, HPy\_ssize\_t length, HPy\_ssize\_t \*start, HPy\_ssize\_t \*stop, HPy\_ssize\_t step Adjust start/end slice indices assuming a sequence of the specified length.

Out of bounds indices are clipped in a manner consistent with the handling of normal slices. This function cannot fail and does not call interpreter routines.

**Parameters**

- **ctx** – The execution context.
- **length** – The length of the sequence that should be assumed for adjusting the indices.
- **start** – Pointer to the start value (must not be NULL).
- **stop** – Pointer to the stop value (must not be NULL).
- **step** – The step value of the slice (must not be 0)

**Returns** Return the length of the slice. Always successful. Doesn't call Python code.

HPy **HPy\_CallMethodTupleDict\_s** (HPyContext \*ctx, **const** char \*utf8\_name, HPy receiver, HPy args, HPy kw)

Call a method of a Python object.

This is a convenience function for calling a method. It uses `HPy_GetAttr_s()` and `HPy_CallTupleDict()` to perform the method call.

**Parameters**

- **ctx** – The execution context.
- **utf8\_name** – The name (UTF-8 encoded C string) of the method. Must not be NULL.
- **receiver** – A handle to the receiver of the call (i.e. the `self`). Must not be `HPy_NULL`.
- **args** – A handle to a tuple containing the positional arguments (must not be `HPy_NULL` but can, of course, be empty).
- **kw** – A handle to a Python dictionary containing the keyword arguments (may be `HPy_NULL`).

**Returns** The result of the call on success, or `HPy_NULL` in case of an error.

HPy **HPy\_CallMethodTupleDict** (HPyContext \*ctx, HPy name, HPy receiver, HPy args, HPy kw)

Call a method of a Python object.

This is a convenience function for calling a method. It uses `HPy_GetAttr()` and `HPy_CallTupleDict()` to perform the method call.

**Parameters**

- **ctx** – The execution context.
- **name** – A handle to the name (a Unicode object) of the method. Must not be `HPy_NULL`.
- **receiver** – A handle to the receiver of the call (i.e. the `self`). Must not be `HPy_NULL`.
- **args** – A handle to a tuple containing the positional arguments (must not be `HPy_NULL` but can, of course, be empty).
- **kw** – A handle to a Python dictionary containing the keyword arguments (may be `HPy_NULL`).

**Returns** The result of the call on success, or `HPy_NULL` in case of an error.



## 2.9 Contributing

### 2.9.1 Getting Started

TBD

### 2.9.2 Adding New API

1. Add the function to `hpy/tools/autogen/public_api.h`. If the CPython equivalent function name is not the same (after removing the leading `H`, add an appropriate CPython function mapping in `hpy/tools/autogen/conf.py`. If the signature is complicated or there is no clear equivalent function, the mapping should be `None`, and follow the directions in the next step. Otherwise all the needed functions will be autogenerated.
2. If the function cannot be autogenerated (i.e. the mapping does not exist), you must write the wrapper by hand. Add the function to `NO_WRAPPER` in `hpy/tools/autogen/debug.py`, and add a `ctx_fname` function to `hpy/devel/src/runtime/*.c` (possibly adding the new file to `setup.py`), add a debug wrapper to `hpy/debug/src/debug_ctx.c`, add a implementation that uses the `ctx` variant to `hpy/devel/include/hpy/cpython/misc.h` and add the declaration to `hpy/devel/include/hpy/runtime/ctx_funcs.h`.
3. Run `make autogen` which will turn the mapping into autogenerated functions
4. Add a test for the functionality
5. Build with `python setup.py build_ext`. After that works, build with `python -m pip install -e .`, then run the test with `python -m pytest ....`

## 2.10 Misc Notes

### 2.10.1 Embedding HPy modules

There might be cases where it is beneficial or even necessary to embed multiple HPy modules into one library. HPy itself already makes use of that. The debug and the trace module do not have individual libraries but are embedded into the universal module.

To achieve that, the embedder will use the macro `HPY_MODINIT` several times. Unfortunately, this macro defines global state and cannot repeatedly be used by default. In order to correctly embed several HPy modules into one library, the embedder needs to consider following:

- The modules must be compiled with preprocessor macro `HPY_EMBEDDED_MODULES` defined to enable this feature.
- There is one major restriction: All HPy-specific module pieces must be in the same compilation unit. *HPy-specific pieces* are things like the module's init function (`HPY_MODINIT`) and all slots, members, methods of the module or any type of it (`HPyDef_*`). The implementation functions (usually the `*_impl` functions) of the slots, members, methods, etc. and any helper functions may still be in different compilation units. The reason for this is that the global state induced by `HPY_MODINIT` is, of course, made local (e.g. using C modifier `static`).
- It is also necessary to use macro `HPY_MOD_EMBEDDABLE` before the first usage of any `HPyDef_*` macro.

Also refer to the API reference *HPy Module*.

#### Example

```
// compile with -DHPY_EMBEDDED_MODULES

HPY_MOD_EMBEDDABLE (hpymodA)

HPyDef_METH(foo, /* ... */)
static HPy foo_impl(/* ... */)
{
    // ...
}

HPy_MODINIT(extension_name, hpymodA)
```

## 2.11 Changelog

### 2.11.1 Version 0.9 (April 25th, 2023)

This release adds numerous major features and indicates the end of HPy’s *alpha* phase. We’ve migrated several key packages to HPy (for a list, see our website <https://hpyproject.org>) and we are now confident that HPy is mature enough for being used as serious extension API. We also plan that the next major release will be 1.0.

#### Major new features

**Support subclasses of built-in types** It is now possible to create pure HPy types that inherit from built-in types like `type` or `float`. This was already possible before but in a very limited way, i.e., by setting `HPyType_Spec.basicsize` to 0. In this case, the type implicitly inherited the basic size of the supertype but that also means that you cannot have a custom C struct. It is now possible inherit from a built-in type **AND** have a custom C struct. For further reference, see `HPyType_Spec.builtin_shape` and `HPyType_BuiltinShape`.

**Support for metaclasses** HPy now supports creating types with metaclasses. This can be done by passing type specification parameter with kind `HPyType_SpecParam_Metaclass` when calling `HPyType_FromSpec()`.

**HPy Hybrid ABI** In addition to *CPython ABI* and *HPy Universal ABI*, we now introduced the Hybrid ABI. The major difference is that whenever you use a legacy API like `HPy_AsPyObject()` or `HPy_FromPyObject()`, the produced binary will then be specific to one interpreter. This was necessary to ensure that universal binaries are really portable and can be used on any HPy-capable interpreter.

**Trace Mode** Similar to the *Debug Mode*, HPy now provides the Trace Mode that can be enabled at runtime and helps analyzing API usage and identifying performance issues.

**Multi-phase Module Initialization** HPy now support multi-phase module initialization which is an important feature in particular needed for two important use cases: (1) module state support (which is planned to be introduced in the next major release), and (2) subinterpreters. We decided to drop support for single-phase module initialization since this makes the API cleaner and easier to use.

**HPy Calling Protocol** This was a big missing piece and is now eventually available. It enables slot `HPy_tp_call`, which can now be used in the HPy type specification. We decided to use a calling convention similar to CPython’s vectorcall calling convention. This is: the arguments are passed in a C array and the keyword argument names are provided as a Python tuple. Before this release, the only way to create a callable type was to set the special method `__call__`. However, this has several disadvantages. In particular, poor performance on CPython (and maybe other implementations) and it was not possible to have specialized call function implementations per object (see `HPy_SetCallFunction()`)

## Added APIs

**Deleting attributes and items** `HPy_DelAttr()`, `HPy_DelAttr_s()`, `HPy_DelItem()`,  
`HPy_DelItem_i()`, `HPy_DelItem_s()`

**Capsule API** `HPyCapsule_New()`, `HPyCapsule_IsValid()`, `HPyCapsule_Get()`,  
`HPyCapsule_Set()`

**Eval API** `HPy_Compile_s()` and `HPy_EvalCode()`

**Formatting helpers** `HPyUnicode_FromFormat()` and `HPyErr_Format()`

**Contextvar API** `HPyContextVar_New()`, `HPyContextVar_Get()`, `HPyContextVar_Set()`

**Unicode API** `HPyUnicode_FromEncodedObject()` and `HPyUnicode_Substring()`

**Dict API** `HPyDict_Keys()` and `HPyDict_Copy()`

**Type API** `HPyType_GetName()` and `HPyType_IsSubtype()`

**Slice API** `HPySlice_Unpack()` and `HPySlice_AdjustIndices()`

**Structseq API** `HPyStructSequence_NewType()`, `HPyStructSequence_New()`

**Call API** `HPy_Call()`, `HPy_CallMethod()`, `HPy_CallMethodTupleDict()`,  
`HPy_CallMethodTupleDict_s()`

**HPy call protocol** `HPy_SetCallFunction()`

## Debug mode

- Detect closing and returning (without dup) of context handles
- Detect invalid usage of stored `HPyContext` \* pointer
- Detect invalid usage of tuple and list builders
- Added Windows support for checking invalid use of raw data pointers (e.g `HPyUnicode_AsUTF8AndSize`) after handle was closed.
- Added support for backtrace on MacOS

## Documentation

- Added incremental *Porting Example*
- Added *HPy Quickstart* guide
- Extended *API Reference*
- Added *HPy Core API Function Index*
- Added possibility to generate examples from tests with argument `--dump-dir` (see *HPy unit tests*)
- Added initial *Contributing* docs

### Incompatible changes to version 0.0.4

- Simplified `HPyDef_*` macros
- Changed macro `HPy_MODINIT` because of multi-phase module init support.
- Replace environment variable `HPY_DEBUG` by `HPY` (see *Debug Mode* or *Trace Mode*).
- Changed signature of `HPyFunc_VARARGS` and `HPyFunc_KEYWORDS` to align with HPy's call protocol calling convention.

### Supported Python versions

- Added Python 3.11 support
- Preliminary Python 3.12 support
- Dropped Python 3.6 support (since EOL)
- Dropped Python 3.7 support (since EOL by June 2023)

### Misc

- Ensure deterministic auto-generation
- Ensure ABI backwards compatibility
  - Explicitly define slot within `HPyContext` of function pointers and handles
  - Compile HPy ABI version into binary and verify at load time
- Added proper support for object members `HPyMember_OBJECT`
- Changed `HPyBytes_AsString()` and `HPyBytes_AS_STRING()` to return `const char *`
- Use fixed-width integers in context functions

### 2.11.2 Version 0.0.4 (May 25th, 2022)

#### New Features/API:

- HPy headers are C++ compliant
- Python 3.10 support
- **HPyField**: References to Python objects that can be stored in raw native memory owned by Python objects.
  - New API functions: `HPyField_Load`, `HPyField_Store`
- **HPyGlobal**: References to Python objects that can be stored into a C global variable.
  - New API functions: `HPyGlobal_Load`, `HPyGlobal_Store`
  - Note: `HPyGlobal` does not allow to share Python objects between (sub)interpreters
- **GIL support** - New API functions: `HPy_ReenterPythonExecution`, `HPy_LeavePythonExecution`
- **Value building support** (`HPy_BuildValue`)
- New type slots
  - `HPy_mp_ass_subscript`, `HPy_mp_length`, `HPy_mp_subscript`
  - `HPy_tp_finalize`

- Other new API functions
  - `HPyErr_SetFromErrnoWithFilename`, `HPyErr_SetFromErrnoWithFilenameObjects`
  - `HPyErr_ExceptionMatches`
  - `HPyErr_WarnEx`
  - `HPyErr_WriteUnraisable`
  - `HPy_Contains`
  - `HPyLong_AsVoidPtr`
  - `HPyLong_AsDouble`
  - `HPyUnicode_AsASCIIString`, `HPyUnicode_DecodeASCII`
  - `HPyUnicode_AsLatin1String`, `HPyUnicode_DecodeLatin1`
  - `HPyUnicode_DecodeFSDefault`, `HPyUnicode_DecodeFSDefaultAndSize`
  - `HPyUnicode_ReadChar`

Debug mode:

- Support activation of debug mode via environment variable `HPY_DEBUG`
- Support capturing stack traces of handle allocations
- Check for invalid use of raw data pointers (e.g `HPyUnicode_AsUTF8AndSize`) after handle was closed.
- Detect invalid handles returned from extension functions
- Detect incorrect closing of handles passed as arguments

Misc Changes:

- Removed unnecessary prefix `"m_"` from fields of `HPyModuleDef` (incompatible change)
- For HPy implementors: new pytest mark for HPy tests assuming synchronous GC

### 2.11.3 Version 0.0.3 (September 22nd, 2021)

This release adds various new API functions (see below) and extends the debug mode with the ability to track closed handles. The default ABI mode now is ‘universal’ for non-CPython implementations. Also, the type definition of `HPyContext` was changed and it’s no longer a pointer type. The name of the HPy dev package was changed to ‘hpy’ (formerly: ‘hpy.devel’). Macro `HPy_CAST` was replaced by `HPy_AsStruct`.

New features:

- Added helper `HPyHelpers_AddType` for creating new types
- Support format specifier ‘s’ in `HPyArg_Parse`
- Added API functions: `HPy_Is`, `HPy_AsStructLegacy` (for legacy types), `HPyBytes_FromStringAndSize`, `HPyErr_NewException`, `HPyErr_NewExceptionWithDoc`, `HPyUnicode_AsUTF8AndSize`, `HPyUnicode_DecodeFSDefault`, `HPyImport_ImportModule`
- Debug mode: Implemented tracking of closed handles
- Debug mode: Add hook for invalid handle access

Bug fixes:

- Distinguish between pure and legacy types
- Fix Sphinx doc errors



## INDICES AND TABLES

- `genindex`
- `modindex`
- `search`





## Symbols

\_HPyContext\_s (C struct), 50  
 \_HPyContext\_s.abi\_version (C member), 50  
 \_HPyContext\_s.h\_ArithmeticError (C member), 50  
 \_HPyContext\_s.h\_AssertionError (C member), 50  
 \_HPyContext\_s.h\_AttributeError (C member), 50  
 \_HPyContext\_s.h\_BaseException (C member), 50  
 \_HPyContext\_s.h\_BaseObjectType (C member), 52  
 \_HPyContext\_s.h\_BlockingIOError (C member), 51  
 \_HPyContext\_s.h\_BoolType (C member), 52  
 \_HPyContext\_s.h\_BrokenPipeError (C member), 51  
 \_HPyContext\_s.h\_BufferError (C member), 50  
 \_HPyContext\_s.h\_Builtins (C member), 52  
 \_HPyContext\_s.h\_BytesType (C member), 52  
 \_HPyContext\_s.h\_BytesWarning (C member), 52  
 \_HPyContext\_s.h\_CapsuleType (C member), 52  
 \_HPyContext\_s.h\_ChildProcessError (C member), 51  
 \_HPyContext\_s.h\_ComplexType (C member), 52  
 \_HPyContext\_s.h\_ConnectionAbortedError (C member), 51  
 \_HPyContext\_s.h\_ConnectionError (C member), 51  
 \_HPyContext\_s.h\_ConnectionRefusedError (C member), 51  
 \_HPyContext\_s.h\_ConnectionResetError (C member), 51  
 \_HPyContext\_s.h\_DeprecationWarning (C member), 52  
 \_HPyContext\_s.h\_EOFError (C member), 50  
 \_HPyContext\_s.h\_Ellipsis (C member), 50  
 \_HPyContext\_s.h\_Exception (C member), 50  
 \_HPyContext\_s.h\_False (C member), 50  
 \_HPyContext\_s.h\_FileExistsError (C member), 51  
 \_HPyContext\_s.h\_FileNotFoundError (C member), 51  
 \_HPyContext\_s.h\_FloatType (C member), 52  
 \_HPyContext\_s.h\_FloatingPointError (C member), 50  
 \_HPyContext\_s.h\_FutureWarning (C member), 52  
 \_HPyContext\_s.h\_GeneratorExit (C member), 50  
 \_HPyContext\_s.h\_ImportError (C member), 50  
 \_HPyContext\_s.h\_ImportWarning (C member), 52  
 \_HPyContext\_s.h\_IndentationError (C member), 51  
 \_HPyContext\_s.h\_IndexError (C member), 50  
 \_HPyContext\_s.h\_InterruptedError (C member), 51  
 \_HPyContext\_s.h\_IsADirectoryError (C member), 51  
 \_HPyContext\_s.h\_KeyError (C member), 50  
 \_HPyContext\_s.h\_KeyboardInterrupt (C member), 51  
 \_HPyContext\_s.h\_ListType (C member), 52  
 \_HPyContext\_s.h\_LongType (C member), 52  
 \_HPyContext\_s.h\_LookupError (C member), 50  
 \_HPyContext\_s.h\_MemoryError (C member), 51  
 \_HPyContext\_s.h\_MemoryViewType (C member), 52  
 \_HPyContext\_s.h\_ModuleNotFoundError (C member), 50  
 \_HPyContext\_s.h\_NameError (C member), 51  
 \_HPyContext\_s.h\_None (C member), 50  
 \_HPyContext\_s.h\_NotADirectoryError (C member), 51  
 \_HPyContext\_s.h\_NotImplemented (C member), 50  
 \_HPyContext\_s.h\_NotImplementedError (C member), 51  
 \_HPyContext\_s.h\_OSError (C member), 50  
 \_HPyContext\_s.h\_OverflowError (C member), 51

\_HPyContext\_s.h\_PendingDeprecationWarning  
     (*C member*), 52  
 \_HPyContext\_s.h\_PermissionError (*C mem-*  
     *ber*), 51  
 \_HPyContext\_s.h\_ProcessLookupError (*C*  
     *member*), 51  
 \_HPyContext\_s.h\_RecursionError (*C mem-*  
     *ber*), 51  
 \_HPyContext\_s.h\_ReferenceError (*C mem-*  
     *ber*), 51  
 \_HPyContext\_s.h\_ResourceWarning (*C mem-*  
     *ber*), 52  
 \_HPyContext\_s.h\_RuntimeError (*C member*),  
     51  
 \_HPyContext\_s.h\_RuntimeWarning (*C mem-*  
     *ber*), 52  
 \_HPyContext\_s.h\_SliceType (*C member*), 52  
 \_HPyContext\_s.h\_StopAsyncIteration (*C*  
     *member*), 50  
 \_HPyContext\_s.h\_StopIteration (*C member*),  
     50  
 \_HPyContext\_s.h\_SyntaxError (*C member*), 51  
 \_HPyContext\_s.h\_SyntaxWarning (*C member*),  
     52  
 \_HPyContext\_s.h\_SystemError (*C member*), 51  
 \_HPyContext\_s.h\_SystemExit (*C member*), 51  
 \_HPyContext\_s.h\_TabError (*C member*), 51  
 \_HPyContext\_s.h\_TimeoutError (*C member*),  
     51  
 \_HPyContext\_s.h\_True (*C member*), 50  
 \_HPyContext\_s.h\_TupleType (*C member*), 52  
 \_HPyContext\_s.h\_TypeError (*C member*), 51  
 \_HPyContext\_s.h\_TypeType (*C member*), 52  
 \_HPyContext\_s.h\_UnboundLocalError (*C*  
     *member*), 51  
 \_HPyContext\_s.h\_UnicodeDecodeError (*C*  
     *member*), 51  
 \_HPyContext\_s.h\_UnicodeEncodeError (*C*  
     *member*), 51  
 \_HPyContext\_s.h\_UnicodeError (*C member*),  
     51  
 \_HPyContext\_s.h\_UnicodeTranslateError  
     (*C member*), 51  
 \_HPyContext\_s.h\_UnicodeType (*C member*), 52  
 \_HPyContext\_s.h\_UnicodeWarning (*C mem-*  
     *ber*), 52  
 \_HPyContext\_s.h\_UserWarning (*C member*), 52  
 \_HPyContext\_s.h\_ValueError (*C member*), 51  
 \_HPyContext\_s.h\_Warning (*C member*), 52  
 \_HPyContext\_s.h\_ZeroDivisionError (*C*  
     *member*), 51  
 \_HPyContext\_s.name (*C member*), 50

## C

CPython ABI, 8

## H

HPy Hybrid ABI, 8  
 HPy Universal ABI, 8  
 HPy\_ASCII (*C function*), 53  
 HPy\_BuildValue (*C function*), 99  
 HPy\_Bytes (*C function*), 53  
 HPy\_Call (*C function*), 63  
 HPy\_CallMethod (*C function*), 63  
 HPy\_CallMethodTupleDict (*C function*), 108  
 HPy\_CallMethodTupleDict\_s (*C function*), 108  
 HPy\_CallTupleDict (*C function*), 64  
 HPy\_Compile\_s (*C function*), 69  
 HPy\_DelAttr (*C function*), 104  
 HPy\_DelAttr\_s (*C function*), 105  
 HPy\_DelItem (*C function*), 53  
 HPy\_DelItem\_i (*C function*), 53  
 HPy\_DelItem\_s (*C function*), 53  
 HPY\_EMBEDDED\_MODULES (*C macro*), 58  
 HPy\_EvalCode (*C function*), 69  
 HPy\_FatalError (*C function*), 67  
 HPy\_GetAttr (*C function*), 52  
 HPy\_GetAttr\_s (*C function*), 52  
 HPy\_GetItem (*C function*), 52  
 HPy\_GetItem\_i (*C function*), 53  
 HPy\_GetItem\_s (*C function*), 52  
 HPy\_HasAttr (*C function*), 52  
 HPy\_HasAttr\_s (*C function*), 52  
 HPy\_Hash (*C function*), 53  
 HPY\_INLINE\_HELPERS\_H (*C macro*), 104  
 HPy\_Is (*C function*), 53  
 HPy\_IsTrue (*C function*), 52  
 HPy\_LeavePythonExecution (*C function*), 66  
 HPY\_MOD\_EMBEDDABLE (*C macro*), 58  
 HPy\_MODINIT (*C macro*), 58  
 HPy\_ReenterPythonExecution (*C function*), 66  
 HPy\_Repr (*C function*), 53  
 HPy\_RichCompare (*C function*), 53  
 HPy\_RichCompareBool (*C function*), 53  
 HPy\_SetAttr (*C function*), 52  
 HPy\_SetAttr\_s (*C function*), 52  
 HPy\_SetCallFunction (*C function*), 53  
 HPy\_SetItem (*C function*), 53  
 HPy\_SetItem\_i (*C function*), 53  
 HPy\_SetItem\_s (*C function*), 53  
 HPy\_SourceKind (*C enum*), 69  
 HPy\_SourceKind.HPy\_SourceKind\_Expr (*C*  
     *enumerator*), 69  
 HPy\_SourceKind.HPy\_SourceKind\_File (*C*  
     *enumerator*), 69  
 HPy\_SourceKind.HPy\_SourceKind\_Single (*C*  
     *enumerator*), 69

- 
- HPy\_Str (C function), 53
  - HPy\_TPFLAGS\_BASETYPE (C macro), 57
  - HPy\_TPFLAGS\_DEFAULT (C macro), 57
  - HPy\_TPFLAGS\_HAVE\_GC (C macro), 57
  - HPy\_Type (C function), 53
  - HPy\_TypeCheck (C function), 53
  - HPyArg\_Parse (C function), 95
  - HPyArg\_ParseKeywords (C function), 96
  - HPyArg\_ParseKeywordsDict (C function), 97
  - HPyBool\_FromLong (C function), 107
  - HPyDef (C struct), 59
  - HPyDef.kind (C member), 59
  - HPyDef\_CALL\_FUNCTION (C macro), 63
  - HPyDef\_GET (C macro), 62
  - HPyDef\_GETSET (C macro), 62
  - HPyDef\_Kind (C enum), 59
  - HPyDef\_Kind.HPyDef\_Kind\_GetSet (C enumerator), 59
  - HPyDef\_Kind.HPyDef\_Kind\_Member (C enumerator), 59
  - HPyDef\_Kind.HPyDef\_Kind\_Meth (C enumerator), 59
  - HPyDef\_Kind.HPyDef\_Kind\_Slot (C enumerator), 59
  - HPyDef\_MEMBER (C macro), 62
  - HPyDef\_METH (C macro), 61
  - HPyDef\_SET (C macro), 62
  - HPyDef\_SLOT (C macro), 61
  - HPyDict\_Check (C function), 65
  - HPyDict\_Copy (C function), 66
  - HPyDict\_Keys (C function), 65
  - HPyDict\_New (C function), 65
  - HPyErr\_Clear (C function), 67
  - HPyErr\_ExceptionMatches (C function), 67
  - HPyErr\_NewException (C function), 67
  - HPyErr\_NewExceptionWithDoc (C function), 67
  - HPyErr\_NoMemory (C function), 67
  - HPyErr\_Occurred (C function), 67
  - HPyErr\_SetFromErrno (C function), 104
  - HPyErr\_SetFromErrnoWithFilename (C function), 66
  - HPyErr\_SetFromErrnoWithFilenameObject (C function), 104
  - HPyErr\_SetFromErrnoWithFilenameObjects (C function), 67
  - HPyErr\_SetObject (C function), 67
  - HPyErr\_SetString (C function), 67
  - HPyErr\_WarnEx (C function), 67
  - HPyErr\_WriteUnraisable (C function), 67
  - HPyField\_Load (C function), 64
  - HPyField\_Store (C function), 64
  - HPyGetSet (C struct), 61
  - HPyGetSet.closure (C member), 61
  - HPyGetSet.doc (C member), 61
  - HPyGetSet.getter\_cpy\_trampoline (C member), 61
  - HPyGetSet.getter\_impl (C member), 61
  - HPyGetSet.name (C member), 61
  - HPyGetSet.setter\_cpy\_trampoline (C member), 61
  - HPyGetSet.setter\_impl (C member), 61
  - HPyGlobal\_Load (C function), 65
  - HPyGlobal\_Store (C function), 64
  - HPyHelpers\_AddType (C function), 102
  - HPyHelpers\_PackArgsAndKeywords (C function), 103
  - HPyListBuilder\_Build (C function), 68
  - HPyListBuilder\_Cancel (C function), 68
  - HPyListBuilder\_New (C function), 68
  - HPyListBuilder\_Set (C function), 68
  - HPyLong\_AsLong (C function), 105
  - HPyLong\_AsLongLong (C function), 106
  - HPyLong\_AsUnsignedLong (C function), 106
  - HPyLong\_AsUnsignedLongLong (C function), 107
  - HPyLong\_AsUnsignedLongLongMask (C function), 107
  - HPyLong\_AsUnsignedLongMask (C function), 106
  - HPyLong\_FromLong (C function), 105
  - HPyLong\_FromLongLong (C function), 105
  - HPyLong\_FromUnsignedLong (C function), 105
  - HPyLong\_FromUnsignedLongLong (C function), 105
  - HPyMember (C struct), 60
  - HPyMember.doc (C member), 61
  - HPyMember.name (C member), 60
  - HPyMember.offset (C member), 60
  - HPyMember.readonly (C member), 61
  - HPyMember.type (C member), 60
  - HPyMember\_FieldType (C enum), 60
  - HPyMember\_FieldType.HPyMember\_BOOL (C enumerator), 60
  - HPyMember\_FieldType.HPyMember\_BYTE (C enumerator), 60
  - HPyMember\_FieldType.HPyMember\_CHAR (C enumerator), 60
  - HPyMember\_FieldType.HPyMember\_DOUBLE (C enumerator), 60
  - HPyMember\_FieldType.HPyMember\_FLOAT (C enumerator), 60
  - HPyMember\_FieldType.HPyMember\_HPYSIZET (C enumerator), 60
  - HPyMember\_FieldType.HPyMember\_INT (C enumerator), 60
  - HPyMember\_FieldType.HPyMember\_LONG (C enumerator), 60
  - HPyMember\_FieldType.HPyMember\_LONGLONG (C enumerator), 60

HPyMember\_FieldType.HPyMember\_NONE (C enumerator), 60

HPyMember\_FieldType.HPyMember\_OBJECT (C enumerator), 60

HPyMember\_FieldType.HPyMember\_OBJECT\_EX (C enumerator), 60

HPyMember\_FieldType.HPyMember\_SHORT (C enumerator), 60

HPyMember\_FieldType.HPyMember\_STRING (C enumerator), 60

HPyMember\_FieldType.HPyMember\_STRING\_INPLACE (C enumerator), 60

HPyMember\_FieldType.HPyMember\_UBYTE (C enumerator), 60

HPyMember\_FieldType.HPyMember\_UINT (C enumerator), 60

HPyMember\_FieldType.HPyMember\_ULONG (C enumerator), 60

HPyMember\_FieldType.HPyMember\_ULONGLONG (C enumerator), 60

HPyMember\_FieldType.HPyMember\_USHORT (C enumerator), 60

HPyMeth (C struct), 59

HPyMeth.cpy\_trampoline (C member), 60

HPyMeth.doc (C member), 60

HPyMeth.impl (C member), 59

HPyMeth.name (C member), 59

HPyMeth.signature (C member), 60

HPyModuleDef (C struct), 58

HPyModuleDef.defines (C member), 58

HPyModuleDef.doc (C member), 58

HPyModuleDef.globals (C member), 58

HPyModuleDef.legacy\_methods (C member), 58

HPyModuleDef.size (C member), 58

HPySlice\_AdjustIndices (C function), 107

HPySlot (C struct), 59

HPySlot.cpy\_trampoline (C member), 59

HPySlot.impl (C member), 59

HPySlot.slot (C member), 59

HPyStructSequence\_Desc (C struct), 101

HPyStructSequence\_Desc.doc (C member), 101

HPyStructSequence\_Desc.fields (C member), 101

HPyStructSequence\_Desc.name (C member), 101

HPyStructSequence\_Field (C struct), 101

HPyStructSequence\_Field.doc (C member), 101

HPyStructSequence\_Field.name (C member), 101

HPyStructSequence\_New (C function), 102

HPyStructSequence\_NewType (C function), 102

HPyStructSequence\_UnnamedField (C var), 102

HPyTuple\_Pack (C function), 104

HPyTupleBuilder\_Build (C function), 68

HPyTupleBuilder\_Cancel (C function), 68

HPyTupleBuilder\_New (C function), 67

HPyTupleBuilder\_Set (C function), 67

HPyType\_BuiltinShape (C enum), 55

HPyType\_BuiltinShape.HPyType\_BuiltinShape\_Float (C enumerator), 55

HPyType\_BuiltinShape.HPyType\_BuiltinShape\_Legacy (C enumerator), 55

HPyType\_BuiltinShape.HPyType\_BuiltinShape\_List (C enumerator), 55

HPyType\_BuiltinShape.HPyType\_BuiltinShape\_Long (C enumerator), 55

HPyType\_BuiltinShape.HPyType\_BuiltinShape\_Object (C enumerator), 55

HPyType\_BuiltinShape.HPyType\_BuiltinShape\_Tuple (C enumerator), 55

HPyType\_BuiltinShape.HPyType\_BuiltinShape\_Type (C enumerator), 55

HPyType\_BuiltinShape.HPyType\_BuiltinShape\_Unicode (C enumerator), 55

HPyType\_FromSpec (C function), 57

HPyType\_GetName (C function), 57

HPyType\_HELPERS (C macro), 56

HPyType\_IsSubtype (C function), 57

HPyType\_LEGACY\_HELPERS (C macro), 56

HPyType\_Spec (C struct), 54

HPyType\_Spec.basicsize (C member), 54

HPyType\_Spec.builtin\_shape (C member), 54

HPyType\_Spec.defines (C member), 55

HPyType\_Spec.doc (C member), 55

HPyType\_Spec.flags (C member), 54

HPyType\_Spec.itemsize (C member), 54

HPyType\_Spec.legacy\_slots (C member), 54

HPyType\_Spec.name (C member), 54

HPyType\_SpecParam (C struct), 55

HPyType\_SpecParam.kind (C member), 55

HPyType\_SpecParam.object (C member), 55

HPyType\_SpecParam\_Kind (C enum), 56

HPyType\_SpecParam\_Kind.HPyType\_SpecParam\_Base (C enumerator), 56

HPyType\_SpecParam\_Kind.HPyType\_SpecParam\_BasesTuple (C enumerator), 56

HPyType\_SpecParam\_Kind.HPyType\_SpecParam\_Metaclass (C enumerator), 56

## P

Python Enhancement Proposals

PEP 3149, 7